

Alice Ward Library Carriage House Rehabilitation

27 Park St. | Canaan, VT 05903

ARCHITECT

R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS
CONTACT: Ryan Edwards, AIA
52 State St., 2nd Fl.
Montpelier, VT 05602
(802) 232-2628
redwards@redwardsandcompany.com

STRUCTURAL ENGINEER

Engineering Ventures, PC
CONTACT: Bob Neeld, P.E.
Marc Nummelin, E.I.T.
208 Flynn Ave., Suite 2A
Burlington, VT 05401
(802) 863-6225
bobn@engineeringventures.com
marcn@engineeringventures.com

MEP ENGINEER

DuBois & King, Inc.
CONTACT: Joe Coutermarsh, P.E. (Mechanical, Plumbing)
Shawn Proulx, P.E. (Electrical)
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043
jcoutermarsh@dubois-king.com
sproulx@dubois-king.com

OWNER

Alice M. Ward Memorial Library (Town of Canaan)

CONTACT: Nancy Petro (Alice M. Ward Library Board of Trustees)
Georgiana Carr (Alice M. Ward Library Board of Trustees)
27 Park St.
Canaan, VT 05903
(802) 266-7135
alice.ward.library@gmail.com

DEVELOPMENT CONSULTANT

North Hill Solutions, Ltd. Co.
CONTACT: Peder Rude
1623 Potter Hill Rd.
Readsboro, VT 05350
(802) 829-2900
hello@northhill.solutions

HISTORIC PRESERVATION CONSULTANT

106 Associates
CONTACT: Scott Newman
11 Ward St.
Burlington, VT 05401
(802) 777-1572
scottnewman@106associates.com

BID SET

01.20.26

GENERAL

- A.000 COVER SHEET
- A.001 GENERAL INFORMATION
- A.002 LIFE SAFETY PLANS

STRUCTURAL

- S-2 STRUCTURAL : BASIS OF DESIGN
- S-3 STRUCTURAL : SCHEDULES + TABLES
- S-4 STRUCTURAL : FOUNDATION PLAN + 1ST FLOOR FRAMING PLAN
- S-5 STRUCTURAL : 2ND FLOOR FRAMING PLAN + ROOF FRAMING COLLAR TIE PLAN
- S-6 STRUCTURAL : ROOF FRAMING PLAN + CUPOLA FRAMING PLAN
- S-7 STRUCTURAL : DETAILS
- S-8 STRUCTURAL : STAIR AND ELEVATOR DETAILS

ARCHITECTURAL

- AD.101 DEMOLITION PLANS : BASEMENT + 1ST FLOOR
- AD.102 DEMOLITION PLANS : 2ND FLOOR
- A.100 CONSTRUCTION PLANS : FOUNDATION + 1ST FLOOR
- A.101 CONSTRUCTION PLANS : 2ND FLOOR
- A.110 INTERIOR RENDERINGS
- A.201 EXTERIOR ELEVATIONS
- A.202 EXTERIOR ELEVATIONS
- A.210 EXTERIOR RENDERINGS
- A.601 SCHEDULES
- A.602 SCHEDULES

PLUMBING [DATED 09.30.25]

- P0.1 PLUMBING LEGENDS + NOTES
- P1.1 BASEMENT PLAN - PLUMBING
- P1.2 1ST + 2ND FLOOR PLAN - PLUMBING
- P5.1 PLUMBING DETAILS

MECHANICAL [DATED 09.30.25]

- M0.1 MECHANICAL LEGEND AND NOTES
- M1.1 BASEMENT PLAN - DUCTWORK
- M1.2 1ST FLOOR PLAN - DUCTWORK
- M1.3 2ND FLOOR PLAN - DUCTWORK
- M5.1 MECHANICAL DETAILS
- M6.1 MECHANICAL SCHEDULES
- M6.2 MECHANICAL SPECIFICATIONS
- M6.3 MECHANICAL SPECIFICATIONS

ELECTRICAL [DATED 09.30.25]

- E0.1 ELECTRICAL LEGENDS + NOTES
- E1.1 BASEMENT FLOOR PLAN - LIGHTING
- E1.2 FIRST FLOOR PLAN - LIGHTING
- E1.3 SECOND FLOOR PLAN - LIGHTING
- E1.4 BASEMENT FLOOR PLAN - POWER
- E1.5 FIRST FLOOR PLAN - POWER
- E1.6 SECOND FLOOR PLAN - POWER
- E5.1 ELECTRICAL DETAILS
- E5.2 ELECTRICAL DETAILS
- E6.1 ELECTRICAL SCHEDULES



PROJECT
**Alice Ward Library Carriage
House Rehabilitation**

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM
STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave., Suite 2A
Burlington, VT 05401
(802) 863-7225

MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

RELEASE + REVISION LOG		
MARK	DESCRIPTION	DATE
	BID SET	01.20.26


PROJECT NORTH

DRAWING NAME
COVER SHEET

DRAWN	RE	DATE	01.20.26
CHECKED		SCALE	

DRAWING NUMBER

A.000



GENERAL BID NOTES	
<ol style="list-style-type: none"> THE CONTRACTOR SHALL VISIT THE SITE PRIOR TO BIDDING AND CAREFULLY EXAMINE THE ENTIRE SET OF DRAWINGS AND SPECIFICATIONS SO AS TO BE INFORMED OF ALL CONDITIONS AFFECTING THE EXECUTION OF THE WORK. BY SUBMITTING A BID, THE CONTRACTOR AGREES AND WARRANTS THAT THEY HAVE EXAMINED THE EXISTING CONDITIONS, DRAWINGS, AND ALL SPECIFIED CONSTRUCTION, MATERIALS, FINISHES, AND PRODUCTS, AND HAS FOUND THEM WHOLLY ADEQUATE FOR COMPLETE EXECUTION OF THE WORK. BY SUBMITTING A BID, THE CONTRACTOR ACKNOWLEDGES THAT THEY UNDERSTAND THE FULL SCOPE OF WORK AS IT PERTAINS TO THE DRAWINGS AND ALL SPECIFIED CONSTRUCTION, MATERIALS, FINISHES, AND PRODUCTS; NO ADDITIONAL CHARGES WILL BE ALLOWED DUE TO THE MISUNDERSTANDING OF THE DRAWINGS AND SPECIFICATIONS BY THE BIDDER. THE CONTRACTOR SHALL REVIEW AND BECOME FAMILIAR WITH "THE SECRETARY OF THE INTERIOR'S STANDARDS FOR REHABILITATION" AND TO PROVIDE FOR ANY NECESSARY MEANS AND METHODS, CONFORMANCE TO THESE STANDARDS IN THE EXECUTION OF THE WORK AS OUTLINED IN THE DRAWINGS AND SPECIFIED CONSTRUCTION, MATERIALS, FINISHES, AND PRODUCTS. 	

QUALITY REQUIREMENTS	
<p>QUALITY MONITORING: MONITOR QUALITY CONTROL OVER SUPPLIERS, MANUFACTURERS, PRODUCTS, SERVICES, SITE CONDITIONS, AND WORKMANSHIP TO PRODUCE WORK OF SPECIFIED QUALITY. PERFORM QUALITY CONTROL PROCEDURES AND INSPECTIONS DURING INSTALLATION.</p> <p>STANDARDS: COMPLY WITH SPECIFIED STANDARDS AS MINIMUM QUALITY FOR THE WORK EXCEPT WHERE MORE STRINGENT TOLERANCES, CODES, OR SPECIFIED REQUIREMENTS INDICATE HIGHER STANDARDS OR MORE PRECISE WORKMANSHIP.</p> <p>TOLERANCES: MONITOR FABRICATION AND INSTALLATION TOLERANCE CONTROL OF PRODUCTS TO PRODUCE ACCEPTABLE WORK. DO NOT PERMIT TOLERANCES TO ACCUMULATE. COMPLY WITH MANUFACTURERS' TOLERANCES.</p> <p>REFERENCE STANDARDS: FOR PRODUCTS OR WORKMANSHIP SPECIFIED BY ASSOCIATION, TRADE, OR OTHER CONSENSUS STANDARDS, COMPLY WITH REQUIREMENTS OF THE STANDARD, EXCEPT WHEN MORE RIGID REQUIREMENTS ARE SPECIFIED OR ARE REQUIRED BY APPLICABLE CODES.</p>	

APPLICABLE CODES	
<p>VERMONT FIRE AND BUILDING SAFETY CODE (2025) -NFPA 101, LIFE SAFETY CODE (2021) (Amended) -NFPA 1, FIRE CODE (2021) (Amended) -IEBC, INTERNATIONAL EXISTING BUILDING CODE (2021) (Structural Requirements Only)</p> <p>VERMONT ELECTRICAL SAFETY RULES (2025) -NFPA 70, NATIONAL ELECTRICAL CODE (2023) (Amended)</p> <p>VERMONT PLUMBING RULES (2025) -IPC, INTERNATIONAL PLUMBING CODE (2024) (Amended)</p> <p>VERMONT ACCESS RULES (2012) -ADA STANDARDS FOR ACCESSIBLE DESIGN (2010) (Amended)</p> <p>VERMONT COMMERCIAL BUILDING ENERGY STANDARDS (2024)</p>	

ITEM	PRODUCT DATA	SHOP DRAWINGS	SAMPLES ¹	OTHER/NOTES
METAL FABRICATIONS		X		
MILLWORK	X*	X		*PROVIDE PRODUCT DATA FOR HARDWARE
DOORS	X	X		
DOOR HARDWARE	X			
WINDOWS	X	X		
TILE	X		X	
WOOD FLOORING			X	
PAINTS / STAINS / CLEAR FINISHES	X		X	
SPECIALTIES / TOILET ACCESSORIES	X			
PLUMBING FIXTURES + EQUIPMENT	X			
HVAC EQUIPMENT	X			
LIGHTING FIXTURES + EQUIPMENT	X			

1. SAMPLES PROVIDED SHOULD BE OF A SIZE SUITABLE FOR OWNER APPROVAL (I.E. CHAINRING SAMPLES WILL NOT BE ACCEPTED)
2. SEE SPECIFICATIONS (A.010) FOR OTHER SPECIFIC DIVISION SUBMITTAL REQUIREMENTS

SUBMITTAL SCHEDULE	
ITEM	PRODUCT DATA
METAL FABRICATIONS	X
MILLWORK	X*
DOORS	X
DOOR HARDWARE	X
WINDOWS	X
TILE	X
WOOD FLOORING	
PAINTS / STAINS / CLEAR FINISHES	X
SPECIALTIES / TOILET ACCESSORIES	X
PLUMBING FIXTURES + EQUIPMENT	X
HVAC EQUIPMENT	X
LIGHTING FIXTURES + EQUIPMENT	X

1. SAMPLES PROVIDED SHOULD BE OF A SIZE SUITABLE FOR OWNER APPROVAL (I.E. CHAINRING SAMPLES WILL NOT BE ACCEPTED)
2. SEE SPECIFICATIONS (A.010) FOR OTHER SPECIFIC DIVISION SUBMITTAL REQUIREMENTS

SUBMITTAL SCHEDULE	
ITEM	PRODUCT DATA
METAL FABRICATIONS	X
MILLWORK	X*
DOORS	X
DOOR HARDWARE	X
WINDOWS	X
TILE	X
WOOD FLOORING	
PAINTS / STAINS / CLEAR FINISHES	X
SPECIALTIES / TOILET ACCESSORIES	X
PLUMBING FIXTURES + EQUIPMENT	X
HVAC EQUIPMENT	X
LIGHTING FIXTURES + EQUIPMENT	X

1. SAMPLES PROVIDED SHOULD BE OF A SIZE SUITABLE FOR OWNER APPROVAL (I.E. CHAINRING SAMPLES WILL NOT BE ACCEPTED)
2. SEE SPECIFICATIONS (A.010) FOR OTHER SPECIFIC DIVISION SUBMITTAL REQUIREMENTS

SUBMITTAL SCHEDULE	
ITEM	PRODUCT DATA
METAL FABRICATIONS	X
MILLWORK	X*
DOORS	X
DOOR HARDWARE	X
WINDOWS	X
TILE	X
WOOD FLOORING	
PAINTS / STAINS / CLEAR FINISHES	X
SPECIALTIES / TOILET ACCESSORIES	X
PLUMBING FIXTURES + EQUIPMENT	X
HVAC EQUIPMENT	X
LIGHTING FIXTURES + EQUIPMENT	X

1. SAMPLES PROVIDED SHOULD BE OF A SIZE SUITABLE FOR OWNER APPROVAL (I.E. CHAINRING SAMPLES WILL NOT BE ACCEPTED)
2. SEE SPECIFICATIONS (A.010) FOR OTHER SPECIFIC DIVISION SUBMITTAL REQUIREMENTS

SUBMITTAL SCHEDULE	
ITEM	PRODUCT DATA
METAL FABRICATIONS	X
MILLWORK	X*
DOORS	X
DOOR HARDWARE	X
WINDOWS	X
TILE	X
WOOD FLOORING	
PAINTS / STAINS / CLEAR FINISHES	X
SPECIALTIES / TOILET ACCESSORIES	X
PLUMBING FIXTURES + EQUIPMENT	X
HVAC EQUIPMENT	X
LIGHTING FIXTURES + EQUIPMENT	X

1. SAMPLES PROVIDED SHOULD BE OF A SIZE SUITABLE FOR OWNER APPROVAL (I.E. CHAINRING SAMPLES WILL NOT BE ACCEPTED)
2. SEE SPECIFICATIONS (A.010) FOR OTHER SPECIFIC DIVISION SUBMITTAL REQUIREMENTS

SUBMITTAL SCHEDULE	
ITEM	PRODUCT DATA
METAL FABRICATIONS	X
MILLWORK	X*
DOORS	X
DOOR HARDWARE	X
WINDOWS	X
TILE	X
WOOD FLOORING	
PAINTS / STAINS / CLEAR FINISHES	X
SPECIALTIES / TOILET ACCESSORIES	X
PLUMBING FIXTURES + EQUIPMENT	X
HVAC EQUIPMENT	X
LIGHTING FIXTURES + EQUIPMENT	X

1. SAMPLES PROVIDED SHOULD BE OF A SIZE SUITABLE FOR OWNER APPROVAL (I.E. CHAINRING SAMPLES WILL NOT BE ACCEPTED)
2. SEE SPECIFICATIONS (A.010) FOR OTHER SPECIFIC DIVISION SUBMITTAL REQUIREMENTS

SUBMITTAL SCHEDULE	
ITEM	PRODUCT DATA
METAL FABRICATIONS	X
MILLWORK	X*
DOORS	X
DOOR HARDWARE	X
WINDOWS	X
TILE	X
WOOD FLOORING	
PAINTS / STAINS / CLEAR FINISHES	X
SPECIALTIES / TOILET ACCESSORIES	X
PLUMBING FIXTURES + EQUIPMENT	X
HVAC EQUIPMENT	X
LIGHTING FIXTURES + EQUIPMENT	X

1. SAMPLES PROVIDED SHOULD BE OF A SIZE SUITABLE FOR OWNER APPROVAL (I.E. CHAINRING SAMPLES WILL NOT BE ACCEPTED)
2. SEE SPECIFICATIONS (A.010) FOR OTHER SPECIFIC DIVISION SUBMITTAL REQUIREMENTS

SUBMITTAL SCHEDULE	
ITEM	PRODUCT DATA
METAL FABRICATIONS	X
MILLWORK	X*
DOORS	X
DOOR HARDWARE	X
WINDOWS	X
TILE	X
WOOD FLOORING	
PAINTS / STAINS / CLEAR FINISHES	X
SPECIALTIES / TOILET ACCESSORIES	X
PLUMBING FIXTURES + EQUIPMENT	X
HVAC EQUIPMENT	X
LIGHTING FIXTURES + EQUIPMENT	X

LIFE SAFETY PLAN KEY

	EXIT ACCESS OR EXIT DISCHARGE
	MEANS OF EGRESS PATH
	EGRESS CAPACITY - LEVEL COMPONENTS (DOORS)
	*CLEAR WIDTH: DOORS (NEW): THE MEASUREMENT BETWEEN THE FACE OF THE OPEN DOOR LEAF OPEN 90 DEGREES AND THE STOP OF THE FRAME
	DOORS (EXISTING): THE MEASUREMENT BETWEEN THE FACE OF THE OPEN DOOR LEAF IN THE FULLY OPEN POSITION AND THE STOP OF THE FRAME
	EGRESS CAPACITY - STAIRWAYS
	CLEAR WIDTH (IN.)
	CALCULATED EGRESS CAPACITY (CLEAR WIDTH (IN.)/0.2 IN.)
	RATED ENCLOSURES
	1 HOUR RATED ENCLOSURE
	ALL DOORS WITHIN RATED PARTITIONS FORMING A RATED ENCLOSURE SHALL BE 1-HOUR (60-MIN.) RATED PER NFPA 101, TABLE 8.3.3.2.



PROJECT Alice Ward Library Carriage House Rehabilitation

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM
STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave, Suite 2A
Burlington, VT 05401
(802) 863-7225


MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

RELEASE + REVISION LOG
MARK DESCRIPTION DATE
BID SET 01.20.26

PROJECT NORTH



DRAWING NAME
LIFE SAFETY PLANS

DRAWN RE DATE 01.20.26
CHECKED SCALE
DRAWING NUMBER

A.002


BUILDING OCCUPANCY SUMMARY

BASEMENT MAX. OCCUPANCY	1 PERSONS
1ST FLOOR MAX. OCCUPANCY	14 PERSONS
2ND FLOOR MAX. OCCUPANCY	25 PERSONS
TOTAL BUILDING MAX. OCCUPANCY 40 PERSONS	

1ST FLOOR OCCUPANCY SUMMARY

OCCUPANCY TYPE	AREA + OCCUPANCY LOAD
ASSEMBLY - LIBRARY READING ROOM	AREA: 333 SF (NET) CALCULATED MAX. OCCUPANCY: 7 (333 SF / 50)
ASSEMBLY - LESS CONCENTRATED USE, WITHOUT FIXED SEATING	AREA: 266 SF (NET) CALCULATED MAX. OCCUPANCY: 18 (266 SF / 15)


1ST FLOOR TOTAL CALCULATED MAX. OCCUPANCY: 14 PERSONS



2ND FLOOR OCCUPANCY SUMMARY

OCCUPANCY TYPE	AREA + OCCUPANCY LOAD
ASSEMBLY - LIBRARY READING ROOM	AREA: 333 SF (NET)
ASSEMBLY - LESS CONCENTRATED USE, WITHOUT FIXED SEATING	AREA: 266 SF (NET)

2ND FLOOR TOTAL CALCULATED MAX. OCCUPANCY: 25 PERSONS



3 LIFE SAFETY PLAN : 2ND FLOOR

SCALE: 3/16" = 1'-0"


2 LIFE SAFETY PLAN : 1ST FLOOR

SCALE: 3/16" = 1'-0"

BASEMENT OCCUPANCY SUMMARY


OCCUPANCY TYPE	AREA + OCCUPANCY LOAD
STORAGE	AREA: 856 SF (GROSS) CALCULATED MAX. OCCUPANCY: 1 (856 SF / 500)

BASEMENT TOTAL CALCULATED MAX. OCCUPANCY: 1 PERSONS



1 LIFE SAFETY PLAN : BASEMENT

SCALE: 3/16" = 1'-0"



Stamp

A. GENERAL NOTES

- ALL STRUCTURAL WORK SHALL CONFORM TO THE PROJECT SPECIFICATIONS, DRAWINGS, AND THE 2018 INTERNATIONAL BUILDING CODE.
- CONTRACTOR SHALL COORDINATE STRUCTURAL WORK WITH RELATED TRADES AND WITH OTHER DESIGN DISCIPLINE REQUIREMENTS PRIOR TO MAKING SUBMITTALS. CONTRACTOR SHALL REPORT ANY DISCREPANCIES TO THE ARCHITECT PRIOR TO PERFORMING WORK.
- REFER TO OTHER DESIGN DISCIPLINE DRAWINGS AND SPECIFICATIONS FOR ADDITIONAL INFORMATION REQUIRED FOR THE SUBMITTALS AND INSTALLATION OF STRUCTURES, INCLUDING BUT NOT LIMITED TO DIMENSIONS, ELEVATIONS, SLOPES, LOCATIONS OF OTHER SYSTEMS AND EQUIPMENT, OPENINGS, WALLS, STAIRS, FINISHES, COATINGS, AND OTHER NON-STRUCTURAL ITEMS. NOTES PROVIDED ON THE DRAWINGS ARE INTENDED FOR USE IN CONJUNCTION WITH PROJECT SPECIFICATIONS.
- DETAILS LABELED AS TYPICAL DETAILS ON THE DRAWINGS SHALL APPLY TO ALL SITUATIONS OCCURRING ON THE PROJECT THAT ARE THE SAME OR SIMILAR TO THOSE SPECIFICALLY DETAILED. SUCH TYPICAL DETAILS SHALL APPLY WHETHER OR NOT THEY ARE MARKED AT EACH LOCATION IN THE DRAWINGS. FOR CONDITIONS NOT SPECIFICALLY SHOWN, PROVIDE DETAILS OF A SIMILAR NATURE. VERIFY APPLICABILITY BY SUBMITTALS.
- CONTRACTOR IS RESPONSIBLE FOR COORDINATION DETAILS AND ACCURACY OF THE WORK FOR CONFIRMING AND CORRELATING ALL QUANTITIES AND DIMENSIONS; FOR SELECTING FABRICATION PROCESSES, FOR TECHNIQUES OF ASSEMBLY IN ACCORDANCE WITH GENERAL CONDITIONS AND DIVISION I SPECIFICATION REQUIREMENTS; AND FOR PERFORMING ALL WORK IN A SAFE AND SECURE MANNER IN ACCORDANCE WITH GOVERNING JOB SAFETY STANDARDS.
- CONTRACTOR SHALL VERIFY ALL CONDITIONS AT THE SITE, INCLUDING LOCATIONS OF ALL EXISTING STRUCTURES AND EXISTING UTILITIES ABOVE AND BELOW GROUND (AS ANY INFORMATION SHOWN IS APPROXIMATE AND NOT NECESSARILY COMPLETE). CONTRACTOR SHALL REPORT ANY DISCREPANCIES TO THE ARCHITECT PRIOR TO PERFORMING WORK.
- LOADS APPLIED DURING CONSTRUCTION SHALL NOT EXCEED THE DESIGN LOADS NOTED ON THE DRAWINGS OR THE CAPACITY OF PARTIALLY COMPLETED CONSTRUCTIONS AS DETERMINED BY THE CONTRACTOR. THE STRUCTURAL ELEMENTS OF THE PROJECT AS SHOWN IN THE CONSTRUCTION DOCUMENTS HAVE BEEN DESIGNED FOR THE SPECIFIED VERTICAL AND LATERAL FORCES ACTING ON THE COMPLETED BUILDING. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO DESIGN AND PROVIDE ALL REQUIRED SHORING AND BRACING NEEDED DURING CONSTRUCTION TO MAINTAIN THE STABILITY AND SAFETY OF THE PARTIALLY-COMPLETED STRUCTURE AND FOR CONSTRUCTION LOADINGS THAT EXCEED THE SPECIFIED DESIGN LOADS.
- SHORING, BRACING, PROTECTING, AND MAINTAINING THE INTEGRITY OF ANY EXISTING, ADJACENT, AND/OR ONGOING PARTIALLY COMPLETED STRUCTURES IS THE RESPONSIBILITY OF THE CONTRACTOR.

B. EXISTING BUILDING NOTES

- DIMENSIONS, ELEVATIONS, MEMBER SIZES AND DETAILS OF EXISTING STRUCTURE SHOWN IN THE STRUCTURAL DRAWINGS HAVE BEEN EXTRACTED FROM RECORD DRAWINGS AND/OR LIMITED FIELD MEASUREMENTS. AS SUCH THEY ARE NOT TO BE CONSIDERED SUITABLY ACCURATE FOR ANY CONSTRUCTION WORK SHOWN, INCLUDING FABRICATIONS, SUBMITTALS, ETC. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS OF THE EXISTING CONSTRUCTION, INCLUDING PLUMBNESS OR FLATNESS OF WALLS, FLOORS, ETC. AT THE JOB SITE PRIOR TO SUBMITTAL, FABRICATION OR CONSTRUCTION WORK. ANY DEVIATIONS FOUND IN THE FIELD FROM WHAT IS SHOWN ON THE DRAWINGS SHALL BE REPORTED TO THE ARCHITECT PRIOR TO FABRICATION OR CONSTRUCTION.
- TEMPORARY SHORING AND BRACING OF FLOORS, WALLS, AND OTHER STRUCTURAL ELEMENTS OF THE EXISTING BUILDINGS REQUIRED TO ACHIEVE THE INSTALLATION OF NEW AND/OR THE REMOVAL OF EXISTING STRUCTURAL ELEMENTS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR SHALL, AT THEIR DISCRETION AND WHERE SPECIFIED, EMPLOY ENGINEERING SERVICES FOR DESIGN OF TEMPORARY BRACING, SHORING AND PROTECTION. EXISTING BUILDING MOVEMENTS SHALL BE LIMITED TO PREVENT DISTRESS FROM OCCURRING.
- REPORT EXISTING CONDITIONS UNCOVERED, REVEALED, FOUND OR DEVELOPED DURING CONSTRUCTION INDICATIVE OF STRUCTURAL INTEGRITY LOSS OR DETERIORATION, UNLESS SPECIFICALLY NOTED ON THE DRAWINGS.
- DO NOT CUT, DRILL OR ALTER ANY EXISTING STRUCTURAL ELEMENTS UNLESS SHOWN OR NOTED ON THE STRUCTURAL DRAWINGS WITHOUT NOTIFY THE ARCHITECT FOR REVIEW, INCLUDING TEMPORARY MEASURES OR FOR THE INSTALLATION OF OTHER DESIGN DISCIPLINE WORK.

C. FOUNDATION RELATED EARTHWORK

- FOUNDATIONS HAVE BEEN DESIGNED FOR A PRESUMPTIVE BEARING PRESSURE OF 2000 PSF BASED ON IBC-2018 TABLE E-1900-2. THIS ASSUMPTION SHALL BE VERIFIED BY THE OWNER OF THE GENERAL CONTRACTOR AT THE TIME OF EXCAVATION. IF NECESSARY, THE OWNER SHALL EMPLOY A TESTING AGENCY OR GEOTECHNICAL ENGINEER TO ASSIST IN THIS EVALUATION. SOIL TESTING OR GEOTECHNICAL ENGINEER HAS NOT BEEN COMPLETED BY THE DESIGN TEAM.
- IBC CHAPTER 18 'SOILS AND FOUNDATION' REQUIREMENTS APPLY, UNLESS SPECIFICALLY NOTED OTHERWISE BY DRAWINGS OR SPECIFICATIONS. REPORT CONFLICTS BETWEEN THE REPORTING AND THE DRAWINGS AND SPECIFICATIONS TO THE ARCHITECT PRIOR TO COMMENCING ANY AFFECTED WORK.
- FOOTINGS, PILE CAPS, AND SLABS CAST DIRECTLY AGAINST THE EARTH SHALL BE SIDE-FORMED AS REQUIRED TO KEEP EARTH OUT OF THE CONCRETE. COMPACT DISTURBED LOAD BEARING SOIL IN DIRECT CONTACT WITH FOUNDATION TO ORIGINAL BEARING CAPACITY. AS WET WEATHER OR GROUND CONDITIONS WARRANT, PLACE A MINIMUM OF 6 INCHES OF CRUSHED STONE OR 12 INCHES OF SAND-GRAVEL GRAVEL IN GEOTEXTILE FABRIC FOR SUBGRADE PROTECTION BEHIND FOUNDATIONS. DO NOT ALLOW FOR STANDING WATER ON EARTH. IF OVER-EXCAVATION OCCURS, REPLACE MATERIAL WITH BACKFILL MEASURES SPECIFIED FOR USE UNDER FOUNDATIONS, AFTER ACCEPTANCE BY GEOTECHNICAL ENGINEER.
- UNLESS NOTED OTHERWISE, PLACE AND COMPACT BACKFILL IN EQUAL CONTINUOUS LAYERS NOT EXCEEDING A MAXIMUM OF 8' OF COMPACTED DEPTH FOR HAND-HELD COMPACTION EQUIPMENT AND A MAXIMUM OF 12' INCHES COMPACTED DEPTH FOR VIBRATORY ROLLERS. MAINTAIN OPTIMUM MOISTURE CONTENT OF BACKFILL MATERIALS TO ATTAIN COMPACTION DENSITY.
- AT EARTH RETAINING AND FOUNDATION WALLS, BACKFILL LIFTS TO NOT EXCEED 12 INCH DIFFERENCE IN ELEVATION UNTIL FINAL ELEVATION ARE REACHED ON BOTH SIDES OF THE WALL. AT BASEMENT WALLS, DO NOT BACKFILL UNTIL GROUND FLOOR AND CONNECTED ELEVATED FRAMED LEVELS SLABS HAVE BEEN COMPLETED AND THE CONCRETE AT WALLS AND FLOORS HAS ACHIEVED FULL DESIGN STRENGTH.
- THE CONSTRUCTION CONSIDERATIONS IN THE GEOTECHNICAL REPORTING AND PROJECT SPECIFICATIONS SHALL APPLY TO THIS PROJECT, INCLUDING BUT NOT LIMITED TO PROOFROLLING SUBGRADES AT THE EXCAVATION AND/OR BEARING ELEVATIONS; REMOVING AND REPLACING LOOSE OR SOFT POCKETS, FILL-SLOPE CONSTRUCTIONS, ETC.
- BACKFILL REQUIREMENTS:
 - FILL WITHIN BUILDING ENVELOPE AND EXTENDING OUTWARD AT 1:1 SLOPE TO ACCEPTABLE NATIVE SOIL CONDITIONS:
 - MATERIAL: "SAND-GRAVEL"; "GRANULAR"; "CRUSHED STONE" WITH GEOTEXTILE WRAP (SEE SECTIONS)
 - COMPACTION: 95% MODIFIED PROCTOR
 - BACKFILL DIRECTLY BELOW INTERIOR SLABS-ON-GRADE ASSEMBLIES (12 INCHES UNLESS NOTED OTHERWISE) "CRUSHED STONE" WITHOUT GEOTEXTILE COMPACTION: 95% MODIFIED PROCTOR
 - BACKFILL BEHIND RETAINING WALLS AND BASEMENT WALLS, OUTSIDE BUILDING ENVELOPE AND UNDER PAVEMENT, WALKS, ENTRY SLABS:
 - MATERIAL: "GRANULAR BACKFILL"
 - COMPACTION: 95% MODIFIED PROCTOR
 - BACKFILL ALONG EXTERIOR OF BUILDING AGAINST WALLS AND NOT UNDER PAVEMENT, WALKS, ENTRY SLABS:
 - MATERIAL: "SUITABLE NATIVE SOIL" COVERED BY 2 FEET DEEP BY 4 FEET WIDTH OF "LESS PERMEABLE FILL" COMPACTION: 92% MODIFIED PROCTOR
- BACKFILL MATERIALS: RECYCLED CONCRETE AGGREGATE TO BE USED IN WHOLE OR BLENDED WITH OTHER AGGREGATES TO ACHIEVE GRADATIONS BELOW. ONSITE MATERIALS MEETING THE FOLLOWING CLASSIFICATIONS MAY BE USED:
 - "SAND-GRAVEL":

SIEVE DESIGNATION	% BY WEIGHT PASSING SIEVES
4 INCH	100
1/2 INCH	50-85
No. 4	45-75
No. 100	10-35
No. 200	0-6

 SEE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS. SHOW ALL SLABS IN PLAN AND ALL WALLS IN ELEVATION WITH OPENINGS AND PENETRATIONS SHOWN BASED ON MEP COORDINATION SUBMITTALS AND ARCHITECTURAL REQUIREMENTS. SUBMIT PROPOSED CONTROL AND CONSTRUCTION JOINTS FOR REVIEW ON REINFORCING SUBMITTALS
 - REINFORCING STEEL SHALL BE DEFORMED BARS CONFORMING TO ASTM A615 GRADE 60, STEEL BARS PER ASTM A305, UNLESS NOTED OTHERWISE.
 - WHERE SPECIFICALLY SHOWN ON THE DRAWINGS, WELD REINFORCING BARS IN ACCORDANCE WITH AWS-D14. PRE-QUALIFIED JOINT: ELECTRODE G90 (LOW HYDROGEN) AND PROCESS REQUIREMENTS INCLUDING COORDINATED WITH MILL CERTIFIED CARBON EQUIVALENT. ALTERNATIVELY, ASTM A706 GRADE 60 MAY BE SUBSTITUTED. INDICATE MATERIAL AND WELDING REQUIREMENTS ON SUBMITTAL. DO NOT WELD AT LOCATIONS NOT DETAILED, UNLESS SUBMITTED AND REVIEWED BY ARCHITECT.
 - FIELD BENDING OR REINFORCEMENT SHALL CONFORM TO ACI 301, INCLUDING PRE-HEAT REQUIREMENTS.
 - WELDED WIRE FABRIC (WWF) SHALL CONFORM TO ASTM A182 WITH A MINIMUM ULTIMATE TENSILE STRENGTH OF 70,000 PSI. LAP ONE CROSS WIRE SPACING PLUS 2". SUPPORT MESH ON CHAIRS PER CRSI WITH #4 AT 4'-0" EACH WAY.
 - PROVIDE MINIMUM CONCRETE COVER TO REINFORCEMENT AS FOLLOWS, UNLESS OTHERWISE NOTED:
 - BOTTOM OF FOOTINGS, GRADE BEAMS, AND SLABS-ON-GRADE: 3"
 - SIDES OF FOOTINGS AND GRADE BEAMS: 2"
 - FOUNDATION WALLS, FROST WALLS, RETAINING WALLS, PIT WALLS: 2"
 - FOUNDATION PIERS: 2" TO TIERS
 - ALL LAPS SHALL BE FULL TENSION LAPS (CLASS B SPLICE) UNLESS SPECIFICALLY NOTED OTHERWISE. DOWELS SHALL MATCH SIZE AND SPACING OF MAIN REINFORCEMENT, UNLESS OTHERWISE NOTED.
 - CHAIRS AND SPACERS SHALL BE PLACED TO ADEQUATELY SUPPORT REINFORCING DURING PLACEMENT. FOREIGN MATERIALS SUCH AS WOOD, CLAY BRICK OR OTHER UNSUITABLE SUPPORTS SHALL NOT BE USED TO SUPPORT REINFORCING. SET WIRE TIES SOEDS ARE DIRECTED INTO CONCRETE WHERE CONCRETE WILL BE EXPOSED. DO NOT USE CONCRETE SUPPORTS OR Pudding FOR SLABS UNLESS SUBMITTED AND ACCEPTABLY REVIEWED.
- GEOTEXTILE FABRIC: NON-WOVEN WITH 12 LAPPED SEAMS SEE GEOTECHNICAL REPORTING FOR USE AND MEETING:
 - GRAB STRENGTH OF 60 POUNDS MINIMUM MEETING ASTM D4632
 - PUNCTURE STRENGTH OF 25 POUNDS MINIMUM MEETING ASTM D4633
 - TRAPEZOID TEAR OF 25 POUNDS MINIMUM MEETING ASTM D4533
 - APPARENT OPENING SIZE OF NO. 70-100 (US SIEVE) MEETING ASTM D4751

D. CAST-IN-PLACE CONCRETE

- CODES AND STANDARDS: COMPLY WITH THE PROVISIONS OF THE LATEST EDITIONS OF:
 - ACI 318 "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE"
 - ACI 319 "SPECIFICATIONS FOR STRUCTURAL CONCRETE"
 - ACI 304 GUIDE FOR MIXING, TRANSPORTING AND PLACING CONCRETE"
 - ACI 305 "HOT WEATHER CONCRETING"
 - ACI 306 "STANDARD SPECIFICATION FOR COLD WEATHER CONCRETING"
 - ACI 308 "STANDARD PRACTICE FOR CURING CONCRETE".
- CONCRETE TESTING: THE CONTRACTOR SHALL PREPARE A SET OF 4 CYLINDERS/TEST SET TO BE TESTED AT AN INDEPENDENT LABORATORY. THE CYLINDERS SHALL BE TAKEN FROM ONE CONCRETE TRUCK AND LABELED WITH DATE, TRUCK NUMBER, AND LOCATION OF CONCRETE PLACEMENT. EACH SAMPLE SHALL ALSO BE TESTED FOR SLUMP, AIR CONTENT, AND TEMPERATURE. THE CYLINDERS SHALL BE TESTED AS FOLLOWS: 1 AT 7 DAYS; 2 AT 28 DAYS, AND A THIRD HELD FOR A 50 DAY BREAK IF REQUIRED. TEST CYLINDERS SHALL BE TAKEN AT LEAST ONCE PER PLACEMENT OR AT THE FOLLOWING INCREMENTS:
 - WALKS AND FOOTINGS: 50 CUBIC YARDS
 - ISOLATED FOOTINGS: 25 CUBIC YARDS
 - SLABS: 50 CUBIC YARDS
 FIELD TESTING SHALL BE PERFORMED BY A GRADE I ACI (MINIMUM) FIELD TESTING TECHNICIAN.
- SUBMIT MIX DESIGN AND EITHER TRIAL MIX DESIGNS OR HISTORIC FIELD DATA FOR APPROVAL IN ACCORDANCE WITH ACI 318, CHAPTER 5. INCLUDE TECHNICAL DATA SHEETS, GRADATIONS, AND MATERIAL VERIFICATIONS ON ALL COMPONENTS. SUBMIT MIX DESIGNS, PRIOR TO PLACEMENT OF CONCRETE, TRANSIT MIX SHALL CONFORM TO ASTM C94.
- COMPRESSIVE MIXTURES AS DELINEATED IN TABLE BELOW, SEE 03 3000 & NOTES BELOW FOR ADDITIONAL INFORMATION:
 - SLUMP: 3'-5" BEFORE ADDITION OF WATER REDUCER, 6"-8" AFTER ADDITION OF WATER REDUCER
 - ALL CONCRETE NORMALWEIGHT, UNLESS NOTED OTHERWISE.
- MAXIMUM AGGREGATE SIZE IN ACCORDANCE WITH ACI 301: CLEARLY NOTE LOCATION WHERE AGGREGATES GREATER THAN 3/4" MAXIMUM SIZE ARE PROPOSED FOR USE.
- NO CHLORIDE OR OTHER UNAUTHORIZED ADMIXTURES SHALL BE USED. MAINTAIN MAXIMUM WATER SOLUBLE CHLORIDE ION (Cl-) IN CONCRETE, BY WEIGHT OF CEMENT AT LESS THAN 1.00 FOR NON-EXPOSED CONCRETES AND 0.30 FOR EXTERIOR EXPOSED CONCRETES
- WHEN AMBIENT TEMPERATURE IS BELOW 40° FAHRENHEIT OR MORE THAN 90° FAHRENHEIT PLACE AND PROTECT CONCRETE IN ACCORDANCE WITH ACI STANDARDS LISTED ABOVE.
- CONCRETE PLACEMENT MAY REQUIRE ADJUSTMENT OF REINFORCEMENT, EMBEDDED ITEMS OR ANCHOR BOLTS. REVIEW DRAWINGS IDENTIFY THESE LOCATIONS TO ARCHITECT PRIOR TO SUBMITTALS. PROVIDE ADDITIONAL SUPERVISION AT ALL STEEL TO CONCRETE CONNECTION LOCATIONS AND MODIFY PLACEMENT MEASURES TO ACCOUNT FOR CONGESTIONS.
- COMPLY WITH ACI CODES AND PLACE CONCRETE IN A CONTINUOUS OPERATION WITHIN PLANNED JOINTS OR SECTIONS. DO NOT PERMIT COLD JOINTS TO OCCUR.

H. WOOD FRAMING NOTES

- UNLESS OTHERWISE SPECIFIED, EACH PIECE OF LUMBER SHALL BEAR THE GRADE MARK, STAMP, OR OTHER IDENTIFYING MARKS INDICATING GRADES OF MATERIAL, AND RULES OR STANDARDS UNDER WHICH PRODUCED. SUCH IDENTIFYING MARKS ON MATERIAL SHALL BE IN ACCORDANCE WITH THE RULE OR STANDARD UNDER WHICH MATERIAL IS PRODUCED, INCLUDING REQUIREMENTS FOR QUALIFICATIONS AND AUTHORITY OF THE INSPECTION ORGANIZATION, USAGE OF AUTHORIZED IDENTIFICATION, AND INFORMATION INCLUDED IN THE IDENTIFICATION. THE INSPECTION AGENCY FOR LUMBER SHALL BE APPROVED BY THE BOARD OF REVIEW, AMERICAN LUMBER STANDARDS COMMITTEE, TO GRADE SPECIES USED.

- PROTECT LUMBER AND OTHER PRODUCTS FROM DAMPNESS BOTH DURING AND AFTER DELIVERY AT THE SITE. PILE PLYWOOD AND LUMBER IN STACKS IN SUCH A MANNER AS TO PROVIDE ADEQUATE AIR CIRCULATION AND TO PREVENT WARPING. LOCATE STACKS IN WELL DRAINED AREAS, SUPPORTED AT LEAST SIX INCHES ABOVE GRADE AND COVER WITH WELL VENTILATED SHELVES HAVING A FIRMLY CONSTRUCTED OVERHANGING ROOF AS WELL AS SUFFICIENT END WALL TO PROTECT LUMBER FROM DRIVING RAIN.

- STORE SEASONED MATERIALS IN DRY PORTIONS OF BUILDING.

- PROTECT SHEET MATERIALS FROM CORNERS BREAKING AND DAMAGING SURFACES WHILE UNLOADING.

- NOMINAL SIZES ARE INDICATED EXCEPT AS SHOWN BY DETAIL DIMENSIONS. PROVIDE ACTUAL SIZES AS REQUIRED BY PRODUCT STANDARD 20, DEPARTMENT OF COMMERCE.

- MAXIMUM MOISTURE CONTENT SHALL NOT EXCEED 19%.

- LIGHT GAGE METAL CONNECTIONS SHALL BE SIMPSON, SUBMIT MANUFACTURERS SPECIFICATION SHEETS.

LUMBER GRADES:

- 2X6 AND 2X4 BEARING WALLS, INTERIOR AND EXTERIOR LOCATIONS: SPRUCE-PINE-FIR No. 1 / No. 2 AS GRADED BY NLGA

- STRUCTURAL ROOF AND FLOOR FRAMING: SPRUCE-PINE-FIR No. 1 / No. 2 AS GRADED BY NLGA

- PRESERVATIVE PRESSURE TREATED (P.P.T. or P.T.) LUMBER: SOUTHERN PINE No. 2, AS GRADED BY SPB

- LAMINATED VENEER LUMBER (LVL):
 - PROVIDE LVL HEADERS AND BEAMS AS INDICATED.
 - LVL FRAMING SHALL BE LAMINATED DOUGLAS FIR OR SOUTHERN PINE (GP LAM BY GEORGIA PACIFIC OR MICHIGAN LAM BY TRUS-JOIST) OR EQUAL MEETING THE FOLLOWING MINIMUM ALLOWABLE STRESS CRITERIA: FB (BENDING STRESS) = 225 PSI
 - FV (HORIZONTAL STRESS) = 265 PSI
 - E (MODULUS OF ELASTICITY) = 1,800,000 PSI
 - FC (COMPRESSIONS PERPENDICULAR TO GRAIN) = 750 PSI

- MISCELLANEOUS LUMBER: PROVIDE WOOD FOR SUPPORT OR ATTACHMENT OF THE WORK INCLUDING NON-BEARING PARTITIONS, CANT STRIPS, BUCKS, NAILERS, BLOCKING, FURRING, GROUNDS, STRIPPING AND SIMILAR MEMBERS. PROVIDE LUMBER OF SIZES AND SHAPES INDICATED. GRADE: SPRUCE-PINE-FIR STUD GRADE AS GRADED BY NLGA

MATERIALS:

- ROOF SHEATHING: 5/8" ADVANTECH ROOF SHEATHING, STRUCTURAL 1 PANEL GRADE, MANUFACTURED BY HUBER ENGINEERED WOODS WITH A PS-2 SPAN RATING OF 40/20 AS DENOTED BY CODE EVALUATION REPORT ESR 1785.

- FLOOR SHEATHING: 23/32" ADVANTECH SUBFLOOR SHEATHING, STRUCTURAL 1 PANEL GRADE, MANUFACTURED BY HUBER ENGINEERED WOODS WITH A PS-2 SPAN RATING OF 24-INCHES AS DENOTED BY CODE EVALUATION REPORT ESR 1785.

- FASTENERS AND ANCHORS: FURNISH ITEMS OF ROUGH HARDWARE, METAL CONNECTORS, BOLTS, ETC. REQUIRED TO COMPLETE THE WORK. BOLTS, NUTS AND WASHERS SHALL BE HOT DIPPED ELECTRO GALVANIZED STEEL.

- SILL GASKET ON TOP OF FOUNDATION WALL: 1/4 INCH THICK, PLATE WIDTH WIDE, CLOSED CELL POLYETHYLENE URETHANE FOAM FROM CONTINUOUS ROLLS.

- SUBFLOOR GLUE: APA AFG-01, WATERPROOF OF WATER SOLVENT BASE, AIR CURE TYPE, CARTRIDGE DISPENSED.

- BUILDING PAPER: NO. 15 ASPHALT FELT, PLAIN UNTREATED CELLULOSE BUILDING PAPER.

- WOOD PRESERVATIVE (PRESSURE TREATMENT): AWPA TREATMENT ACQ USING WATER BORNE PRESERVATIVE WITH 0.40 PERCENT RETAINAGE.

- SET STRUCTURAL MEMBERS LEVEL AND PLUMB, IN CORRECT POSITION.

- MAKE PROVISIONS FOR ECTION LOADS, AND FOR SUFFICIENT TEMPORARY BRACING TO MAINTAIN STRUCTURE SAFE, PLUMB, AND IN TRUE ALIGNMENT UNTIL COMPLETION OF ECTION AND INSTALLATION OF PERMANENT BRACING.

- PLACE HORIZONTAL MEMBERS, CROWN SIDE UP.

- CONSTRUCT LOAD BEARING FRAMING FULL LENGTH WITHOUT SPLICES.

- DOUBLE MEMBERS AT OPENINGS OVER 24 INCHES WIDE. SPACE SHORT STUDS OVER AND UNDER OPENING TO STUD SPACING.

- CONSTRUCT DOUBLE JOIST HEADERS AT FLOOR AND CEILING OPENINGS AND UNDER WALL STUD PARTITIONS THAT ARE PARALLEL TO FLOOR JOISTS. FRAME RIGIDLY INTO JOISTS.

- BRIDGE JOISTS FRAMING IN EXCESS OF 8 FEET SPAN AT MID-SPAN AND WHERE SHOWN ON DRAWINGS. FIT SOLID BLOCKING OR BRADING AT ENDS OF MEMBERS.

- SECURE ROOF SHEATHING WITH LONGER EDGE PERPENDICULAR TO FRAMING MEMBERS AND WITH ENDS STAGGERED AND SHEET ENDS OVER BEARING.

- USE SHEATHING CLIPS BETWEEN SHEETS BETWEEN ROOF FRAMING MEMBERS.

- WHERE TONGUE AND GROOVE PLYWOOD IS USED, FULLY ENGAGE TONGUE AND GROOVE EDGES.


- SECURE WALL SHEATHING WITH LONG DIMENSION PERPENDICULAR TO WALL STUDS, WITH ENDS OVER FIRM BEARING AND STAGGERED.

- PLACE BUILDING PAPER HORIZONTALLY OVER WALL SHEATHING; WEATHER LAP EDGES AND ENDS.

- SECURE SUB-FLOOR SHEATHING WITH LONGER EDGE PERPENDICULAR TO FLOOR FRAMING AND WITH END JOINTS STAGGERED AND SHEET ENDS OVER BEARING. ATTACH WITH SUB-FLOOR GLUE AND 8D NAILS AT 6" ON CENTER AT PERIMETER AND 12" ON CENTER ON INTERIOR OF PANEL.

- TOLERANCES:
 - FRAMING MEMBERS: 1/4 INCH FROM TRUE POSITION, MAXIMUM.
 - SURFACE FLATNESS OF FLOOR: 1/4 INCH IN 10 FEET MAXIMUM, AND 1/2 INCH IN 30 FEET MAXIMUM.

- ALL POSTS AND COLUMNS FROM HEADERS AND BEAMS SHALL BEAR CONTINUOUSLY TO CONCRETE



Stamp

BASIS OF DESIGN

1. Building Code: 2018 IBC & ASCE7-16

2. Dead Loads:
a. Roof Dead Load: 20 psf
b. Floor Dead Load: 20 psf

3. Live Loads:
a. Roof Live Load: Snow Load Governs
b. First Floor Live Load (Stack rooms): 150 psf
c. Second Floor Live Load (Reading Room and Meeting Room): 60 psf

4. Roof Snow Load:
a. Ground Snow Load, P_g : 60 psf
b. Flat Roof Snow Load, P_f : 46 psf
c. Snow Exposure Factor, C_e : 1.0
d. Snow Load Importance Factor, I : 1.0
e. Thermal Factor, C_t : 1.1

5. Wind Design Data:
a. Basic Wind Speed (3-second gust), V : 115 mph
b. Wind Exposure: C
c. Internal Pressure Coefficients: +/- 0.18
d. Components and Cladding Wind Pressure: per ASCE 7

6. Allowable Soil Bearing Pressure: 2000 psf (Assumed to be verified)

**ENGINEERING
VENTURES PC**

Vermont • New Hampshire • New York
208 Flynn Avenue, Suite 2A, Burlington, VT 05401 | (802) 442-3333
89 Mechanic Street, Suite E2-3, Lebanon, NH 03766 | (603) 442-3333
368 Broadway, Suite 15, Saratoga Springs, NY 12866 | (518) 205-9914
www.engineeringventures.com

27 Park St.
Canaan, VT 05903

B.O.D.
ALLICE WARD LIBRARY

Sheet Title: Project Title:
Designed By: MAN
Checked By: RN
Drawn By: MAN
Scale: 1/8" = 1'-0"
Date: 01/20/26

S-2


EV Project #24649

ABBREVIATIONS

AB	ANCHOR BOLT	MC	MOMENT CONNECTION
AFF	ABOVE FINISH FLOOR	N.S.	NEAR SIDE
AL	ALUMINUM	oc	ON CENTER
B.O.F.	BOTTOM OF FOOTING	P#	PIER DESIGNATION
DWG	DRAWING	PL	PLATE
E.F.	EACH FACE	SS	STAINLESS STEEL
ELEV.	ELEVATION	STD	STANDARD
EP	EMBED PLATE	T.O.C.	TOP OF CONCRETE
EQ	EQUAL	T.O.S.	TOP OF STEEL
E.S.	EACH SIDE	T.O.SHELF	TOP OF SHELF
E.W.	EACH WAY	T.O.W.	TOP OF WALL
EX.	EXISTING	TYP.	TYPICAL
F#	FOOTING DESIGNATION	U.N.O.	UNLESS NOTED OTHERWISE
FND	FOUNDATION	V.I.F.	VERIFY IN FIELD
F.S.	FAR SIDE		
H.T.	HEAVY TIMBER		

DRAWING LEGEND


NOTE: NOT ALL SYMBOLS AND NOTATIONS USED



Sheet Title: Project Title:
Designed By: MAN
Checked By: RN
Drawn By: MAN
Scale: 1/8" = 1'-0"
Date: 01/20/26

S-2

EV Project #24649



FASTENING SCHEDULE

(TABLE 2304.10.1, IBC)

FASTENING SCHEDULE

(TABLE 2304.10.1, IBC 2018)

DESCRIPTION OF BUILDING ELEMENTS	NUMBER AND TYPE OF FASTENER	SPACING AND LOCATION	DESCRIPTION OF BUILDING ELEMENTS	NUMBER AND TYPE OF FASTENER	SPACING AND LOCATION	
1. Blocking between ceiling joists, rafters or trusses to top plate or other framing below	(3) 8d common (2-1/2" x 0.131"); or (3) 10d box (3" x 0.128"); or (3) 3"x0.131" nails; or (3) 3" 14 gage staples, 7/16" crown	Each end, toenail			Wall	
			21. Joist to sill, top plate, or girder	(3) 8d common (2 1/2" x 0.131"); or (3) 10d box (3" x 0.128"); or (3) 3"x0.131" nails; or (3) 3" 14 gage staples, 7/16" crown	Toenail	
Blocking between rafters or truss at the wall top plate, to rafter or truss	(2) 8d common (2-1/2" x 0.131") (2) 3"x0.131" nails (2) 3" 14 gage staples	Each end, toenail	22. Rim joist, band joist, or blocking to top plate, sill or other framing below	8d common (2 1/2" x 0.131"); or 10d box (3" x 0.128"); or 3"x0.131" nails; or 3" 14 gage staples, 7/16" crown	6"oc, toenails	
Flat blocking to truss and web filler	16d common (3-1/2" x 0.162") 3"x0.131" nails 3" 14 gage staples	6"oc Face nails	23. 1" x 6" subfloor or less to each joist	(2) 8d common (2-1/2" x 0.131"); or (2) 10d box (3" x 0.128")	Face nail	
2. Ceiling joists to top plate	(3) 8d common (2-1/2" x 0.131"); or (3) 10d box (3" x 0.128"); or (3) 3"x0.131" nails; or (3) 3" 14 gage staples, 7/16" crown	Each joist, toe nails	24. 2" subfloor to joist or girder	(2) 16d common (3-1/2" x 0.162")	Face nail	
3. Ceiling joist not attached to parallel rafter, laps over partitions (no thrust) (see Section 2308.7.3.1, Table 2308.7.3.1)	(3) 16d common (3-1/2" x 0.162"); or (4) 10d box (3" x 0.128"); or (4) 3"x0.131" nails; or (4) 3" 14 gage staples, 7/16" crown	Face nails	25. 2" planks (plank & beam - floor & roof)	(2) 16d common (3-1/2" x 0.162")	Each bearing, face nail	
4. Ceiling joist attached to parallel rafter (heel joint) (see Section 2308.7.3.1, Table 2308.7.3.1)	Per Table 2308.7.3.1	Face nails	26. Built-up girders and beams, 2" lumber layers	20d common (4" x 0.192") 10d box (3" x 0.128"); or 3"x0.131" nails; or 3" 14 gage staples, 7/16" crown And: (2) 20d common (4" x 0.192"); or (3) 10d box (3" x 0.128"); or (3) 3"x0.131" nails; or (3) 3" 14 gage staples, 7/16" crown	32"oc face nails at top and bottom staggered on opposite sides 24"oc face nails at top and bottom staggered on opposite sides Ends and at each splice, face nail	
5. Collar tie to rafter	(3) 10d common (3" x 0.148"); or (4) 10d box (3" x 0.128"); or (4) 3"x0.131" nails; or (4) 3" 14 gage staples, 7/16" crown	Face nails	27. Ledger strip supporting joists or rafters	(3) 16d common (3 1/2" x 0.162"); or (4) 10d box (3" x 0.128"); or (4) 3"x0.131" nails; or (4) 3" 14 gage staples, 7/16" crown	Each joist or rafter, face nail	
6. Rafter or roof truss to top plate (See section 2308.7.5, Table 2308.7.5)	(3) 10d common (3" x 0.148"); or (3) 16d box (3 1/2" x 0.135"); or (4) 10d box (3" x 0.128"); or (4) 3"x0.131" nails; or (4) 3" 14 gage staples, 7/16" crown	Toenail ^c	28. Joist to band joist or rim joist	(3) 16d common (3 1/2" x 0.162"); or (4) 10d box (3" x 0.128"); or (4) 3"x0.131" nails; or (4) 3" 14 gage staples, 7/16" crown	End nail	
7. Roof rafters to ridge valley or hip rafters; or roof rafter to 2-inch ridge beam	(2) 16d common (3 1/2" x 0.162"); or (3) 10d box (3" x 0.128"); or (3) 3"x0.131" nails; or (3) 3" 14 gage staples, 7/16" crown; or (3) 10d common (3" x 0.148"); or (4) 16d box (3 1/2" x 0.135"); or (4) 10d box (3" x 0.128"); or (4) 3"x0.131" nails; or (4) 3" 14 gage staples, 7/16" crown	End nail Toenail	29. Bridging or blocking to joist, rafter or truss	(2) 8d common (2 1/2" x 0.131"); or (2) 10d box (3" x 0.128"); or (2) 3"x0.131" nails; or (2) 3" 14 gage staples, 7/16" crown	Each end, toenail	
					Wood structural panels (WSP), subfloor, roof and interior wall sheathing to framing and particleboard wall sheathing to framing^a	
					Edges (inches)	
8. Studs to stud (not at braced wall panels)	16d common (3-1/2" x 0.162") 10d box (3" x 0.128"); or 3"x0.131" nails; or 3" 14 gage staples, 7/16" crown	24"oc face nail 16"oc face nail	30. 3/8" - 1/2"	6d common or deformed (2" x 0.113") (subfloor and wall) 8d common or deformed (2 1/2" x 0.131") (roof) or RSRS-01 (2 3/8" x 0.113") nail (roof) ^d 2 3/8" x 0.113" nail (subfloor and wall)	6	12
9. Stud to stud and abutting studs at intersecting wall corners (at braced wall panels)	16d common (3-1/2" x 0.162"); or 16d box (3-1/2" x 0.135"); or 3"x0.131" nails; or 3" 14 gage staples, 7/16" crown	16"oc face nail 12"oc face nail 12"oc face nail		1 3/4" 16 gage staple, 7/16" crown (subfloor and wall) 2 3/8" x 0.113" nail (roof) 1 3/4" 16 gage staple, 7/16" crown (roof)	4	8
10. Built-up header (2" to 2" header)	16d common (3-1/2" x 0.162"); or 16d box (3-1/2" x 0.135")	16"oc each edge, face nail 12"oc each edge, face nail	31. 19/32" - 3/4"	8d common (2 1/2" x 0.131"); or 6d deformed (2" x 0.113") (subfloor and wall) 8d common or deformed (2 1/2" x 0.131") (roof) or RSRS-01 (2 3/8" x 0.113") nail (roof) ^d 2 3/8" x 0.113" nail; or 2" 16 gage staple, 7/16" crown	6	12
11. Continuous header to stud	(3) 8d common (2-1/2" x 0.131"); or (3) 10d box (3" x 0.128")	Toenails				
12. Top plate to top plate	16d common (3-1/2" x 0.162"); or 10d box (3" x 0.128"); or 3"x0.131" nails; or 3" 14 gage staples, 7/16" crown	16"oc face nail 12"oc face nail	32. 7/8" - 1 1/4"	10d common (3" x 0.148"); or 8d deformed (2 1/2" x 0.131")	4	8
13. Top plate to top plate, at end joints	(8) 16d common (3 1/2" x 0.162"); or (12) 10d box (3" x 0.128"); or (12) 3"x0.131" nails; or (12) 3" 14 gage staples, 7/16" crown	Each side of end joint, face nail (minimum 24" lap splice length each side of end joint)	33. 1/2" fiberboard sheathing ^b	1 1/2" galvanized roofing nail (7/16" head diameter); or 1 1/4" 16 gage staple with 7/16" or 1" crown	3	6
14. Bottom plate to joist, rim joist, band joist or blocking (not at braced wall panels)	16d common (3-1/2" x 0.162"); or 16d box (3" x 0.135"); or 3"x0.131" nails; or 3" 14 gage staples, 7/16" crown	16"oc face nail 12"oc face nail	34. 25/32" fiberboard sheathing ^b	1 1/2" galvanized roofing nail (7/16" head diameter); or 1 1/4" 16 gage staple with 7/16" or 1" crown	3	6
15. Bottom plate to joist, rim joist, band joist or blocking at braced wall panels	(2) 16d common (3 1/2" x 0.162"); or (3) 10d box (3" x 0.128"); or (4) 3"x0.131" nails; or (4) 3" 14 gage staples, 7/16" crown	16"oc face nail				
16. Stud to top or bottom plate	(4) 8d common (2 1/2" x 0.131"); or (4) 10d box (3" x 0.128"); or (4) 3"x0.131" nails; or (4) 3" 14 gage staples, 7/16" crown	Toenails	35. 3/4" and less 36. 7/8" - 1"	8d common (2 1/2" x 0.131"); or 6d deformed (2" x 0.113") (subfloor and wall)	6	12
	(2) 16d common (3 1/2" x 0.162"); or (3) 10d box (3" x 0.128"); or (3) 3"x0.131" nails; or (3) 3" 14 gage staples, 7/16" crown	End nails	37. 1 1/8" - 1 1/4"	8d common (2 1/2" x 0.131"); or 6d deformed (2" x 0.113") (subfloor and wall)	6	12
17. Top plates, laps at corners and intersections	(2) 16d common (3 1/2" x 0.162"); or (3) 10d box (3" x 0.128"); or (3) 3"x0.131" nails; or (3) 3" 14 gage staples, 7/16" crown	Face nails	38. 1/2" and less 39. 5/8"	10d common (3" x 0.148"); or 8d deformed (2 1/2" x 0.131")	6	12
18. 1" brace to each stud and plate	(2) 8d common (2 1/2" x 0.131"); or (2) 10d box (3" x 0.128"); or (2) 3"x0.131" nails; or (2) 3" 14 gage staples, 7/16" crown	Face nails	40. 1/4"	4d casing (1 1/2" x 0.080"); or 4d finish (1 1/2" x 0.072")	6	12
19. 1" x 6" sheathing to each bearing	(2) 8d common (2-1/2" x 0.131"); or (2) 10d box (3" x 0.128")	Face nails	41. 3/8"	6d casing (2" x 0.099"); or 6d finish (Panel supports at 24 inches)	6	12
20. 1" x 8" and wider sheathing to each bearing	(3) 8d common (2-1/2" x 0.131"); or (3) 10d box (3" x 0.128")	Face nails				

TABLE 1. CONCRETE MIXTURES

OIST HANGER SCHEDULE

MARK	WOOD MEMBER	NAME	TYPE	NAILING	
				HEADER	JOIST
JH-1	(3) 1 3/4"x9 1/2" LVL	HU610	FACE MOUNT	(18) 1/4"x1 3/4" TITEN 2 SCREWS	(8) 16d
JH-2	(3) 1 3/4"x9 1/2" LVL	HUCQ610-SDS	FACE MOUNT	(12) 1/4"x2 1/2" SDS SCREWS	(6) 1/4"x2 1/2" SDS SCREWS
JH-3	REINF. 2"x8" (5" TO 5 1/2" TOTAL WIDTH)	U66	FACE MOUNT	(8) 16d	(4) 10d
JH-4	(2) 2x8	U26-2	FACE MOUNT	(8) 16d	(4) 10d
JH-5	(2) 1 3/4"x11 1/4" LVL	HHUS48	FACE MOUNT	(22) 10d	(8) 10d
JH-6	REINF. 2"x8" (3 1/2" TOTAL WIDTH)	LUS46	FACE MOUNT	(4) 16d	(4) 16d
JH-7	2"x8"	APLH26	FACE MOUNT	(6) SD10112DBB	(4) SD10112DBB
JH-8	1 3/4"x8" LVL	HU1.81/5	FACE MOUNT	(12) 16d	(6) 16d
JH-9	(3) 1 3/4"x16" LVL	THGQ5.50-SDS	FACE MOUNT	(38) 1/4"x4 1/2" SDS SCREWS	(16) 1/4"x4 1/2" SDS SCREWS
JH-10	(3) 1 3/4"x16" LVL	HHGU5.50-SDS	FACE MOUNT	(44) 1/4"x2 1/2" SDS SCREWS	(28) 1/4"x2 1/2" SDS SCREWS
JH-11	2x8	LUS26	FACE MOUNT	(4) 10d	(4) 10d

NOTES:

1. JOIST HANGERS BY SIMPSON STRONG-TIE. ALL JOIST HANGERS SUPPORTING PT LUMBER SHALL BE GALVANIZED.
2. 10dx1 1/2" = 0.148"Ø x 1 1/2"
3. 10d = 0.148"Ø x 3"
4. 16d = 0.162"Ø x 3 1/2"
5. 1/4"x1 3/4" TITEN CONCRETE SCREW BY SIMPSON STRONG TIE.
6. SD10112DRB SCREW BY SIMPSON STRONG TIE

SHOOTING SCHEDULE

FOOTING SCHEDULE		
PLAN DESIGNATION	FOOTING SIZE	REINFORCING (BOTTOM U.N.O.)
F2.0	2'-0" x 2'-0" x 12" THICK	(2) #5 x 1'-8" EACH WAY TOP AND BOTTOM
F3.0	3'-0" x 3'-0" x 12" THICK	(3) #5 x 2'-6" EACH WAY TOP AND BOTTOM
F3.0X5.0	3'-0" x 5'-0" x 12" THICK	(5) #5 x 2'-6" SHORT WAY (4) #5 x 4'-6" LONG WAY TOP AND BOTTOM

ENGINEERING VENTURES PC

Vermont • New Hampshire • New York

208 Flynn Avenue, Suite 2A, Burlington, VT 05401 | (802)863-6225
15 Mechanic Street, Suite E2-3, Lebanon, NH 03766 | (603) 442-9333
3368 Broadway, Suite 11, Saratoga Springs, NY 12866 | (518) 205-9141
www.engineeringventures.com

201 Canaan, VT 05903

ALLICE WARD LIBRARY

SCHEDULES AND TABLES



ALICE WARD LIBRARY


Project Title

signed By:	MAN
checked By:	RN
own By:	MAN
le:	As indicated
e:	01/20/26

-3

Project #24649





Stamp

No.	Description	Date
Engineering Ventures PC		
 <p>Vermont • New Hampshire • New York 208 Flynn Avenue, Suite 2A, Burlington, VT 05401 (802) 860-4225 85 Mechanic Street, Suite E2, Lebanon, NH 03766 (603) 442-3333 368 Broadview, Suite 11, Saratoga Springs, NY 12866 (518) 205-9114 www.engineeringventures.com</p>		

PLANS
27 Park St.
Canaan, VT 05903


Sheet Title: PLANS
Project Title: ALICE WARD LIBRARY

Sheet Title: PLANS
Project Title: ALICE WARD LIBRARY


Designed By: MAN
Checked By: RN
Drawn By: MAN
Scale: 1/4" = 1'-0"
Date: 01/20/26

S-6

EV Project #24649



① ROOF FRAMING PLAN
1/4" = 1'-0"



② CUPOLA FRAMING PLAN
1/4" = 1'-0"

DEMOLITION PLAN DRAWING LEGEND

- EXISTING CONSTRUCTION TO REMAIN
- EXISTING CONSTRUCTION TO BE REMOVED
- EXISTING CONSTRUCTION TO BE REMOVED AND SUITABLY STORED FOR REUSE

DEMOLITION PLAN GENERAL NOTES

1. DEMOLITION DRAWINGS ARE DIAGRAMMATIC IN NATURE AND ARE PROVIDED TO CONVEY THE DEMOLITION INTENT REQUIRED TO SATISFY THE COMPLETED SCOPE OF WORK FOR THE PROJECT; THESE DRAWINGS MAY NOT SHOW ALL AREAS, ELEMENTS, SIZES OR QUANTITIES OF EQUIPMENT TO BE REMOVED; THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS AND PROJECT DRAWINGS PRIOR TO THE START OF DEMOLITION OR REMOVALS FOR COORDINATION WITH THE INTENT OF THE COMPLETED WORK; ADDITIONAL REMOVALS AND/OR REPLACEMENT IN KIND OF ELEMENTS OR EQUIPMENT MAY BE REQUIRED TO ACCOMMODATE THE COMPLETED PROJECT AND ALL SUCH WORK SHALL BE INCLUDED AS PART OF THE CONTRACT
2. THE CONTRACTOR SHALL FIELD LOCATE ALL EXISTING UTILITIES PRIOR TO COMMENCEMENT OF DEMOLITION AND SHALL PROTECT ANY EXISTING UTILITIES TO REMAIN IN SERVICE
3. IN AREAS INDICATING DEMOLITION OF EXISTING PARTITIONS, DEMOLITION SHALL INCLUDE THE REMOVAL OF ALL ASSOCIATED DOORS AND FRAMES, ATTACHED EQUIPMENT, AND MEP/FA COMPONENTS (PIPE/WIRING, DUCTWORK, ETC.) FOR COMPLETE REMOVAL
4. PROTECT ALL EXISTING CONSTRUCTION TO REMAIN DURING DEMOLITION AND CONSTRUCTION
5. PATCH, REPAIR, AND PAINT/REFINISH ALL SURFACES TO MATCH EXISTING WHERE EXISTING CONSTRUCTION IS REMOVED OR ALTERED
6. PATCH, REPAIR, AND PAINT/REFINISH ANY SURFACES AND BUILDING ELEMENTS DAMAGED BY DEMOLITION OF ANY MEP ELEMENTS
7. PROVIDE TEMPORARY BRACING AND SHORING OF EXISTING WALLS AND STRUCTURAL ELEMENTS TO REMAIN AS REQUIRED FOR DEMOLITION OR NEW CONSTRUCTION UNTIL NEW STRUCTURAL SYSTEMS AND MODIFICATIONS ARE SECURE AND IN PLACE
8. ANY AND ALL DISCOVERED ARTIFACTS FOUND DURING DEMOLITION ARE THE PROPERTY OF THE OWNER AND SHALL BE SUITABLY STORED FOR THE OWNER'S ACQUISITION



PROJECT Alice Ward Library Carriage House Rehabilitation

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM
STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave, Suite 2A
Burlington, VT 05401
(802) 863-7225


MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

MARK	DESCRIPTION	DATE



PROJECT NORTH



DRAWING NAME
**DEMOLITION PLANS :
BASEMENT + 1ST FLOOR**

DRAWN RE DATE 01.20.26
CHECKED SCALE 1/4" = 1'-0"
DRAWING NUMBER

AD.101



DEMOLITION PLAN DRAWING LEGEND

- EXISTING CONSTRUCTION TO REMAIN
- EXISTING CONSTRUCTION TO BE REMOVED
- EXISTING CONSTRUCTION TO BE REMOVED AND SUITABLY STORED FOR REUSE

DEMOLITION PLAN GENERAL NOTES

1. DEMOLITION DRAWINGS ARE DIAGRAMMATIC IN NATURE AND ARE PROVIDED TO CONVEY THE DEMOLITION INTENT REQUIRED TO SATISFY THE COMPLETED SCOPE OF WORK FOR THE PROJECT; THESE DRAWINGS MAY NOT SHOW ALL AREAS, ELEMENTS, SIZES OR QUANTITIES OF EQUIPMENT TO BE REMOVED; THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS AND PROJECT DRAWINGS PRIOR TO THE START OF DEMOLITION OR REMOVALS FOR COORDINATION WITH THE INTENT OF THE COMPLETED WORK; ADDITIONAL REMOVALS AND/OR REPLACEMENT IN KIND OF ELEMENTS OR EQUIPMENT MAY BE REQUIRED TO ACCOMMODATE THE COMPLETED PROJECT AND ALL SUCH WORK SHALL BE INCLUDED AS PART OF THE CONTRACT
2. THE CONTRACTOR SHALL FIELD LOCATE ALL EXISTING UTILITIES PRIOR TO COMMENCEMENT OF DEMOLITION AND SHALL PROTECT ANY EXISTING UTILITIES TO REMAIN IN SERVICE
3. IN AREAS INDICATING DEMOLITION OF EXISTING PARTITIONS, DEMOLITION SHALL INCLUDE THE REMOVAL OF ALL ASSOCIATED DOORS AND FRAMES, ATTACHED EQUIPMENT, AND MEP/FA COMPONENTS (PIPE/WIRING, DUCTWORK, ETC.) FOR COMPLETE REMOVAL
4. PROTECT ALL EXISTING CONSTRUCTION TO REMAIN DURING DEMOLITION AND CONSTRUCTION
5. PATCH, REPAIR, AND PAINT/REFINISH ALL SURFACES TO MATCH EXISTING WHERE EXISTING CONSTRUCTION IS REMOVED OR ALTERED
6. PATCH, REPAIR, AND PAINT/REFINISH ANY SURFACES AND BUILDING ELEMENTS DAMAGED BY DEMOLITION OF ANY MEP ELEMENTS
7. PROVIDE TEMPORARY BRACING AND SHORING OF EXISTING WALLS AND STRUCTURAL ELEMENTS TO REMAIN AS REQUIRED FOR DEMOLITION OR NEW CONSTRUCTION UNTIL NEW STRUCTURAL SYSTEMS AND MODIFICATIONS ARE SECURE AND IN PLACE
8. ANY AND ALL DISCOVERED ARTIFACTS FOUND DURING DEMOLITION ARE THE PROPERTY OF THE OWNER AND SHALL BE SUITABLY STORED FOR THE OWNER'S ACQUISITION



PROJECT Alice Ward Library Carriage House Rehabilitation

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM
STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave., Suite 2A
Burlington, VT 05401
(802) 863-7225


MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE BID SET

RELEASE DATE
01.20.26

MARK	DESCRIPTION	DATE


PROJECT NORTH



DRAWING NAME
**DEMOLITION PLANS :
2ND FLOOR**

DRAWN	RE	DATE	01.20.26
CHECKED		SCALE	1/4" = 1'-0"
DRAWING NUMBER			

AD.102



CONSTRUCTION PLAN DRAWING LEGEND

EXISTING CONSTRUCTION TO REMAIN
NEW CONSTRUCTION
NEW BUILT-IN MILLWORK

CONSTRUCTION PLAN GENERAL NOTES

- THE CONSTRUCTION PLANS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL, STRUCTURAL, MECHANICAL, PLUMBING, AND ELECTRICAL DRAWINGS; ANY DISCREPANCY SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT PRIOR TO THE EXECUTION OF THE WORK.
- ALL DIMENSIONS ARE TO FACE OF FINISHED WALL UNLESS OTHERWISE NOTED.
- GIVEN THE AGE OF THE BUILDING IT SHALL BE ASSUMED THAT NOT ALL WALLS AND FLOORS ARE SQUARE, LEVEL, OR IN ALIGNMENT, AND THAT DIMENSIONS MAY VARY FROM FLOOR TO FLOOR AND SIDE TO SIDE OF THE BUILDING.
- MAINTAIN REQUIRED FIRE-RESISTANCE RATINGS FOR ALL EXISTING AND NEW ASSEMBLIES.
- ALL NEW PARTITIONS CONSTRUCTED IN ALIGNMENT WITH OR AS A CONTINUATION OF AN EXISTING PARTITION SHALL MATCH THE WIDTH AND CONSTRUCTION OF THE EXISTING PARTITION, UNLESS OTHERWISE NOTED.
- ALL NEW INTERIOR PARTITIONS SHALL CONSIST OF 2X4 WOOD STUD FRAMING AT 16" O.C. WITH 5/8" TYPE "X" GYPSUM WALLBOARD, EXCEPT WHERE OTHERWISE INDICATED; PROVIDE MOISTURE-RESISTANT GYPSUM WALLBOARD AT NEW ADA RESTROOM.
- AT ALL EXISTING PARTITIONS TO REMAIN, PATCH AND REPAIR EXISTING FINISHES AS REQUIRED TO MATCH EXISTING WHERE INTERSECTING WALLS HAVE BEEN REMOVED OR WHERE DAMAGE HAS OCCURRED; PATCH AND REPAIR EXISTING FINISH(ES), INCLUDING ANY HOLES OR GAPS LEFT BY THE REMOVAL OF ANY OBSOLETE MEP COMPONENTS INCLUDING, BUT NOT LIMITED TO, CONDUIT, DUCTWORK, HANGERS, ETC.



PROJECT Alice Ward Library Carriage House Rehabilitation

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM

STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave, Suite 2A
Burlington, VT 05401
(802) 863-7225


MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

RELEASE + REVISION LOG	MARK	DESCRIPTION	DATE



PROJECT NORTH



CONSTRUCTION PLANS : BASEMENT + 1ST FLOOR

DRAWN RE DATE 01.20.26
CHECKED SCALE 1/4" = 1'-0"
DRAWING NUMBER

A.101



CONSTRUCTION PLAN DRAWING LEGEND

■	EXISTING CONSTRUCTION TO REMAIN
■	NEW CONSTRUCTION
■	NEW BUILT-IN MILLWORK


CONSTRUCTION PLAN GENERAL NOTES

1. THE CONSTRUCTION PLANS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL, STRUCTURAL, MECHANICAL, PLUMBING, AND ELECTRICAL DRAWINGS; ANY DISCREPANCY SHALL BE BROUGHT TO THE ATTENTION TO THE ARCHITECT PRIOR TO THE EXECUTION OF THE WORK.
2. ALL DIMENSIONS ARE TO FACE OF FINISHED WALL UNLESS OTHERWISE NOTED.
3. GIVEN THE AGE OF THE BUILDING IT SHALL BE ASSUMED THAT NOT ALL WALLS AND FLOORS ARE SQUARE, LEVEL, OR IN ALIGNMENT, AND THAT DIMENSIONS MAY VARY FROM FLOOR TO FLOOR AND SIDE TO SIDE OF THE BUILDING.
4. MAINTAIN REQUIRED FIRE-RESISTANCE RATINGS FOR ALL EXISTING AND NEW ASSEMBLIES.
5. ALL NEW PARTITIONS CONSTRUCTED IN ALIGNMENT WITH OR AS A CONTINUATION OF AN EXISTING PARTITION SHALL MATCH THE WIDTH AND CONSTRUCTION OF THE EXISTING PARTITION, UNLESS OTHERWISE NOTED.
6. ALL NEW INTERIOR PARTITIONS SHALL CONSIST OF 2X4 WOOD STUD FRAMING AT 16" O.C. WITH 5/8" TYPE "X" GYPSUM WALLBOARD, EXCEPT WHERE OTHERWISE INDICATED; PROVIDE MOISTURE-RESISTANT GYPSUM WALLBOARD AT NEW ADA RESTROOM.
7. AT ALL EXISTING PARTITIONS TO REMAIN, PATCH AND REPAIR EXISTING FINISHES AS REQUIRED TO MATCH EXISTING WHERE INTERSECTING WALLS HAVE BEEN REMOVED OR WHERE DAMAGE HAS OCCURRED; PATCH AND REPAIR EXISTING FINISH(ES), INCLUDING ANY HOLES OR GAPS LEFT BY THE REMOVAL OF ANY OBSOLETE MEP COMPONENTS INCLUDING, BUT NOT LIMITED TO, CONDUIT, DUCTWORK, HANGERS, ETC.


MERP FUNDING SCOPE OF WORK

GENERAL NOTE:

THE LIMITED SCOPE OF WORK AS DEFINED HEREIN ON DRAWING 2/A.102, CONSTRUCTION PLAN: BASEMENT @ MAIN LIBRARY (MERP) IS FOR ENERGY EFFICIENCY WORK IN THE MAIN LIBRARY FUNDED BY THE VERNON MUNICIPAL ENERGY RESILIENCE GRANT PROGRAM (MERP). THIS WORK IS INCLUDED AS PART OF THE CARRIAGE HOUSE REHABILITATION PROJECT.



2 CONSTRUCTION PLAN : BASEMENT @ MAIN LIBRARY (MERP)
SCALE: 1/4" = 1'-0"



1 CONSTRUCTION PLAN : 2ND FLOOR
SCALE: 1/4" = 1'-0"



PROJECT Alice Ward Library Carriage House Rehabilitation

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM
STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave, Suite 2A
Burlington, VT 05401
(802) 863-7225


MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

MARK	DESCRIPTION	DATE

PROJECT NORTH



DRAWING NAME
**CONSTRUCTION PLANS :
2ND FLOOR + ROOF**

DRAWN RE DATE 01.20.26
CHECKED SCALE 1/4" = 1'-0"
DRAWING NUMBER

A.102

SEAL



9 2ND FLOOR PERSPECTIVE (LOOKING SOUTHWEST AT COMMUNITY ROOM)
SCALE: NTS



8 2ND FLOOR PERSPECTIVE (LOOKING NORTHEAST AT COMMUNITY ROOM)
SCALE: NTS




7 2ND FLOOR PERSPECTIVE (LOOKING SOUTHEAST)
SCALE: NTS




6 2ND FLOOR PERSPECTIVE (LOOKING SOUTHWEST)
SCALE: NTS



5 2ND FLOOR PERSPECTIVE (LOOKING NORTHEAST)
SCALE: NTS



4 1ST FLOOR PERSPECTIVE (LOOKING SOUTHEAST)
SCALE: NTS



3 1ST FLOOR PERSPECTIVE (LOOKING NORTHEAST)
SCALE: NTS



2 1ST FLOOR PERSPECTIVE (LOOKING NORTHWEST)
SCALE: NTS



1 1ST FLOOR PERSPECTIVE (LOOKING SOUTHWEST)
SCALE: NTS

PROJECT
Alice Ward Library Carriage House Rehabilitation

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM

STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave., Suite 2A
Burlington, VT 05401
(802) 863-7225

MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

MARK	DESCRIPTION	DATE


PROJECT NORTH

DRAWING NAME
INTERIOR RENDERINGS


DRAWN	RE	DATE	01.20.26
CHECKED		SCALE	NTS

DRAWING NUMBER

A.110



2 NORTH (RIGHT) ELEVATION
SCALE: 1/4" = 1'-0"



1 EAST (FRONT) ELEVATION
SCALE: 1/4" = 1'-0"

PROJECT
**Alice Ward Library Carriage
House Rehabilitation**

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM
STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave., Suite 2A
Burlington, VT 05401
(802) 863-7225

MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

MARK	DESCRIPTION	DATE

PROJECT NORTH

DRAWING NAME
EXTERIOR ELEVATIONS

DRAWN RE DATE 01.20.26

CHECKED SCALE 1/4" = 1'-0"

DRAWING NUMBER

A.201



PROJECT
**Alice Ward Library Carriage
House Rehabilitation**

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM

STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave., Suite 2A
Burlington, VT 05401
(802) 863-7225

MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26


MARK	DESCRIPTION	DATE

PROJECT NORTH

DRAWING NAME
EXTERIOR ELEVATIONS


DRAWN DATE 01.20.26
RE CHECKED DATE 01.20.26
SCALE 1/4" = 1'-0"
DRAWING NUMBER

A.202






4 SOUTHEAST PERSPECTIVE
SCALE: NTS




2 NORTHWEST PERSPECTIVE
SCALE: NTS



1 NORTHEAST PERSPECTIVE
SCALE: NTS

3 SOUTHWEST PERSPECTIVE
SCALE: NTS



PROJECT
**Alice Ward Library Carriage
House Rehabilitation**

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM

STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave., Suite 2A
Burlington, VT 05401
(802) 863-7225

MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

MARK	DESCRIPTION	DATE

PROJECT NORTH

DRAWING NAME
EXTERIOR RENDERINGS

DRAWN RE DATE 01.20.26
CHECKED SCALE NTS
DRAWING NUMBER

A.210

INTERIOR ROOM FINISH SCHEDULE


ROOM #	ROOM NAME	FLOOR		WALL		BASE		CEILING		REMARKS	
BASEMENT		EXISTING CONCRETE SLAB		EXISTING CRUSHED GRAVEL (CRAWLSPACE)		EXISTING RUBBER TREADING (LANDINGS) AND RUBBER TREADS AND RISERS (STAIRS)		EXISTING WOOD FLOORING, SATIN POLYURETHANE FINISH			
		EXISTING CARPET TILE		NEW RUBBER TREADING (LANDINGS) AND RUBBER TREADS AND RISERS (STAIRS)		EXISTING WOOD FLOORING		NEW PORCHANT TILE (LOORING)			
	001	OPEN STOR	X			NEW WOOD TREADS AND RISERS, SATIN POLYURETHANE FINISH		EXISTING EXPOSED FOUNDATION			
	002	STAIR	X			NEW GYPSUM WALL BOARD (GWB), PAINTED		NEW PARLOR HIGH (EAB) BOARD PANELING, PAINTED (OPAQUE) FINISH			
	003	LOCK STOR	X			EXISTING WOOD BASE, STAINED		NEW 1X6 TONGUE AND GROOVE WOOD PANELING, PAINTED			
	004	UTILITY	X			EXISTING WOOD BASE		EXISTING GYPSUM WALL BOARD (GWB), PAINTED			
	101	OPEN LIBRARY	X	X		EXISTING WOOD BASE		EXISTING GYPSUM WALL BOARD (GWB)			
	102	STAIR		X		X		X			
	103	HALL	X			X		X			
	104	STOR		X				X			
1ST FLOOR	105	ADA BR		X	X	X		X			
	106	STAIR		X	X			N/A			
	201	READING	X		X	X		X			
	202	PRIVACY	X		X	X		X			
	203	PRIVACY	X		X	X		X			
	204	STAIR		X		X	X	X			
	205	COMMUNITY	X		X	X		X			
	206	STOR		X		X	X	X			

PARTITION TYPES

EXTERIOR E1	1. EXISTING CONCRETE FOUNDATION 2. NEW 2" RIGID INSULATION (XPS) (R-10) 3. NEW 2X4 WOOD STUDS @ 16" O.C. WITH MINERAL WOOL BATT INSULATION (R-15) 4. NEW 5/8" TYPE 'X' GYPSUM WALL BOARD, PAINTED	
EXTERIOR E2	1. EXISTING WOOD CLAPBOARD SIDING 2. EXISTING 1" BOARD SHEATHING 3. EXISTING 4" X 4" STUD FRAMING @ 24" O.C. (VARIES) 4. NEW 4" DEPTH DENSE PACK CELLULOSE INSULATION (ALL STUD BAYS) 5. NEW POLYPROPYLENE FABRIC NETTING (INSULWEB® OR SIM.) 6. NEW SMART VAPOR RETARDER (CERTAINTEED MEMBRANE™ OR SIM.) 7. NEW 1X6 TONGUE-AND-GROOVE D-SELECT OR BETTER EASTERN WHITE PINE WOOD PANELING, PAINTED	
EXTERIOR E3	1. EXISTING WOOD CLAPBOARD SIDING 2. EXISTING 1" BOARD SHEATHING 3. EXISTING 4" X 4" STUD FRAMING @ 24" O.C. (VARIES) 4. NEW 4" DEPTH DENSE PACK CELLULOSE INSULATION (ALL STUD BAYS) 5. NEW POLYPROPYLENE FABRIC NETTING (INSULWEB® OR SIM.) 6. NEW SMART VAPOR RETARDER (CERTAINTEED MEMBRANE™ OR SIM.) 7. NEW 5/8" TYPE 'X' GYPSUM WALL BOARD, PAINTED	
INTERIOR 1	1. NEW 5/8" GYPSUM WALL BOARD, PAINTED 2. NEW 2X4 WOOD STUDS @ 16" O.C.; PROVIDE ACOUSTIC BATT INSULATION AT ALL BATHROOM AND PRIVACY ROOM PARTITIONS 3. NEW 5/8" GYPSUM WALL BOARD, PAINTED	
INTERIOR 2	1. NEW 5/8" GYPSUM WALL BOARD, PAINTED 2. NEW 2X4 WOOD STUDS @ 16" O.C.; PROVIDE ACOUSTIC BATT INSULATION AT ALL BATHROOM PARTITIONS 3. NEW 5/8" GYPSUM WALL BOARD, PAINTED	

ROOF TYPE

EXTERIOR R1	1. EXISTING ASPHALT SHINGLES 2. EXISTING ROOF SHEATHING 3. EXISTING 2" X 8" ROOF RAFTERS 4. NEW SISTERED 2X8 AND 7-1/4" LVLs (REF: STRUCTURAL) 5. NEW 2X4 WOOD STRAPPING; ATTACH TO UNDERSIDE OF RAFTERS 6. NEW CLOSED CELL SPRAY FOAM INSULATION (R-50 MIN.) 7. NEW 1X6 TONGUE-AND-GROOVE D-SELECT OR BETTER EASTERN WHITE PINE WOOD PANELING, TONGUE OIL FINISH	
INTERIOR		



DOOR SCHEDULE

FLOOR	TAG	TYPE	OPERATION	INTERIOR/ EXTERIOR	MATERIAL	WIDTH	HEIGHT	THICKNESS	hardware set	work type	fire rating	REMARKS
BASEMENT	001	NSB1	SWING BI-PART	EXTERIOR	METAL	8'-0" <small>[(23'-0")]</small>	6'-8"	1-3/4"	01	NEW	—	PROVIDE NEW DOOR AND FRAME AT EXISTING OPENING; VERIFY DIMENSIONS IN FIELD PRIOR TO FURNISH AND INSTALL
	002	NS1	SWING SIMPLE	INTERIOR	METAL	3'-0"	6'-8"	1-3/4"	02	NEW	60-MIN.	
	003	NS2	SWING SIMPLE	INTERIOR	METAL	3'-0"	6'-8"	1-3/4"	03	NEW	—	
	004	NS2	SWING SIMPLE	INTERIOR	METAL	3'-0"	6'-8"	1-3/4"	03	NEW	45-MIN.	
1ST FLOOR	101	ETR	SWING BI-PART	EXTERIOR	WOOD	7'-10" <small>[(23'-11")]</small>	7'-9" <small>±</small>	1-3/8" <small>±</small>	04	REHABILITATE	—	EXISTING HISTORIC CARRIAGE HOUSE DOORS TO BE REHABILITATED AND RECONFIGURED AS SHOWN; FINAL DETAILS PENDING
	102	NS3	SWING SIMPLE	INTERIOR	WOOD	3'-0"	6'-8"	1-3/4"	05	NEW	60-MIN.	
	103	NS4	SWING SIMPLE	EXTERIOR	METAL	3'-0"	6'-8"	1-3/4"	05	NEW	—	
	104	NS5	SWING SIMPLE	INTERIOR	WOOD	3'-0"	7'-0"	1-3/4"	06	NEW	45-MIN.	
	105	NS3	SWING SIMPLE	INTERIOR	WOOD	3'-0"	6'-8"	1-3/4"	07	NEW	—	
	106	NS5	SWING SIMPLE	INTERIOR	WOOD	3'-0"	7'-0"	1-3/4"	06	NEW	—	
2ND FLOOR	201					-NOT USED-						
	202	NS5	SWING SIMPLE	INTERIOR	WOOD	3'-0"	7'-0"	1-3/4"	08	NEW	—	
	203	NS5	SWING SIMPLE	INTERIOR	WOOD	3'-0"	7'-0"	1-3/4"	08	NEW	—	
	204	NS3	SWING SIMPLE	INTERIOR	WOOD	3'-0"	6'-8"	1-3/4"	05	NEW	60-MIN.	
	205	NSLB1	SLIDE BI-PART (OXO)	INTERIOR	WOOD	12'-0" <small>[(43'-2")]</small>	6'-8"	1-3/4"	09	NEW	—	
	206	NS3	SWING SIMPLE	INTERIOR	WOOD	3'-0"	6'-8"	1-3/4"	03	NEW	—	

DOOR SCHEDULE GENERAL NOTES

1. REFER TO DIVISION 08, OPENINGS, FOR ADDITIONAL INFORMATION AND SPECIFICATIONS
2. INSTALL ALL DOOR FRAMES, DOORS, AND DOOR HARDWARE PER MANUFACTURER'S SPECIFICATIONS; WHERE A DISCREPANCY EXISTS BETWEEN THE ARCHITECTURAL SPECIFICATIONS AND THE MANUFACTURER'S SPECIFICATIONS, THE MANUFACTURER'S SPECIFICATIONS SHALL GOVERN
3. ALL NEW EXTERIOR AND INTERIOR METAL DOORS SHALL BE INSTALLED IN KNOCKED-DOWN (KD) HOLLOW METAL FRAMES; WHERE FIRE-RESISTANCE RATINGS ARE REQUIRED, FULL DOOR ASSEMBLY SHALL COMPLY WITH NFPA 80, STANDARD FOR FIRE DOORS AND OTHER OPENING PROTECTIVES (2019)
4. ALL NEW NON-FIRE-RESISTANCE RATED INTERIOR DOOR FRAMES SHALL BE STAIN GRADE POPLAR WITH APPLIED FLAT STOPS
5. ALL NEW INTERIOR FIRE-RESISTANCE RATED JAMBS TO BE FERCHE MILLWORK, INC. F343 (45-MIN.) OR F344 (60-MIN.) FIRE RATED LAMINATED DOOR FRAMES, GRANDOR FRAMES WOOD VENERED 45-60-MIN. FIRE FRAME, OR SIM.; RED OAK FINISH; PROVIDE SPECIFICATION FOR ARCHITECT APPROVAL
6. DOOR TYPE NS3 BASIS OF DESIGN: VT INDUSTRIES EGGRS COLLECTION, DOOR #E107 (5-PANEL); FLAT PANEL
7. DOOR TYPE NS5 BASIS OF DESIGN: VT INDUSTRIES EGGRS COLLECTION, DOOR #E201 (1-LITE); FLAT PANEL

WINDOW SCHEDULE

FLOOR	TAG	TYPE	CONFIGURATION	OPERATION	WIDTH	HEIGHT	SILL HEIGHT	HEAD HEIGHT	WORK TYPE	SCREEN	STORM WINDOW	REMARKS
1ST FLOOR	1.01	A	1-LITE	FIXED	4'-0"	6'-3"	0'-4"	6'-7"	NEW	—	—	NEW WINDOW AT EXISTING OPENING; VERIFY DIMENSIONS IN FIELD; PROVIDE TEMPERED GLASS
	1.02	ETR	2/2	DOUBLE-HUNG	2'-8" <small>±</small>	4'-6" <small>±</small>	2'-1" <small>±</small> </td					

R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS

APPLIANCE SCHEDULE
2023.20 : ALICE WARD LIBRARY CARRIAGE HOUSE REHABILITATION
RELEASE: BID SET (JANUARY 20, 2026)

APPLIANCE SCHEDULE GENERAL NOTES:

1. ALL APPLIANCES SHALL BE INSTALLED PER THE MANUFACTURER'S SPECIFICATIONS AND ALL APPLICABLE BUILDING CODES IN FORCE. WHERE DISCREPANCIES EXIST, BRING TO THE ATTENTION OF THE ARCHITECT.
2. COORDINATE INSTALLATION OF ALL APPLIANCES WITH ALL APPLICABLE TRADES AS REQUIRED.
3. ANY DISCREPANCIES BETWEEN REQUIRED APPLIANCE DIMENSIONAL CLEARANCES AND THE DRAWINGS OR EXISTING FIELD CONDITIONS SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT PRIOR TO INSTALL.
4. ALL APPLIANCES SPECIFIED FOR THIS PROJECT SHALL BE CONSIDERED BASIS OF DESIGN. SUBSTITUTIONS MAY BE PRESENTED TO THE OWNER AND ARCHITECT FOR CONSIDERATION.
5. PROVIDE SUBMITTALS OF ALL APPLIANCES FOR ARCHITECT APPROVAL.

TAG	QTY	TYPE	MANUFACTURER	MODEL	COLOR / FINISH	NOTES
AP01	1	REFRIGERATOR	KITCHENAID	KRFF1365PS	SILVER	
AP02	1	30" ELECTRIC RANGE	KITCHENAID	KSEG700ESS	SILVER	ADA-COMPLIANT
AP03	1	RANGE HOOD	Z-LINE	617-30	SILVER	



PROJECT
**Alice Ward Library Carriage
House Rehabilitation**

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
2023.20

PROJECT TEAM

STRUCTURAL ENGINEER
Engineering Ventures, PC
208 Flynn Ave., Suite 2A
Burlington, VT 05401
(802) 863-7225

MEP ENGINEER
DuBois & King, Inc.
10 Corporate Dr., Suite 210
Bedford, NH 03110
(603) 637-1043

RELEASE
BID SET

RELEASE DATE
01.20.26

MARK	DESCRIPTION	DATE

PROJECT NORTH

DRAWING NAME
SCHEDULES

R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS

TOILET ACCESSORIES SCHEDULE
2023.20 : ALICE WARD LIBRARY CARRIAGE HOUSE REHABILITATION
RELEASE: BID SET (JANUARY 20, 2026)

TOILET ACCESSORIES SCHEDULE GENERAL NOTES:

1. REFER TO SPECIFICATION SECTION 102800 – TOILET ACCESSORIES, FOR ADDITIONAL INFORMATION
2. ALL TOILET ACCESSORIES SHALL BE INSTALLED PER THE MANUFACTURER'S SPECIFICATIONS.
3. ALL TOILET ACCESSORIES INSTALLED AT ADA-COMPLIANT RESTROOMS SHALL BE INSTALLED WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL ACCESSIBILITY REGULATIONS IN FORCE. ANY DISCREPANCIES BETWEEN THE DRAWINGS AND THESE REGULATIONS SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT PRIOR TO INSTALL.
4. PROVIDE FIRE-TREATED IN-WALL BLOCKING FOR ALL TOILET ACCESSORIES AS REQUIRED.
5. COORDINATE INSTALLATION OF ALL TOILET ACCESSORIES WITH ALL APPLICABLE TRADES AS REQUIRED.
6. ALL TOILET ACCESSORIES SPECIFIED FOR THIS PROJECT SHALL BE CONSIDERED BASIS OF DESIGN. SUBSTITUTIONS MAY BE PRESENTED TO THE OWNER AND ARCHITECT FOR CONSIDERATION.
7. PROVIDE SUBMITTALS OF ALL TOILET ACCESSORIES FOR ARCHITECT APPROVAL.

TAG	QTY	TYPE	MANUFACTURER	MODEL	COLOR / FINISH	NOTES
AC01	1	TOILET TISSUE DISPENSER	BOBRICK	B-9547	STAINLESS STEEL (SATIN)	
AC02	1	36" GRAB BAR	BOBRICK	B-9806x36	STAINLESS STEEL (SATIN)	
AC03	1	42" GRAB BAR	BOBRICK	B-9806x42	STAINLESS STEEL (SATIN)	
AC04	1	MIRROR	BOBRICK	B-290 2436	STAINLESS STEEL (SATIN)	
AC05	1	PAPER TOWEL DISPENSER	BOBRICK	B-35903	STAINLESS STEEL (SATIN)	
AC06	1	BABY CHANGING STATION	KOALA KARE	KB200-05	WHITE GRANITE	
AC07	1	COAT HOOK	BOBRICK	B.9542	STAINLESS STEEL (SATIN)	

2023.20 : ALICE WARD LIBRARY

TOILET ACCESSORIES SCHEDULE

SHEET 1 OF 1

R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS

SIGNAGE SCHEDULE
2023.20 : ALICE WARD LIBRARY CARRIAGE HOUSE REHABILITATION
RELEASE: BID SET (JANUARY 20, 2026)

SIGNAGE SCHEDULE GENERAL NOTES:

1. REFER TO SPECIFICATION SECTION 101400 – SIGNAGE, FOR ADDITIONAL INFORMATION
2. INSTALL ALL SIGNAGE PER MANUFACTURER'S SPECIFICATIONS.
3. PROVIDE SUBMITTALS OF ALL SIGNAGE FOR ARCHITECT APPROVAL.
4. VERIFY ALL FINAL SIGN LOCATIONS IN FIELD WITH ARCHITECT PRIOR TO INSTALL.

TAG	QTY	SIGN IMAGE	SIZE (W X H)	LOCATION	MOUNTING HEIGHT	NOTES
S101	1		9" X 6"	1. INTERIOR; ADJACENT TO DOOR 105 (LATCH SIDE) @ HALL 103 (FOR ADA BR 105)	+57" A.F. (CENTERLINE)	BASIS OF DESIGN: COMPLIANCESIGNS.COM 'CHARCOAL GRAY ADA BRILLE ACCESSIBLE RESTROOM SIGN WITH SYMBOL' (SKU: RRE-35193-White_on_CharcoalGray CS302345)
S102	1		8" X 4"	1. INTERIOR; ADJACENT TO DOOR 004 (LATCH SIDE) @ OPEN STOR 001 (FOR UTILITY 004)	+54" A.F. (CENTERLINE)	BASIS OF DESIGN: COMPLIANCESIGNS.COM 'CHARCOAL GRAY ADA BRILLE MECHANICAL ROOM SIGN WITH TACTILE TEXT' (SKU: RSME-426_White_on_CharcoalGray CS196222)

2023.20 : ALICE WARD LIBRARY

SIGNAGE SCHEDULE

SHEET 1 OF 1

DRAWN RE DATE 01.20.26
CHECKED SCALE
DRAWING NUMBER

A.602

PLUMBING GENERAL NOTES

QUALITY OF WORK

- CONTRACT DOCUMENTS ARE IN PART DIAGRAMMATIC, INTENDED TO CONVEY SCOPE & ARRANGEMENT OF WORK. CONSULT ELECTRICAL AND STRUCTURAL CONSTRUCTION DRAWINGS FOR FAMILIARITY WITH CONDITIONS AFFECTING WORK. VERIFY SPACES IN WHICH WORK MUST BE PERFORMED BY ON-SITE MEASUREMENTS. DO NOT SCALE DRAWINGS.
- CONTRACTOR MUST VERIFY EXISTING CONDITIONS AS THERE MAY BE VARIOUS CONDITIONS AT THE SITE WHICH DO NOT SHOW ON THE ACCOMPANYING DRAWINGS, OR WHICH ARE AT VARIANCE WITH THE CONDITIONS INDICATED ON THE DRAWINGS. IT IS IMPORTANT THAT EACH BIDDER VISIT THE SITE TO BECOME ACQUAINTED WITH THE EXISTING CONDITIONS, AND TO TAKE THESE CONDITIONS INTO CONSIDERATION WHEN PREPARING THEIR PROPOSAL. EACH BIDDER MUST OBTAIN INFORMATION OR MAKE MEASUREMENTS DESIRED. LACK OF KNOWLEDGE RELATIVE TO THE EXISTING SITE CONDITIONS IS NOT ALLOWED AS A BASIS FOR EXTRA COMPENSATION.
- THE PLUMBING CONTRACTOR MUST PROVIDE MATERIALS, EQUIPMENT, AND LABOR TO FABRICATE NEW PLUMBING INSTALLATIONS AS SHOWN ON THE DRAWINGS AND AS SPECIFIED HEREIN:
 - FURNISH AND INSTALL PIPING, CONNECTIONS, AND HARDWARE NECESSARY FOR AN ENTIRE OPERATING SYSTEM.
 - A LICENSED PLUMBER MUST PERFORM PLUMBING WORK.
- WHERE TWO OR MORE ITEMS OF THE SAME TYPE OF EQUIPMENT ARE REQUIRED, THE PRODUCT OF ONE MANUFACTURER MUST BE USED.
- WORKSMANSHIP, MATERIALS, AND EQUIPMENT MUST BE GUARANTEED FOR A PERIOD OF ONE YEAR AFTER ACCEPTANCE BY THE OWNER.

CODES/PERMITS

- WORK MUST BE PERFORMED IN STRICT ACCORDANCE WITH THE UNDERWRITERS LABORATORY STANDARDS AND MUNICIPAL, STATE AND OTHER AUTHORITIES' REGULATIONS, PUBLIC AND PRIVATE, HAVING JURISDICTION. REPORT DISCREPANCIES WITH SUCH REGULATIONS TO ENGINEER AND DO NOT PROCEED WITH WORK UNTIL WRITTEN AUTHORIZATION IS RECEIVED FROM THE ENGINEER.
- NECESSARY FEES, PERMITS, AND APPROVALS AS REQUIRED BY THE WORK OF THESE DRAWINGS AND SPECIFICATIONS MUST BE OBTAINED AND PASSED BY THIS CONTRACTOR.

COORDINATION OF WORK

- COORDINATE CONSTRUCTION OF PLUMBING WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, MECHANICAL, ELECTRICAL WORK, ETC., SHOWN ON OTHER CONTRACT DOCUMENT DRAWINGS.
- PLUMBING CONTRACTOR MUST DISCONNECT, REMOVE, AND PROPERLY DISPOSE OF PLUMBING MATERIALS AND EQUIPMENT IN ORDER TO PREPARE EXISTING AREAS AND BUILDINGS FOR RENOVATION WORK. CONTRACTOR TO CLOSELY COORDINATE WITH THE GENERAL CONTRACTOR TO PROVIDE ENTIRE DEMOLITION OF NECESSARY AREAS AND SYSTEMS. CONTRACTOR MUST REVIEW PROJECT DOCUMENTS FOR EXTENT OF DEMOLITION REQUIREMENTS – ENTIRE DEMOLITION SCOPE IS NOT NECESSARILY NOTED ON THE PLUMBING DRAWINGS.
- THE LOCATIONS OF ITEMS SHOWN ON THE DRAWINGS OR CALLED FOR IN THE SPECIFICATIONS THAT ARE NOT DEFINITIVELY FIXED BY DIMENSIONS ARE APPROXIMATE ONLY. THE EXACT LOCATIONS NECESSARY TO SECURE THE MOST DESIRABLE CONDITIONS AND RESULTS MUST BE DETERMINED BY THE PROJECT SITE CONDITIONS AND MUST HAVE THE APPROVAL OF THE ENGINEER BEFORE BEING INSTALLED. DO NOT SCALE THE DRAWINGS.
- PROVIDE LOCATIONS OF REQUIRED ACCESS PANELS FOR INSTALLATION IN WALLS AND CEILINGS TO SERVICE VALVES, DAMPERS, AND OTHER CONCEALED PLUMBING EQUIPMENT. GENERAL CONTRACTOR MUST FURNISH & INSTALL ACCESS PANELS.
- LOCATIONS AND SIZES OF FLOOR, WALL, AND ROOF OPENINGS MUST BE COORDINATED WITH OTHER TRADES INVOLVED. OPENINGS IN FIRE WALLS DUE TO PIPING MUST BE FIRE STOPPED.

PIPING

- TAKE NECESSARY MEASUREMENTS AT THE BUILDING AND FABRICATE THE PIPING ON THE SITE, IF REQUIRED, TO PROVIDE AN APPROVABLE INSTALLATION.
- INSTALL PIPING CONCEALED ABOVE CEILING OR IN WALL CHASES UNLESS OTHERWISE INDICATED. EXPOSED PIPING IS TO BE 3/4" MINIMUM FROM WALL SURFACE.
- PROVIDE STOP VALVES AT FIXTURE AND EQUIPMENT SUPPLIES. EXPOSED FIXTURE CONNECTIONS MUST BE CHROME PLATED. PROVIDE VACUUM BREAKERS WHERE REQUIRED BY CODE.
- PROVIDE NECESSARY HANGERS FOR SUPPORT OF HORIZONTAL AND VERTICAL PIPING IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- PROVIDE NECESSARY UNIONS TO FACILITATE REPAIR OF EQUIPMENT AND FITTINGS.
- IDENTIFICATION: CONTINUOUSLY IDENTIFY PIPING 8' ON CENTER.
- PROVIDE NECESSARY VALVES, PIPES, FITTINGS, AND WATER HAMMER ARRESTORS THROUGHOUT THE SYSTEM TO ELIMINATE WATER HAMMER.
- PROVIDE NECESSARY FLOOR AND WALL CLEANOUTS THROUGHOUT THE SYSTEM FOR A CODE COMPLIANT INSTALLATION.
- PIPING AT FLOOR PENETRATIONS AND PENETRATIONS OF FIRE RATED WALLS MUST BE SEALED WITH FIRE CAULK (BOTH SIDES WHERE ACCESSIBLE).
- COMPLY WITH LOW LEAD REQUIREMENTS. PIPING, FITTINGS, AND VALVES USED FOR HUMAN CONSUMPTION (WATER FOR DRINKING OR COOKING) MUST MEET THE MOST RECENT NSF/ANSI LOW LEAD STANDARD (<.025% WEIGHTED AVERAGE LEAD CONTENT FOR WETTED SURFACES).


PLUMBING LEGENDS & ABBREVIATIONS							
PLUMBING SYSTEMS		PIPE VALVES		DRAWING NOTATIONS		ABBREVIATIONS	
— - - - -	COLD WATER	— - - - -	GATE VALVE	Ø	PHASE OR ROUND DIAMETER	AD	AREA DRAIN
— - - - -	HOT WATER	— - - - -	GLOBE VALVE	—	DEMO LINE	BTU	BRITISH THERMAL UNITS
— - - - -	HOT WATER RECIRCULATION	— - - - -	CHECK VALVE	—	EXISTING LINE	CO	CLEANOUT
— - - - -	SANITARY	— - - - -	BACKFLOW PREVENTER	—	REVISION CLOUD WITH REVISION NUMBER	CPVC	CHLORINATED POLYVINYL CHLORIDE (PIPE)
— - - - -	SANITARY LINE BELOW FLOOR/GRADE	— - - - -	BALL VALVE	—	CONNECT TO EXISTING	DCW	DOMESTIC COLD WATER
— - - - -	SANITARY VENT	— - - - -	SAFETY RELIEF VALVE	—	REMOVE EXISTING	DF	DRINKING FOUNTAIN
— - - - -	SD	— - - - -	BUTTERFLY VALVE	—	EXISTING TO REMAIN	DH	DOMESTIC HOT WATER
— - - - -	STORM DRAINAGE	— - - - -	ELECTRIC SOLENOID ACTUATED SAFETY SHUTOFF VALVE	—	EFFICIENCY FACTOR	DHWC	DOMESTIC HOT WATER RECIRCULATION
— - - - -	STORM DRAINAGE BELOW FLOOR/GRADE	— - - - -	PRESSURE REGULATING/REDUCING VALVE	—	ET	DS	DOWNSPOUT
— - - - -	CA	— - - - -	PRESSURE GAUGE WITH VALVE	—	EW	DW	DISHWASHER
— - - - -	COMPRESSED AIR	— - - - -	BALANCING VALVE	—	FLOOR CLEANOUT	DWH	DOMESTIC WATER HEATER
— - - - -	N	— - - - -	PLUMBING EQUIPMENT	—	FD	DRAIN, WASTE, AND VENT	
— - - - -	MEDICAL GAS: NITROGEN	— - - - -	(PLUMBING & DRAINAGE INSTITUTE SIZE CATEGORY)	—	FDC	EXISTING TO REMAIN	
— - - - -	NO	— - - - -	WATER HAMMER ARRESTOR	—	FS	EFFICIENCY FACTOR	
— - - - -	MEDICAL GAS: NITROUS OXIDE	— - - - -	FLOOR DRAIN TRAP PRIMER	—	GI	ET	
— - - - -	O	— - - - -	FLOOR DRAIN	—	EW	FLOOR SINK	
— - - - -	MEDICAL GAS: OXYGEN	— - - - -	ROOF DRAIN	—	FCC	HOSE BIBB	
— - - - -	VAC	— - - - -	FLOOR CLEANOUT	—	MS	INDIRECT WASTE	
— - - - -	MEDICAL GAS: VACUUM	— - - - -	WALL CLEANOUT	—	MTD	LAVATORY	
— - - - -	MA	— - - - -	FIXTURE OR DRAIN TRAP	—	NFB	MOP SINK	
— - - - -	MEDICAL GAS: COMPRESSED AIR	— - - - -	HOSE BIBB	—	PRV	NON-FREEZE HOSE BIBB	
— - - - -	PIPE FITTINGS	— - - - -	WALL HYDRANT	—	PVC	PRESSURE REDUCING VALVE	
— - - - -	UNION	— - - - -	CIRCULATOR PUMP	—	RD	POLYVINYL CHLORIDE (PIPE)	
— - - - -	STRAINER	— - - - -	—	—	RD	ROOF DRAIN	
— - - - -	STRAINER WITH BLOW DOWN VALVE	— - - - -	—	—	RD	RAIN LEADER	
— - - - -	FLOW DIRECTION	— - - - -	—	—	S	SANITARY WASTE	
— - - - -	PIPE TURNED UP	— - - - -	—	—	SD	STORM DRAINAGE	
— - - - -	PIPE TURNED DOWN	— - - - -	—	—	TMV	TMV	
— - - - -	TEE BOTTOM TAKE-OFF	— - - - -	—	—	U	URINAL	
— - - - -	TEE TOP TAKE-OFF	— - - - -	—	—	V	VENT	
— - - - -	PIPE CONTINUED	— - - - -	—	—	VTR	VENT THROUGH ROOF	
— - - - -	PIPE CAPPED	— - - - -	—	—	WC	WC	
— - - - -	CONCENTRIC REDUCER	— - - - -	—	—	WCO	WALL CLEANOUT	
— - - - -	ECCENTRIC REDUCER	— - - - -	—	—	WH	WALL HYDRANT	
— - - - -	FLEXIBLE PIPE CONNECTOR	— - - - -	—	—	WSFU	WATER SUPPLY FIXTURE UNITS	
— - - - -	FLOW SWITCH	— - - - -	—	—	—	—	
— - - - -	MANUAL AIR VENT	— - - - -	—	—	—	—	
— - - - -	AUTOMATIC AIR VENT	— - - - -	—	—	—	—	

PLUMBING FIXTURE SCHEDULE								
ITEM	DESCRIPTION	BASIS OF DESIGN MANUFACTURER	BASIS OF DESIGN MODEL	TRIM & ACCESSORIES	CONNECTION SIZE			REMARKS
					0"	0"	1/2"	
PHB-1	Ecolotrol Ceramic Disc Wall Hydrant, Encased, Non-Freeze, Anti-Siphon, Automatic Draining	Zurn Industries, LLC	Z1320XL					
L-1	LUCERNE Basin, 4" (102mm) centres, 20-1/2" x 18-1/4" x 8-1/8" (511mm x 464mm x 206mm) deep, ADA compliant, wall hung, vitreous china, splash back, front overflow, self-draining deck, for concealed arm support.	AMERICAN STANDARD	0355.012	SYMONS SYMMETRIX S202G FAUCET, ADA COMPLIANT SINGLE LEVER, NON-AERATED LAMINAR SPRAY AT 0.5 GPM, PROVIDE FLOOR MOUNTED WALL CARRIER ZURN 21224 SERIES WITH BACK PLATE. PROVIDE WATTS 1/2" LEAD FREE LF480 LAVATORY TEMPERING VALVE	2"	1 1/2"	1/2"	LOW FLOW AERATOR TO BE PROVIDED WITH FAUCET. FAUCET MUST CONTAIN NO MORE THAN 0.25% WEIGHTED AVERAGE LEAD CONTENT.
MS-1	Mop Service Basin	FIAT	MSB2424	SERVICE FAUCET B30AA WITH VACUUM BREAKER, HOSE & BRACKET, MOP HOLDER	3"	1 1/2"	3/4"	SS WALL GUARDS
S-1	Lustertone Single Bowl sink, ADA compliant	Elkay Manufacturing	LRAD19185	SYMONS ORIGIN KITCHEN FAUCET SK23, ADA COMPLIANT, 1.0 GPM AERATOR	2"	1 1/2"	1/2"	LOW FLOW AERATOR TO BE PROVIDED WITH FAUCET. FAUCET MUST CONTAIN NO MORE THAN 0.25% WEIGHTED AVERAGE LEAD CONTENT.
WC-1	Two-Piece Close Coupled Toilet, ADA compliant	TOTO	CST454CEF	AMERICAN STANDARD SEAT MODEL 5321.110 EVERCLEAN ELONGATED SEAT WITH SLOW CLOSE SNAP-OFF HINGES	3"	2"	1/2"	PROVIDE WITH TRIP LEVER ON APPROACH SIDE

WATER HEATER SCHEDULE												
TAG	BASIS OF DESIGN MANUFACTURER	BASIS OF DESIGN MODEL	TYPE	FIRST HOUR GPH	CONTINUOUS GPH	TEMPERATURE RISE	STORAGE GALLONS	HEATING ELEMENT KW	ELECTRICAL			REMARKS
									VOLTAGE	PHASE	Hz	
WH-1	BRADFORD WHITE	AEROTHERM RE2H65T10	HPWH	79	24	90 °F	65	4 KW	240 V	1	60 Hz	

CONDENSATE PUMP SCHEDULE											
TAG	LOCATION	SERVES	BASIS OF DESIGN MANUFACTURER	BASIS OF DESIGN MODEL	GPH	WPD (FT)	WATTS	VOLTS	PH	HZ	REMARKS

R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS



PROJECT ALICE WARD LIBRARY

PROJECT NUMBER
30597

CONSULTANTS

**DuBois
& King** Inc.

ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
www.dubois-king.com.
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
www.dubois-king.com.
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE


USE DATE

RELEASE & REVISION LOG

EST. 1970

EXISTING BASEMENT - PLUMBING

SCALE: 1/4" = 1'



BASEMENT PLAN - PLUMBING

SCALE: 1/4" = 1'-0"

PLUMBING KEYNOTES

1 SLOPE CONDENSATE DRAIN DOWN FROM FAN COIL UNITS. TERMINATE 12" MIN ABOVE FINISHED GRADE WITH DOWNTURN ELBOW AND INSECT SCREEN. INSULATE WITH 1/2" THICK FIBERGLASS WITH ASJ FACING.



NG NAME

BASEMENT PLAN - PLUMBING

PLUMBING
I JJC DATE 09.30.2
ED JHP


NUMBER

P1.1



R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS

52 State St., 2nd Floor | Montpelier, VT 05602
(802) 232-2628 | info@edwardsandcompany.com
www.edwardsandcompany.com



PROJECT
**ALICE WARD
LIBRARY**

PROJECT NUMBER
530597

CONSULTANTS

**DuBois
& King** INC.


ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
www.duboisandking.com
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

RELEASE

RELEASE DATE

RELEASE & REVISION LOG		
MARK	REVISION DESCRIPTION	DATE

PROJECT NORTH




**1ST & 2ND
FLOOR PLAN -
PLUMBING**

DRAWN JJC DATE 09.30.25
CHECKED JHP
DRAWING NUMBER

P1.2


CD SET
FOR BIDDING
09.30.25



DOMESTIC WATER HEATING PIPING SCHEMATIC

SCALE: NOT TO SCALE

SE



PROJECT
**ALICE WARD
LIBRARY**

PROJECT NUMBER
530597

CONSULTANT

DuBois & King Inc.

ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
www.dubois-king.com.
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

RELEASE

RELEASE DATE

COORDINATE WITH MECHANICAL DWG'S

6" MIN

6" MIN

BROOM FINISH

OUTLINE OF MECH EQUIPMENT

3/4" CHAMFER (TYPICAL)

EXIST CONC SLAB

4"

8"

5 1/2"

#4 @ 12" E.W.

PLACE 1" CLEAR FROM TOP

EMBED 2 1/2" INTO CONCRETE USING HILTI HIT RE 500 ADHESIVE


#4 DWLS @ 24" o/c MINIMUM 1#4 AT EACH CORNER

1. CONCRETE SHALL BE STONE CONCRETE HAVING A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI AT 28 DAYS.
2. COORDINATE SIZES, LOCATIONS AND QUANTITIES WITH MECHANICAL AND ARCHITECTURAL DRAWINGS.

TYPICAL INTERIOR EQUIPMENT PAD DETAIL

SCALE: NOT TO SCALE

PROJECT NORTH



DRAWING NAME

PLUMBING DETAILS

DRAWN	JJC	DATE	09.30.2
CHECKED	JHP		
DRAWING NUMBER			


P5_1

MECHANICAL LEGENDS & ABBREVIATIONS

NOTE: NOT ALL SYMBOLS/ABBREVIATIONS SHOWN IN THE LEGEND ARE USED IN THIS DRAWING SET. IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY CONTENT SHOWN ON DRAWINGS.			
DUCTWORK	PIPING SYSTEMS	CONTROLS & BALANCING	ABBREVIATIONS
20x12	RECTANGULAR DUCT, FIRST NUMBER IS DIMENSION IN VIEW OF DRAWING	PC PUMPED STEAM	Ø DIAMETER
20"	ROUND RIGID DUCT	CD CONDENSATE DRAIN	A AMPS/AMPERAGE
	SUPPLY/OUTSIDE AIR DUCT ELBOW UP/DOWN	L REFRIGERATED LIQUID	AA ALL AROUND
	RETURN DUCT ELBOW UP/DOWN	S REFRIGERANT SUCTION	ABV AUTOMATIC BALANCE VALVE
	EXHAUST DUCT ELBOW UP/DOWN	CWR CONDENSER WATER RETURN	ACV MOTORIZED VALVE
20x20	RECTANGULAR DUCT 90° MITERED ELBOW WITH TURNING VANES	CWS CONDENSER WATER SUPPLY	AD ACCESS DOOR
20x20	TYPICAL LONG RADIUS ELBOW, RECTANGULAR/ROUND DUCT	GHR GLYCOL HEATING RETURN	AFF ABOVE FINISH FLOOR
	TYPICAL BRANCH DUCT 45° TAKE-OFF W/ VOLUME DAMPER	GHS GLYCOL HEATING SUPPLY	AI ANALOG INPUT
	DUCT RISE	LPS LOW PRESSURE STEAM	AO ANALOG OUTPUT
	DUCT SET DOWN	MPS MEDIUM PRESSURE STEAM	APD AIR PRESSURE DROP
	FLEXIBLE DUCT	HPS HIGH PRESSURE STEAM	ARCH (ARCHITECTURAL)
	FIRE DAMPER	LPC LOW PRESSURE CONDENSATE	ATC AUTOMATIC TEMPERATURE CONTROL
	SMOKE DAMPER	MPC MEDIUM PRESSURE CONDENSATE	AWT AVERAGE WATER TEMPERATURE
	FIRE & SMOKE DAMPER	HPC HIGH PRESSURE CONDENSATE	BAS BUILDING AUTOMATION SYSTEM
FD	DUCT SMOKE DAMPER	HWR HEATING HOT WATER RETURN	BF BOILER FEEDWATER
	DUCT SOUND ATTENUATION LINING	HWS HEATING HOT WATER SUPPLY	BHP BRAKE HORSEPOWER
	BACKDRAFT DAMPER	MU MAKE-UP WATER	BOD BOTTOM OF DUCTWORK (ELEVATION)
	BAROMETRIC RELIEF DAMPER	CHWR CHILLED WATER RETURN	BTU/H BRITISH THERMAL UNITS PER HOUR
	FLEXIBLE DUCT CONNECTOR	CHWS CHILLED WATER SUPPLY	C COMMON
	EQUIPMENT FLEX CONNECTOR	GCR CHILLED GLYCOL RETURN	CAPACITY
	ELEVATION OF TOP OF DUCT (TOD) AFF	GCS CHILLED GLYCOL SUPPLY	CFM CUBIC FEET PER MINUTE
	ELEVATION OF BOTTOM OF DUCT (BOD) AFF	CTR COOLING TOWER RETURN	CKT CIRCUIT
	DIRECTION OF SUPPLY AIR FLOW	CTS COOLING TOWER SUPPLY	CONN CONNECTION
	DIRECTION OF RETURN OR EXHAUST AIR FLOW	FOS FUEL OIL SUPPLY	COP COEFFICIENT OF PERFORMANCE
	SUPPLY FAN ROOF MOUNTED	FOR FUEL OIL RETURN	CP CONTROL PANEL
	EXHAUST FAN ROOF MOUNTED	PIPE FITTINGS	db DRY BULB TEMPERATURE
	SMOKE DETECTOR	UNION	DCW DOMESTIC COLD WATER
	FAN (SCHEMATIC)	STRAINER	DDC DIRECT DIGITAL CONTROL
	SUPPLY AIR DIFFUSER, REGISTER, OR GRILLE	STRAINER WITH BLOW DOWN VALVE	DI DIGITAL INPUT
	RETURN AIR REGISTER OR GRILLE	FLOW DIRECTION	DIA. DIAMETER
	EXHAUST AIR REGISTER OR GRILLE	PIPE TURNED UP	DN DOWN
		PIPE TURNED DOWN	DO DIGITAL OUTPUT
		TEE BOTTOM TAKE-OFF	DR DRAIN
		TEE TOP TAKE-OFF	DWG DRAWING
		CONCENTRIC REDUCER	DWV DRAIN, WASTE, VENT
		ECCENTRIC REDUCER	EXISTING
		THERMOMETER	E/A EXHAUST AIR
		AUTOMATIC AIR VENT	EAT ENTERING AIR TEMPERATURE
		CIRCULATOR PUMP	EC ELECTRICAL CONTRACTOR
		FAT FLOAT & THERMOSTATIC TRAP	ECON ECONOMIZER
		PIPE CAPPED	EDB ENTERING DRY BULB
		PIPE ANCHOR	EER ENERGY EFFICIENCY RATIO
		PIPE VALVES	EFF EFFICIENCY
		GATE VALVE	ESP EXTERNAL STATIC PRESSURE
		GLOBE VALVE	EWB ENTERING WET BULB
		CHECK VALVE	EWT ENTERING WATER TEMPERATURE
		BACKFLOW PREVENTER RPZ ASSY	FA FREE AREA
		BALL VALVE	FLA FULL LOAD AMPS
		SAFETY RELIEF VALVE	FOB FLAT ON BOTTOM
		BUTTERFLY VALVE	FOT FLAT ON TOP
		TRIPLE DUTY VALVE	FPI FINS PER INCH
		TRIPLE DUTY VALVE ANGLE	FPM FEET PER MINUTE
		TWO-WAY MOTORIZED VALVE	FT FEET
		THREE-WAY MOTORIZED VALVE	FVR FULL VOLTAGE ON-REVERSING
		PRESSURE REGULATING VALVE	GAL GALLONS
		GAS COCK	GC GENERAL CONTRACTOR
		PRESSURE GAUGE WITH VALVE	GPM GALLONS PER MINUTE

MECHANICAL GENERAL NOTES	
A. QUALITY OF WORK	4. PROVIDE LOCATIONS OF REQUIRED ACCESS PANELS FOR INSTALLATION IN WALLS AND CEILINGS TO SERVICE VALVES, DAMPERS, AND OTHER CONCEALED MECHANICAL EQUIPMENT. GENERAL CONTRACTOR IS TO FURNISH & INSTALL ACCESS PANELS, COORDINATE LOCATIONS AND SIZES OF ALL FLOOR, WALL, AND ROOF OPENINGS WITH ALL OTHER TRADES INVOLVED. ALL OPENINGS IN FIRE WALLS, FLOORS AND RATED PARTITIONS FOR PIPING, CONDUIT, ETC., ARE TO BE FIRE STOPPED WITH A UL APPROVED SYSTEM.
1. IT IS THE INTENT OF THE DRAWINGS AND SPECIFICATIONS TO OBTAIN A COMPLETE AND SATISFACTORY INSTALLATION. AN ATTEMPT HAS BEEN MADE TO SEPARATE AND DEFINE THE WORK OF THE CONTRACTOR. DRAWINGS ARE DIAGRAMMATIC, BUT MUST BE FOLLOWED AS CLOSELY AS ACTUAL CONSTRUCTION OF THE FACILITY AND WORK OF OTHER TRADES WILL PERMIT. THE DRAWINGS UTILIZE SYMBOLS AND SCHEMATIC DIAGRAMS TO INDICATE VARIOUS ITEMS OF WORK; THEREFORE, NO INTERPRETATION WILL BE MADE FROM THE LIMITATION OF SYMBOLS AND DIAGRAMS THAT ANY ELEMENTS NECESSARY FOR THE COMPLETE INSTALLATION ARE EXCLUDED. THE ENGINEER IS TO BE NOTIFIED OF ANY DISCREPANCIES, OMISSIONS, CONFLICTS, OR INTERFERENCE WHICH OCCUR BETWEEN VARIOUS DRAWINGS AND SPECIFICATIONS, IF SUCH NOTIFICATION IS NOT RECEIVED, THE INSTALLING CONTRACTOR(S) IS TO BE RESPONSIBLE FOR THEIR INTERPRETATIONS.	5. PROVIDE MEANS "FURNISH AND INSTALL" AND MUST INCLUDE ALL EQUIPMENT (THAT INCLUDE THE ACCESSORIES, SUPPORTS, FITTINGS, AND OTHER INCIDENTAL MATERIAL NEEDED FOR THE EQUIPMENT), DEVICES, HARDWARE, MOUNTS, LABOR, RIGGING, SUBCONTRACTS, ETC., THAT RESULT IN A COMPLETE AND FUNCTIONAL PROJECT INDICATED ON THE DRAWINGS, AS SPECIFIED AND AS REQUIRED BY CODE. MINOR ITEMS TO FINISH THE WORK SUCH AS PATCHING, BLOCKING, TRIM, TOUCH-UP PAINT, ETC., SHALL BE PROVIDED WHETHER OR NOT INDICATED IN THE CONTRACT DOCUMENTS.
2. "PROVIDE" MEANS "FURNISH AND INSTALL" AND MUST INCLUDE ALL EQUIPMENT (THAT INCLUDE THE ACCESSORIES, SUPPORTS, FITTINGS, AND OTHER INCIDENTAL MATERIAL NEEDED FOR THE EQUIPMENT), DEVICES, HARDWARE, MOUNTS, LABOR, RIGGING, SUBCONTRACTS, ETC., THAT RESULT IN A COMPLETE AND FUNCTIONAL PROJECT INDICATED ON THE DRAWINGS, AS SPECIFIED AND AS REQUIRED BY CODE. MINOR ITEMS TO FINISH THE WORK SUCH AS PATCHING, BLOCKING, TRIM, TOUCH-UP PAINT, ETC., SHALL BE PROVIDED WHETHER OR NOT INDICATED IN THE CONTRACT DOCUMENTS.	3. LOCATE ALL TEMPERATURE, PRESSURE, AND FLOW MEASURING DEVICES IN ACCESSIBLE LOCATIONS IN STRAIGHT SECTIONS OF PIPE OR DUCT AS RECOMMENDED BY THE MANUFACTURER. NOTIFY ENGINEER FOR FIELD REVIEW IF CONFIGURATION WILL NOT ALLOW, WHERE TWO OR MORE ITEMS OF THE SAME TYPE OF EQUIPMENT ARE REQUIRED, THE PRODUCT OF ONE MANUFACTURER IS TO BE USED.
4. SCHEDULED EQUIPMENT IS TO BE BALANCED AND A PRELIMINARY REPORT SUBMITTED TO THE ENGINEER FOR REVIEW. PROVIDE ALLOWANCE FOR (2) RETURN TRIPS FOR ADDITIONAL REBALANCE WORK AFTER ENGINEER REVIEW OF INITIAL REPORTS. PROVIDE THE FINAL REPORT TO ENGINEER.	5. TOLERANCE OF HYDROSTATIC SYSTEMS: ADJUST FLUID FLOW RATES AT BALANCE VALVES AND ALL EQUIPMENT TO PLUS/MINUS 10% OF DESIGN FLOW RATES.
B. CODES/PERMITS	6. TOLERANCE OF AIR SYSTEMS: ADJUST AIR FLOW RATES AT AIR HANDLING UNITS TO PLUS/MINUS 5% OF DESIGN FOR SUPPLY SYSTEMS AND PLUS/MINUS 10% OF DESIGN FOR RETURN AND EXHAUST SYSTEMS. ADJUST AIR FLOW RATES AT AIR INLETS AND OUTLETS TO PLUS/MINUS 10% OF DESIGN TO THE SPACE. IN ALL CASES MAINTAIN REQUIRED FLOW OR SPACE PRESSURIZATION CRITERIA.
1. WORK IS TO BE PERFORMED IN STRICT ACCORDANCE WITH STATE RECOGNIZED BUILDING CODES, NFPA, ASHRAE, UNDERWRITERS LABORATORIES AND ALL MUNICIPAL, STATE AND OTHER AUTHORITIES, PUBLIC AND PRIVATE, HAVING JURISDICTION. REPORT ALL DISCREPANCIES WITH SUCH REGULATIONS TO ENGINEER AND DO NOT PROCEED WITH ANY WORK UNTIL WRITTEN AUTHORIZATION IS RECEIVED FROM THE ENGINEER.	7. ALL WORKSHIPS, MATERIALS, AND EQUIPMENT IS TO BE GUARANTEED FOR A PERIOD OF ONE YEAR AFTER ACCEPTANCE BY THE OWNER.
2. ALL NECESSARY FEES, PERMITS, AND APPROVALS AS REQUIRED BY THE WORK OF THESE DRAWINGS AND SPECIFICATIONS IS TO BE OBTAINED AND PAID FOR BY THIS CONTRACTOR.	8. PROVIDE IDENTIFICATION LABELS FOR NEW EQUIPMENT. AFFIX PERMANENT IDENTIFYING TAGS OR LABELS TO FANS, TERMINAL UNITS, AIR-HANDLERS ETC. IDENTIFY SYSTEM ON PIPING AND DUCTWORK MAINS AND INDICATE DIRECTION OF FLOW ON PIPING. INDICATE THE CONTROLLED EQUIPMENT ON WALL MOUNTED CONTROLS.
3. NOTHING CONTAINED IN THE SPECIFICATIONS OR INDICATED ON THESE DRAWINGS IS TO BE CONSTRUED TO CONFLICT WITH APPLICABLE PORTIONS OF ANY LAWS, ORDINANCES, REGULATIONS, OR CODES.	9. SCHEDULED EQUIPMENT IS TO BE BALANCED AND A PRELIMINARY REPORT SUBMITTED TO THE ENGINEER FOR REVIEW. PROVIDE ALLOWANCE FOR (2) RETURN TRIPS FOR ADDITIONAL REBALANCE WORK AFTER ENGINEER REVIEW OF INITIAL REPORTS. PROVIDE THE FINAL REPORT TO ENGINEER.
C. COORDINATION OF WORK	10. WORK IS TO BE PERFORMED IN STRICT ACCORDANCE WITH STATE RECOGNIZED BUILDING CODES, NFPA, ASHRAE, UNDERWRITERS LABORATORIES AND ALL MUNICIPAL, STATE AND OTHER AUTHORITIES, PUBLIC AND PRIVATE, HAVING JURISDICTION. REPORT ALL DISCREPANCIES WITH SUCH REGULATIONS TO ENGINEER AND DO NOT PROCEED WITH ANY WORK UNTIL WRITTEN AUTHORIZATION IS RECEIVED FROM THE ENGINEER.
1. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.	11. ALL NECESSARY FEES, PERMITS, AND APPROVALS AS REQUIRED BY THE WORK OF THESE DRAWINGS AND SPECIFICATIONS IS TO BE OBTAINED AND PAID FOR BY THIS CONTRACTOR.
2. WHEN MECHANICAL WORK (HVAC, PLUMBING, FIRE PROTECTION, ETC.) IS SUBCONTRACTED, IT IS TO BE THE MECHANICAL CONTRACTOR'S RESPONSIBILITY TO COORDINATE SUBCONTRACTORS AND THE ASSOCIATED CONTRACTS. WHEN DISCREPANCIES ARISE PERTAINING TO WHICH CONTRACTOR PROVIDES A PARTICULAR ITEM OF THE MECHANICAL CONTRACT OR WHICH CONTRACTOR PROVIDES FINAL CONNECTIONS FOR A PARTICULAR ITEM OF THE MECHANICAL CONTRACT, IT MUST BE BROUGHT TO THE ATTENTION OF THE MECHANICAL CONTRACTOR, WHOSE DECISION IS FINAL.	12. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
3. THE LOCATIONS OF ALL ITEMS SHOWN ON THE DRAWINGS OR CALLED FOR IN THE SPECIFICATIONS ARE APPROXIMATE AND NOT DEFINITELY FIXED BY DIMENSIONS. THE EXACT LOCATIONS NECESSARY TO SECURE THE BEST CONDITIONS AND RESULTS MUST BE DETERMINED BY THE PROJECT SITE CONDITIONS. CASES WHERE THERE ARE MAJOR CONFLICTS THE CONTRACTOR MUST NOTIFY THE ENGINEER FOR FIELD REVIEW. DO NOT SCALE THE DRAWINGS.	13. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
D. PIPING	14. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
1. SEE PIPING PLAN SHEETS FOR PIPING GENERAL NOTES.	15. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
E. DUCTWORK	16. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
1. SEE DUCTWORK PLANS SHEETS FOR DUCTWORK GENERAL NOTES.	17. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
F. TESTING, ADJUSTING, AND BALANCING	18. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
1. WORK IS TO BE PERFORMED BY AN INDEPENDENT TESTING AND BALANCING AGENCY SPECIALIZING IN TESTING, ADJUSTING, AND BALANCING OF HEATING, VENTILATION, AND COOLING SYSTEMS. TESTING AND BALANCING CONTRACTOR MUST BE AABC OR NEBB CERTIFIED.	19. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
2. TOLERANCE OF HYDROSTATIC SYSTEMS: ADJUST FLUID FLOW RATES AT BALANCE VALVES AND ALL EQUIPMENT TO PLUS/MINUS 10% OF DESIGN FLOW RATES.	20. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
3. TOLERANCE OF AIR SYSTEMS: ADJUST AIR FLOW RATES AT AIR HANDLING UNITS TO PLUS/MINUS 5% OF DESIGN FOR SUPPLY SYSTEMS AND PLUS/MINUS 10% OF DESIGN FOR RETURN AND EXHAUST SYSTEMS. ADJUST AIR FLOW RATES AT AIR INLETS AND OUTLETS TO PLUS/MINUS 10% OF DESIGN TO THE SPACE. IN ALL CASES MAINTAIN REQUIRED FLOW OR SPACE PRESSURIZATION CRITERIA.	21. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
4. SCHEDULED EQUIPMENT IS TO BE BALANCED AND A PRELIMINARY REPORT SUBMITTED TO THE ENGINEER FOR REVIEW. PROVIDE ALLOWANCE FOR (2) RETURN TRIPS FOR ADDITIONAL REBALANCE WORK AFTER ENGINEER REVIEW OF INITIAL REPORTS. PROVIDE THE FINAL REPORT TO ENGINEER.	22. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
G. WARRANTY	23. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
1. GUARANTEE ALL WORK PERFORMED AND MATERIALS AND EQUIPMENT INSTALLED TO THE FULL EXTENT REQUIRED BY THE DRAWINGS AND SPECIFICATIONS TO BE FREE FROM INHERENT DEFECTS OF MATERIAL AND WORKMANSHIP FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF FINAL ACCEPTANCE.	24. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
2. REPLACE ANY MATERIALS AND EQUIPMENT PRIOR TO THE FINAL ACCEPTANCE WHICH IS CORRODED OR OTHERWISE DAMAGED THROUGH THE MECHANICAL CONTRACTOR'S FAILURE TO PROPERLY OPERATE AND MAINTAIN THE INSTALLATION DURING CONSTRUCTION OR RETESTING.	25. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
3. KEEP THE WORK IN REPAIR AND REPLACE ANY DEFECTIVE MATERIALS, EQUIPMENT, OR WORKMANSHIP UPON NOTICE FROM THE ENGINEER OR OWNER'S REPRESENTATIVE FOR A PERIOD OF ONE YEAR FROM DATE OF ACCEPTANCE.	26. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
H. INSURANCE	27. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
1. THE CONTRACTOR MUST, DURING THE LIFE OF THE CONTRACT, MAINTAIN IN FORCE, SUCH INSURANCE AS IS REQUIRED OF THE PRIME CONTRACTOR IN THE GENERAL CONDITIONS OF THE CONTRACT; AND IS TO FURNISH THE PRIME CONTRACTOR AND THE OWNER WITH CERTIFICATION OF SUCH INSURANCE BEFORE BEGINNING WORK ON THIS SECTION OF CONTRACT.	28. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
I. DOCUMENTATION	29. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.
1. PROVIDE AN ENTIRE SET OF PROJECT CLOSE-OUT DOCUMENTS TO OWNER PER CONTRACT DOCUMENTS. PACKAGE MUST CONTAIN ENTIRE O&M MANUALS WITH PROJECT SUBMITTALS AND SUBMITTAL COMMENTS, TAB REPORTS, TEST REPORTS, AND RECORD DRAWINGS, PLUS ADMINISTRATIVE DOCUMENTS.	30. COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, AND ELECTRICAL WORK - NEW OR EXISTING.

BASIS OF DESIGN - REPLACE OIL-FIRED FURNACE AND AIR CONDITIONING UNIT WITH COLD CLIMATE HEAT PUMPS	
APPLICABLE CODES AND STANDARDS:	1. REMOVE EXISTING OIL-FIRED FURNACE (140 MBH OUTPUT), BREECHING TO CHIMNEY, OIL TANK, DX COIL, AND EXTERIOR CONDENSING UNIT. INFILL OPENING INTO CHIMNEY WITH GROUT.
2021 ASHRAE 62.1 VENTILATION FOR ACCEPTABLE INDOOR AIR QUALITY	2. EXISTING SUPPLY AND RETURN BRANCH DUCTWORK TO REMAIN.
2024 ASHRAE 15 SAFETY STANDARDS FOR REFRIGERATION SYSTEMS	3. EXISTING E-Z-VENT ENERGY RECOVERY UNIT TO REMAIN. REMOVE SUPPLY AND RETURN DUCTS.
2024 ASHRAE 34 DESIGNATION AND SAFETY CLASSIFICATION OF REFRIGERANTS	4. INSTALL FOUR (4) NEW INDOOR AIR HANDLING UNITS IN PLACE OF OIL-FIRED FURNACE. AIR HANDLING UNITS TO BE TRANE MITSUBISHI SVZ-AP60NL, 60 MBH COOLING AT 95 DEG. F, 42.5 MBH HEATING AT 7.5 MCA, 75 WATTS, 208/1/60.
2015 INTERNATIONAL BUILDING CODE	5. INSTALL TOTAL OF FOUR (4) EXTERIOR HEAT UNITS IN PLACE OF THE DEMO CONDENSING UNIT. HEAT PUMP UNITS TO BE TRANE MITSUBISHI SUZ-AP60NL, R454B REFRIGERANT, 5 TON COOLING CAPACITY, 38 MCA, 67 MOPC, 426 WATTS, 208/1/60.
2015 NFPA 1 FIRE CODE	6. DESIGN BUILD CONTRACTOR SHALL BE RESPONSIBLE FOR CALCULATING HEATING AND COOLING LOADS FOR EACH CONDITIONED SPACE WITHIN THE BUILDING.
2021 INTERNATIONAL PLUMBING CODE WITH VERMONT PLUMBING RULES	7. BASED ON HEATING AND COOLING LOADS FOR INDIVIDUAL SPACES DESIGN BUILD CONTRACTOR SHALL DETERMINE HOW TO CONNECT THE FOUR AIR HANDLING UNITS INTO EXISTING BRANCH DUCTWORK TO MATCH SPACE HEATING AND COOLING DEMANDS WITH AIR HANDLING UNIT HEATING AND COOLING CAPACITIES. PROVIDE NEW SUPPLY AND RETURN DUCTS TO CONNECT TO EXISTING BRANCH DUCTS.</




MECHANICAL DUCTWORK NOTES	
1.	SEE SHEET M0.1 FOR MECHANICAL GENERAL NOTES.
2.	FABRICATE DUCTWORK FROM FIELD VERIFIED DIMENSIONS. FABRICATE DUCTWORK IN ACCORDANCE WITH SMACNA GUIDELINES (LATEST EDITION). PRIOR TO FABRICATING DUCTWORK VERIFY CEILING CLEARANCES WITH STRUCTURE, PIPES, ETC. COORDINATE THE INSTALLATION OF DUCTWORK WITH SPRINKLER PIPING. INSTALL DUCTWORK PRIOR TO INSTALLING ANY PIPING AND ELECTRICAL WORK TO REDUCE CONFLICTS.
3.	ALL DUCTWORK IS TO BE FABRICATED FROM G-90 GALVANIZED SHEET METAL IN LOCK-FORMING QUALITY, UNLESS SPECIFIED OTHERWISE.
4.	ALL DUCTWORK DIMENSIONS SHOWN ON PLANS ARE CLEAR INTERNAL SIZES.
5.	ALL SUPPLY, RETURN, EXHAUST, AND OUTSIDE AIR DUCTWORK SHALL BE FABRICATED AT A MINIMUM CLASS OF 2 INCH WATER GAGE SEAL CLASS 'A'.
6.	ALL DUCT SEALANT TO BE WATER BASED LOW VOC.
7.	ALL SUPPLY AND D/A DUCT WORK TO BE INSULATED TO MEET THE ENERGY CONSERVATION CODE ADOPTED BY THE STATE. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.
8.	COORDINATE THE LOCATION OF CEILING AIR INLETS AND OUTLETS WITH LIGHTS, SPRINKLER HEADS, AND LIFE SAFETY DEVICES.
9.	PROVIDE ADJUSTABLE VOLUME DAMPERS AT ALL BRANCH DUCT TAKE OFFS. 'RAP-IT' STYLE VOLUME DAMPERS AND HARDWARE IS NOT PERMITTED. FOR LOW FLOW BRANCHES, PROVIDE EDGE SEALED DAMPERS TO OBTAIN PROPER FLOW BALANCING.
10.	INSTALL ALL DUCTS IN BASEMENT TIGHT TO CEILING STRUCTURE AND OFFSET BELOW BEAMS AS REQUIRED.

MECHANICAL KEYNOTES	
2	SUSPEND FAN COILS FROM CEILING STRUCTURE. MOUNT TIGHT TO CEILING TO MAINTAIN MAXIMUM HEADROOM.
3	24" X 12" OUTSIDE AIR LOUVER MOUNT IN EXISTING WINDOW OPENING. CONFIRM OPENING DIMENSIONS IN FIELD.
4	MOUNT HEAT PUMPS ON EXTERIOR MASONRY WALL WITH WALL MOUNT BRACKETS PROVIDED WITH THE HEAT PUMP UNIT. PROVIDE VIBRATION ISOLATORS.
5	1/2" S AND 1/4" L INSULATED REFRIGERANT PIPELINE ROUTE BUNDLED AND INSTALLED TIGHT TO CEILING STRUCTURE.
6	PROVIDE WALL PENETRATION SEAL KIT FOR BOTH REFRIGERANT SUCTION AND LIQUID PIPING. AIREX PRO-SYSTEM KIT WITH INSULATION PROTECTION.
8	DUCT MOUNTED TEMPERATURE SENSOR PROVIDED WITH ELECTRIC DUCT HEATER.

R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS

52 State St., 2nd Floor | Montpelier, VT 05602
(802) 232-2628 | info@redwardsandcompany.com
www.redwardsandcompany.com



PROJECT
ALICE WARD
LIBRARY

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King inc.


ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
www.duboisandking.com
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

RELEASE

RELEASE DATE

RELEASE & REVISION LOG		
MARK	REVISION DESCRIPTION	DATE

PROJECT NORTH




BASEMENT
PLAN -
DUCTWORK

DRAWN JJC DATE 09.30.25
CHECKED JHP
DRAWING NUMBER

M1.1


CD SET
FOR BIDDING
09.30.25



MECHANICAL KEYNOTES	
9	MOUNT GRILLES AT 8'-0" AFF

R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS

52 State St., 2nd Floor | Montpelier, VT 05602
(802) 232-2628 | info@edwardsandcompany.com
www.edwardsandcompany.com



PROJECT
ALICE WARD
LIBRARY

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King inc.


ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
www.duboisandking.com
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

RELEASE

RELEASE DATE

RELEASE & REVISION LOG		
MARK	REVISION DESCRIPTION	DATE

PROJECT NORTH




1ST FLOOR
PLAN -
DUCTWORK

DRAWN JJC DATE 09.30.25
CHECKED JHP
DRAWING NUMBER

M1.2

CD SET
FOR BIDDING

09.30.25




2nd FLOOR - DUCTWORK
SCALE: 1/4" = 1'-0"

MECHANICAL KEYNOTES	
7	ALL EXPOSED DUCT TO BE ROUND SPIRAL WOUND WITH DUCT MOUNTED SUPPLY DIFFUSERS AND RETURN GRILLES. MOUNT NEAR INTERFACE OF WALLS AND ROOFLINE.

R. Edwards & Co.
ARCHITECTS + PRESERVATIONISTS

52 State St., 2nd Floor | Montpelier, VT 05602
(802) 232-2628 | info@edwardsandcompany.com
www.edwardsandcompany.com



PROJECT
ALICE WARD
LIBRARY

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King inc.


ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (603) 228-3376
FAX: (603) 228-7101
www.duboisandking.com
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

RELEASE

RELEASE DATE

RELEASE & REVISION LOG		
MARK	REVISION DESCRIPTION	DATE

PROJECT NORTH




**2ND FLOOR -
DUCTWORK**

DRAWN JJC DATE 09.30.25
CHECKED JHP
DRAWING NUMBER


CD SET
FOR BIDDING 09.30.25

M1.3




DUCTED FAN COIL INSTALLATION DETAIL

SCALE: NOT TO SCALE




FIRE DAMPER INSTALLATION DETAIL

SCALE: NOT TO SCALE



METALLIC PIPE WALL PENETRATION DETAILS

NOT TO SCALE



METALLIC PIPE FLOOR PENETRATION DETAILS


NOT TO SCALE

NOTES:

1. FOLLOW FIRE SEALANT MANUFACTURERS WRITTEN INSTALLATION INSTRUCTIONS IN CONJUNCTION WITH REQUIREMENTS AS DETAILED.
2. ALL WALL AND FLOOR PIPE PENETRATIONS SHALL BE INSTALLED PER THIS DETAIL.
3. DETAIL BASED ON STI "SPEC SEAL" FIRE STOPPING PRODUCTS, ALTERNATE MANUFACTURERS INSTALLATION REQUIREMENTS MAY VARY.
4. ALL WALL AND FLOOR PENETRATIONS SHALL BE INSTALLED TO MEET U.L. TESTED ASSEMBLIES. REFER TO ARCHITECTS DRAWINGS FOR U.L. DESIGNATIONS OF WALL AND FLOOR ASSEMBLIES.
5. PROVIDE CHROME PLATED ESCUTCHEONS FOR ALL EXPOSED LOCATIONS.


WALL & FLOOR PIPE PENETRATION DETAIL

SCALE: NOT TO SCALE



DUCT BRANCH CONNECTION DETAIL

SCALE: NOT TO SCALE



PROJECT
ALICE WARD
LIBRARY

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King INC.


ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
WWW.DUBOISANDCOMPANY.COM
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

RELEASE

RELEASE DATE

RELEASE & REVISION LOG
MARK REVISION DESCRIPTION DATE

PROJECT NORTH




MECHANICAL
DETAILS

DRAWN JJC DATE 09.30.25
CHECKED JHP
DRAWING NUMBER

M5.1

CD SET
FOR BIDDING 09.30.25



PROJECT
ALICE WARD
LIBRARY

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King INC.

ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
www.duboisandking.com
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

RELEASE

RELEASE DATE

RELEASE & REVISION LOG

PROJECT NORTH

DRAWING NAME

MECHANICAL SCHEDULES

DRAWN JJC DATE 09.30.25
CHECKED JHP
DRAWING NUMBER

M6.1

HEAT PUMP, SPLIT TYPE OUTDOOR UNIT SCHEDULE

TAG	MATCHED UNIT TAG	SERVES	BASIS OF DESIGN MANUFACTURER	BASIS OF DESIGN MODEL	COOLING CONDITION				HEATING CONDITION 1				HEATING CONDITION MIN				FAN AIRFLOW	ELECTRICAL				REFRIGERANT	SOUND (DBA)	WEIGHT (LBS)	REMARKS			
					COOLING CAPACITY (TONS)	EAT DB	EAT WB	EER	SEER	HEATING CAPACITY	EAT DB	EAT WB	COP	HEATING CAPACITY	EAT DB	EAT WB		2,193 CFM	208V	1	60 Hz	17.0 A						
HP-1	FC-1	READING STUDY	MITSUBISHI	SUZAA15NLHZ	1.25 ton	95 °F	75 °F	13.2	25.2	23,000 Btu/h	47 °F	43 °F	4.4	11,000 Btu/h	-13 °F	-13 °F	2,193 CFM	208V	1	60 Hz	17.0 A	R454B	37	115				
HP-2	FC-2	LIBRARY STACKS	MITSUBISHI	SUZAA15NLHZ	1.25 ton	95 °F	75 °F	13.2	25.2	23,000 Btu/h	47 °F	43 °F	4.4	11,000 Btu/h	-13 °F	-13 °F	2,193 CFM	208V	1	60 Hz	17.0 A	R454B	37	115				
HP-3	FC-3	COMMUNITY ROOM	MITSUBISHI	SUZAA12NLHZ	1 ton	95 °F	75 °F	13.6	17	18,000 Btu/h	47 °F	43 °F	3.6	9,000 Btu/h	-13 °F	-13 °F	1,590 CFM	208V	1	60 Hz	25.0 A	R454B	37	99				

NOTES:

1. 1/4" REFRIGERANT LIQUID AND 1/2" REFRIGERANT GAS CONNECTIONS

2. INCLUDE WALL MOUNTING BRACKET.

3. ALL STARTERS FOR HVAC EQUIPMENT WHICH ARE NOT FACTORY MOUNTED SHALL BE FURNISHED UNDER DIVISION 23, AND INSTALLED UNDER DIVISION 26. ALL DISCONNECTS SHALL BE FURNISHED AND INSTALLED BY DIVISION 26.

HEAT PUMP, SPLIT TYPE INDOOR UNIT SCHEDULE

TAG	BASIS OF DESIGN MANUFACTURER	BASIS OF DESIGN MODEL	COOLING PERFORMANCE				HEATING PERFORMANCE				CFM	QTY	E.S.P.	POWER (WATTS)	VOLTS	PHASE	MCA	HZ	WEIGHT (LBS)	SOUND (DBA)	REMARKS											
			CAPACITY	EAT		CAPACITY	EAT																									
				DB	WB		DB	WB																								
FC-1	MITSUBISHI	PEAD-AA15NL	15,000.0 Btu/h	80 °F	67 °F	23000.0 Btu/h	47 °F	43 °F	512 CFM	1	0.40 in-wg	121 W	208V	1	2.3 A	60 Hz	60	34														
FC-2	MITSUBISHI	PEAD-AA15NL	15,000.0 Btu/h	80 °F	67 °F	23000.0 Btu/h	47 °F	43 °F	512 CFM	1	0.40 in-wg	121 W	208V	1	2.3 A	60 Hz	60	34														
FC-3	MITSUBISHI	PEAD-AA12NL	12,000.0 Btu/h	80 °F	67 °F	18000.0 Btu/h	47 °F	43 °F	420 CFM	1	0.40 in-wg	121 W	208V	1	2.5 A	60 Hz	58	31														

NOTES:

1. 1/4" REFRIGERANT LIQUID AND 1/2" REFRIGERANT GAS CONNECTIONS

2. PROVIDE WIRED WALL MOUNT CONTROLS

3. PROVIDE ALL LINE SETS, FILTERS, DRYERS, CONDENSATE DRAINS, CONDENSATE PUMP FOR A COMPLETE PACKAGE

ELECTRIC HEATER SCHEDULE

TAG	LOCATION	BASIS OF DESIGN MANUFACTURER	BASIS OF DESIGN MODEL	TYPE	HEATING CAPACITY BTU/HR	MOTOR				REMARKS
						KW	VOLTS	PHASE	AMPS	
EH-1	ADA BATH HALL 103	BERKO	SRA2027DSF	WALL RECESSED	5,120	1.5	240V	1	6.3 A	PROVIDE WALL MOUNTED THERMOSTAT
EH-2	STAIR	BERKO	VFK304F	WALL RECESSED	10,200	3	240V	1	12.5 A	PROVIDE WALL MOUNTED THERMOSTAT
EH-3	BASEMENT	QMARK	MUH03-21	HORIZONTAL UNIT HEATER	10,200	3	240V	1	12.5 A	PROVIDE INTEGRAL THERMOSTAT AND CEILING MOUNT BRACKET
EH-4	UTILITY ROOM	BERKO	SRA2027DSF	SURFACE MOUNTED	0	0	240V	1	6.3 A	PROVIDE WALL MOUNTED THERMOSTAT

ELECTRIC DUCT HEATER SCHEDULE

TAG	LOCATION	BASIS OF DESIGN MANUFACTURER	BASIS OF DESIGN MODEL	TYPE	HEATING CAPACITY	HEIGHT (INCHES)	WIDTH (INCHES)	KW	VOLTS	PHASE	FULL LOAD CURRENT (AMPS)	MCA	REMARKS
EDH-1	BASEMENT	RENEWAIRE	EDH 6"	ELECTRIC DUCT HEATER	3,410 Btu/h	8.0	11.5	1	240V	1	4.2	20.0 A	SEE NOTES
EDH-2	UTILITY ROOM	RENEWAIRE	EDH 8"	ELECTRIC DUCT HEATER	10,200 Btu/h	10.0	11.5	3	240V	1	12.5	20.0 A	SEE NOTES

DIVISION 22 - PLUMBING
SECTION 221005
PLUMBING PIPING

PART 1 GENERAL

1.01 SECTION INCLUDES

- A Sanitary waste piping, above grade.
- B Domestic water piping, above grade.
- 1.02 REFERENCE STANDARDS**
 - A ASME B16.18 - Cast Copper Alloy Solder Joint Pressure Fittings; 2021.
 - B ASME B16.22 - Wrought Copper and Copper Alloy Solder-Joint Pressure Fittings; 2021.
 - C ASME B16.51 - Copper and Copper Alloy Press-Connect Pressure Fittings; 2021.
 - D ASME B31.9 - Building Services Piping; 2020.
 - E ASTM B32 - Standard Specification for Solder Metal; 2020.
 - F ASTM B88 - Standard Specification for Seamless Copper Water Tube; 2022.
 - G ASTM B813 - Standard Specification for Water Flushable Liquid and Paste Fluxes for Soldering of Copper and Copper Alloy Tube; 2024.
 - H ASTM D2564 - Standard Specification for Solvent Cements for Poly(Vinyl Chloride) (PVC) Plastic Piping Systems; 2020 (Reapproved 2024).
 - I ASTM D2729 - Standard Specification for Poly(Vinyl Chloride) (PVC) Sewer Pipe and Fittings; 2021.
 - J ASTM F877 - Standard Specification for Crosslinked Polyethylene (PEX) Hot- and Cold-Water Distribution Systems; 2024.
 - K ASTM F1960 - Standard Specification for Cold Expansion Fittings with PEX Reinforcing Rings for Use with Cross-Linked Polyethylene (PEX) and Polyethylene of Raised Temperature (PE-RT) Tubing; 2024.
 - L IAPMO/ANSI/CAN Z1117 - Standard for Press Connections; 2022.
 - M ICC (IPC) - International Plumbing Code; Most Recent Edition Adopted by Authority Having Jurisdiction, Including All Applicable Amendments and Supplements.
 - N MSS SP-58 - Pipe Hangers and Supports - Materials, Design, Manufacture, Selection, Application, and Installation; 2018, with Amendment (2019).
 - O MSS SP-110 - Ball Valves Threaded, Socket-Welding, Solder Joint, Grooved and Flared Ends; 2010, with Errata.
 - P NSF 372 - Drinking Water System Components - Lead Content; 2024.

1.03 DELIVERY, STORAGE, AND HANDLING

- A Provide temporary end caps and closures on piping and fittings. Maintain in place until installation.
- B Protect piping systems from entry of foreign materials by temporary covers, completing sections of the work, and isolating parts of completed system.

PART 2 PRODUCTS

2.01 GENERAL REQUIREMENTS

- A Potable Water Supply Systems: Provide piping, pipe fittings, and solder and flux (if used), that comply with NSF 61 and NSF 372 for maximum lead content; label pipe and fittings.

2.02 SANITARY WASTE PIPING, ABOVE GRADE

- A PVC Pipe: ASTM D2729.
- 1. Fittings: PVC.
- 2. Joints: Solvent welded, with ASTM D2564 solvent cement.

2.03 DOMESTIC WATER PIPING, ABOVE GRADE

- A Copper Tube: ASTM B88 (ASTM B88M), Type L (B), Drawn (H).
 - 1. Fittings: ASME B16.18, cast copper alloy or ASME B16.22, wrought copper and bronze.
 - 2. Joints: ASTM B32, alloy Sn95 solder.
- 3. Mechanical Press Sealed Fittings: ASME B16.51 or IAPMO/ANSI/CAN Z1117, ICC (IPC), and IAPMO (UPC) approved, NSF 61 and NSF 372 certified, with EPDM seals.
- B Cross-Linked Polyethylene (PEX) Pipe: ASTM F876 or ASTM F877.
 - 1. PPI TR-4 Pressure Design Basis:
 - a. 160 psig at maximum 73 degrees F.
 - b. 100 psig at maximum 180 degrees F.
 - 2. Fittings: Brass and copper.
 - 3. Fittings: Brass and engineered polymer (EP) ASTM F1960.
 - 4. Joints: Mechanical compression fittings.
 - 5. Joints: ASTM F1960 cold-expansion fittings.

2.04 PIPE HANGERS AND SUPPORTS

- A Provide hangers and supports that comply with MSS SP-58.
 - 1. If type of hanger or support for a particular situation is not indicated, select appropriate type using MSS SP-58 recommendations.
 - 2. Overhead Supports: Individual steel rod hangers attached to structure or to trapeze hangers.
 - 3. Trapeze Hangers: Welded steel channel frames attached to structure.
 - 4. Vertical Pipe Support: Steel riser clamp.

2.05 BALL VALVES

- A Construction, 4 inch and Smaller: MSS SP-110, Class 150, 400 psi CWP, bronze body, 304 stainless steel or chrome plated brass ball, regular port, teflon seats and stuffing box ring, blow-out proof stem, lever handle with balancing stops, threaded or grooved ends with union.

PART 3 EXECUTION

3.01 PREPARATION

- A Ream pipe and tube ends. Remove burrs. Bevel plain end ferrous pipe.
- B Remove scale and dirt, on inside and outside, before assembly.
- C Prepare piping connections to equipment with flanges or unions.

3.02 INSTALLATION

- A Install in accordance with manufacturer's instructions.
- B Provide non-conducting dielectric connections wherever joining dissimilar metals.
- C Route piping in orderly manner and maintain gradient. Route parallel and perpendicular to walls.
- D Install piping to maintain headroom, conserve space, and not interfere with use of space.
- E Group piping whenever practical at common elevations.
- F Provide clearance in hangers and from structure and other equipment for installation of insulation and access to valves and fittings.
- G Provide access where valves and fittings are not exposed.
- H Copper Pipe and Tube: Make soldered joints in accordance with ASTM B828, using specified solder, and flux meeting ASTM B813; in potable water systems use flux also complying with NSF 61 and NSF 372.
- I PVC Pipe: Make solvent-welded joints in accordance with ASTM D2855.
- J Pipe Hangers and Supports:
 - 1. Install in accordance with ASME B31.9.
 - 2. Install hangers to provide minimum 1/2 inch space between finished covering and adjacent work.
 - 3. Place hangers within 12 inches of each horizontal elbow.
 - 4. Provide copper plated hangers and supports for copper piping.

3.03 APPLICATION

- A Install ball valves for shut-off and to isolate equipment, part of systems, or vertical risers.

3.04 FIELD TESTS AND INSPECTIONS

- A Verify and inspect systems according to requirements by the Authority Having Jurisdiction. In the absence of specific test and inspection procedures proceed as indicated below.

END OF SECTION 221005

SECTION 223000
PLUMBING EQUIPMENT

PART 1 GENERAL

1.01 SECTION INCLUDES

- A Residential hybrid electric water heaters

1.02 REFERENCE STANDARDS

- A ASHRAE Std 90.1 I-P - Energy Standard for Buildings Except Low-Rise Residential Buildings; Most Recent Edition Adopted by Authority Having Jurisdiction, Including All Applicable Amendments and Supplements.
- B AWWA C652 - Disinfection of Water-Storage Facilities; 2019.
- C ICC (IPC) - International Plumbing Code; Most Recent Edition Adopted by Authority Having Jurisdiction, Including All Applicable Amendments and Supplements.

1.03 DELIVERY, STORAGE, AND HANDLING

- A Provide temporary inlet and outlet caps. Maintain caps in place until installation.

PART 2 PRODUCTS

2.01 WATER HEATERS

A Manufacturers:

- 1. A.O. Smith Water Products Co: www.hotwater.com/sle.
- 2. Bradford White Corporation: www.bradfordwhite.com/sle.
- 3. Rheem Manufacturing Company: www.rheem.com/sle.

B Residential Hybrid Electric Water Heaters:

- 1. Type: Vertical storage.
- 2. Minimum Efficiency: ASHRAE Std 90.1 I-P.
- 3. Maximum Working Pressure: 150 psig.
- 4. Heat Pump Air Temperature Operation Range: 35 to 120 deg. F.
- 5. Tank: Glass lined welded steel, thermally insulated with foam plastic; encased in corrosion-resistant steel jacket; baked-on enamel finish.
- 6. Heat Pump System: Integral to unit with compressor, heat exchangers, fan, refrigerant piping, R-134a refrigerant.
- 7. Display: LCD with integral diagnostic and troubleshooting information.
- 8. Controls: Automatic water thermostat with externally adjustable temperature range, flanged or screw-in chrome elements, enclosed controls and electrical junction box. Wire double element units so elements do not operate simultaneously. Ability to operate in heat pump, hybrid, or electric-only modes.
- 9. Water Connections: 3/4" NPT brass.
- 10. Dip Tube: Brass.
- 11. Drain Valve.
- 12. Condensate Drain.
- 13. Anode: Magnesium.
- 14. Temperature and Pressure Relief Valve: ASME labeled.

PART 3 EXECUTION

3.01 INSTALLATION

- A Install plumbing equipment in accordance with manufacturer's instructions, as required by code, and complying with conditions required for applicable certifications.
- B Coordinate system, equipment, and piping work with applicable electrical, vent, drain, and waste support interconnections as included or provided by other trades.

3.02 CLEANING

- A Clean interior of water tanks and disinfect in accordance with AWWA C652.

END OF SECTION 223000

SECTION 224000
PLUMBING FIXTURES

PART 1 GENERAL

1.01 SECTION INCLUDES

- A Tank type water closets.
- B Lavatories.
- C Sinks.
- D Under-lavatory pipe supply covers.
- E Mop sinks.

1.02 REFERENCE STANDARDS

- A ADA Standards - 2010 ADA Standards for Accessible Design; 2010.
- B ASME A112.6.1M - Floor-Affixed Supports for Off-the-Floor Plumbing Fixtures for Public Use; 1997 (Reaffirmed 2017).
- C ASME A112.18.1 - Plumbing Supply Fittings; 2024.
- D ASME A112.18.9 - Protectors/Insulators for Exposed Waste and Supplies on Accessible Fixtures; 2011 (Reaffirmed 2022).
- E ASME A112.19.2 - Ceramic Plumbing Fixtures; 2024.
- F ASME A112.19.3 - Stainless Steel Plumbing Fixtures; 2022.
- G NSF 61 - Drinking Water System Components - Health Effects; 2024.
- H NSF 372 - Drinking Water System Components - Lead Content; 2024.

1.03 DELIVERY, STORAGE, AND HANDLING

- A Accept fixtures on-site in factory packaging. Inspect for damage.

PART 2 PRODUCTS

2.01 GENERAL REQUIREMENTS

- A Potable Water Systems: Provide drinking water system components certified as complying with NSF 61 and NSF 372.
- B ADA: Where indicated to be ADA-compliant, provide fixtures complying with ADA Standards and ICC A117.1.

2.02 TANK TYPE WATER CLOSETS

A Floor-Mounted Bowl:

- 1. ASME A112.19.2; siphon jet, vitreous china, 16.5 inches high, close-coupled closet combination with elongated rim, insulated vitreous china closet tank with fittings and lever flushing valve, bolt caps, vandalproof cover locking device.
- 2. Water Consumption: 1.28 gal per flush, maximum.

B Toilet Seats:

- 1. Plastic: Solid, white, elongated, closed front, slow-closing hinged seat cover, and brass bolts with covers.

2.03 LAVATORIES

A Wall-Hung Basin:

- 1. Vitreous China: ASME A112.19.2; white, rectangular basin with splash lip, front overflow, soap depression, and hanger. Size as indicated on drawings with 4-inch centerset spacing.
- 2. Carrier:
 - a. ASME A112.6.1M; cast iron and steel frame with tubular legs, lugs for floor and wall attachment, threaded studs for fixture hanger, bearing plate and studs.

B Supply Faucet:

- 1. ASME A112.18.1; chrome plated combination supply fitting with pop-up waste, water economy aerator with maximum flow of 2.2 gpm, indexed handles.
- 2. Single-Lever Handle, Supply Faucet: ASME A112.18.1; deck-mount, ceramic cartridge disc valve, and maximum flow of 0.5 gpm, low-flow.

2.04 SINKS

A Single Compartment Bowl

- 1. ASME A112.19.3; 19 by 18 by 5 1/2 inch outside dimensions, 18 gauge, 0.050 inch thick, type 304 stainless steel, self-rimming and undercoated, with ledge back drilled for trim.
- 2. Drain: 3-1/2 inch crumb cup and tailpiece.

B Kitchen Faucets:

- 1. Single Handle Faucet with Side Spray:

- a. Type: Deck-mount spout faucet with mounting plate.
- b. Spray Type: Full stream spray at 1.5 gpm, maximum.
- c. ASME A112.18.1, ADA Standards, and NSF 61 compliant assembly.
- d. Materials: Ceramic disc-cartridge valve on brass body with polished chrome finish.

- C Accessories: Provide braided water supply lines, slip-joint p-trap, and stainless steel basket strainer.

2.05 UNDER-LAVATORY PIPE SUPPLY COVERS

A General:

- 1. Insulate exposed drainage piping including hot, cold and tempered water supplies under lavatories or sinks per ADA Standards.
- 2. Construction: 1/8 inch PVC with antimicrobial, antifungal and UV resistant properties.
 - a. Comply with ASME A112.18.9 for covers on accessible lavatory piping.
 - b. Comply with ICC A117.1.

2.06 MOP SINKS

- A Material: Molded stone one piece homogenous product.

B Type: Rectilinear, standard height.

C Tiling Flange Construction: Galvanized steel.

D Grid strainer: Stainless steel; integral; removable.

E Dimensions: As indicated on drawings.

F Accessories:

- 1. 5 feet of 1/2 inch diameter plain end reinforced plastic hose.
- 2. Hose clamp hanger.
- 3. Mop hanger.

PART 3 EXECUTION

3.01 EXAMINATION


- A Verify walls, floors, and finishes are prepared and ready for installation of fixtures.

- B Verify rough-ins for field connections match sizes and locations shown on drawings.

3.02 INSTALLATION



PROJECT NORTH



SPECIFICATIONS


M6.3

DRAWN	JJC	DATE	09.30.25
CHECKED	JHP		

DRAWING NUMBER

CD SET FOR BIDDING

09.30.25



PROJECT
ALICE WARD
LIBRARY

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King
INC.


ENGINEERING • PLANNING •
MANAGEMENT • DEVELOPMENT
BEDFORD, NH
TEL: (802) 728-3376
FAX: (802) 783-7101
www.duboisandking.com
OFFICES IN VERMONT,
NEW HAMPSHIRE & MAINE

RELEASE

RELEASE DATE

RELEASE & REVISION LOG
MARK REVISION DESCRIPTION DATE

PROJECT NORTH



SPECIFICATIONS

DRAWN

CD SET FOR BIDDING

09.30.25

CHECKED

JHP

DRAWING NUMBER

CD SET FOR BIDDING

09.30.25

◀	COMBINATION TELEPHONE/DATA OUTLET (RJ45), PROVIDE BACK BOX, COVER PLATE, PATHWAY AND (2) CAT6 DROPS – SEE NOTE #1 BELOW.	4. IN	3. PHONE 4. IN
▶	TELEPHONE OUTLET (RJ45), PROVIDE BACK BOX, COVER PLATE, PATHWAY AND (1) CAT6 DROP – SEE NOTE #1 BELOW.	5. IN	5. IN
△W	WIRELESS ACCESS POINT, DEVICE AND TERMINATION BY OTHERS. PROVIDE BACK BOX AND (2) CAT6 DROPS WITH 10-FT SERVICE LOOP.	6. A	6. A
■WAP	NOTES	7. P	7. P
	1. PROVIDE A FOUR INCH SQUARE BACK BOX AT EACH LOCATION OF A TELEPHONE/DATA/CATV/AV OUTLET. RUN A ONE INCH CONDUIT AND PULL STRING FROM EACH BACK BOX TO ABOVE THE NEAREST ACCESSIBLE CEILING. RUN 1-1/4" CONDUIT AND PULL STRING FOR AV OUTLET TO ABOVE ACCESSIBLE CEILING.	8. H	8. H
	2. PROVIDE INSULATED BUSHINGS ON THE ENDS OF ALL CONDUITS.	9. P	9. P
	3. PROVIDE A SINGLE GANG BACK BOX WITH A 3/4" CONDUIT AND PULL STRING FROM THE BACK BOX TO ABOVE THE NEAREST ACCESSIBLE CEILING. COORDINATE REQUIREMENTS/LOCATIONS WITH SECURITY AND DOOR HARDWARE CONTRACTOR.	10. W	10. W
	4. PROVIDE A SINGLE GANG BACK BOX WITH A 3/4" CONDUIT AND PULL STRING FROM THE BACK BOX TO ABOVE THE NEAREST ACCESSIBLE CEILING. PROVIDE CABLE AS REQUIRED FROM DEVICE TO HEAD-END (NEAREST DATA CLOSET). COORDINATE REQUIREMENTS/LOCATIONS WITH OWNER'S I.T. PERSONNEL AND AUDIO/VISUAL CONTRACTOR.	11. P	11. P
	NOTES	12. C	12. C
	13. THE LIGHTING CONTROL SEQUENCE, PROGRAMMING AND OPERATION NOTES: □	13. S	13. S
	1. OFFICES, BREAK ROOM: DUAL TECHNOLOGY, CEILING MOUNTED, LOW VOLTAGE OCCUPANCY SENSOR(S), LOW VOLTAGE, DIMMING RELAY POWER PACKS AND LOW VOLTAGE ON/OFF/RAISE LOWER DIMMING SWITCHES – PROGRAM SWITCHES FOR SEPARATE MANUAL ON/OFF/RAISE/LOWER CONTROL OF THE DESIGNATED FIXTURES. PROGRAM ALL LIGHT FIXTURES IN THIS ROOM FOR AUTOMATIC OFF VIA THE CEILING MOUNTED OCCUPANCY SENSOR(S) AFTER FIFTEEN MINUTES OF VACANCY. CONTROL OF THE LIGHT FIXTURES LOCATED IN THIS ROOM IS CONSIDERED TO COMPLY WITH THE 2018 IECC C405.2.1.1. DAYLIGHT RESPONSIVE CONTROLS ARE PROVIDED AS REQUIRED PER 2018 IECC C405.2.3 IN AREAS WITH DAYLIGHT ZONES. CONTROLS WILL BE STAND-ALONE AND NOT PART OF A NETWORK LIGHTING CONTROL SYSTEM.	14. P	14. P
	2. RESTROOMS, MECHANICAL/UTILITY SPACES, CUSTODIAL, STORAGE: LINE VOLTAGE, OCCUPANCY SENSOR SWITCH FOR ON/OFF CONTROL OF THE LIGHT FIXTURE AT THIS LOCATION – PROGRAM THIS SWITCH FOR AUTOMATIC OFF AFTER FIFTEEN MINUTES OF VACANCY. CONTROL OF THIS LIGHT FIXTURE IS CONSIDERED TO COMPLY WITH THE 2018 IECC C405.2.1.1.	15. T	15. T
	3. EXTERIOR SITE LIGHTING: LIGHTS SHALL BE CONTROLLED VIA LIGHTING CONTACTORS AND A PROGRAMMABLE TIME CLOCK WITH EXTERIOR LIGHT SENSOR. THE EXTERIOR LIGHT SENSOR SHALL TURN THE LIGHT FIXTURES ON AT DUSK AND OFF AT DAWN. CONTROL OF THIS LIGHT FIXTURE IS CONSIDERED TO COMPLY WITH 2018 IECC C405.2.6. IT SHOULD BE NOTED THAT IF THE OWNER DOES NOT WANT THESE FIXTURES TO OPERATE FROM DUSK TO DAWN, THEN THEY CAN BE PROGRAMMED VIA THE TIME CLOCK TO THE 'ON' AND 'OFF' TIMES DIRECTED BY THE OWNER. FIELD COORDINATE WITH THE OWNER PRIOR TO PROGRAMMING THE LIGHTING CONTROLS.	16. IT	16. IT
	4. CORRIDORS, LOBBIES, VESTIBULES: PROGRAM ALL LIGHT FIXTURES IN THIS AREA TO REDUCE BY NOT LESS THAN 50 PERCENT VIA THE CEILING MOUNTED OCCUPANCY SENSOR(S) AFTER TWENTY MINUTES OF VACANCY DURING BUSINESS HOURS. THE OCCUPANCY SENSORS IN THIS AREA SHALL BE PROGRAMMED FOR AUTOMATIC ON/AUTOMATIC OFF AFTER FIFTEEN MINUTES (MINIMUM TIME PER NFPA 101 7.8.1.2.2) OF VACANCY DURING NON-BUSINESS HOURS. CONTROLS WILL BE STAND-ALONE AND NOT PART OF A NETWORK LIGHTING CONTROL SYSTEM. (CAFFETERIA ONLY) PROVIDE LOW VOLTAGE, DIMMING RELAY POWER PACKS AND LOW VOLTAGE ON/OFF/RAISE LOWER DIMMING SWITCHES FOR LOCAL OVERRIDE CONTROL. ALL OTHER AREAS SHALL HAVE LOCAL OVERRIDE FOR ON/OFF CONTROL.	17. P	17. P
	NOTES	18. S	18. S
	19. C	19. C	19. C
	20. D	20. D	20. D
	21. T	21. T	21. T
	22. U	22. U	22. U
	23. A	23. A	23. A
	24. L	24. L	24. L
	25. O	25. O	25. O
	26. A	26. A	26. A
	27. E	27. E	27. E

SYMBOL		DESCRIPTION	
USB GROUND, 'USB' DENOTES (1) TYPE A PORT AND (1) TYPE B PORT, '4' DENOTES CIRCUIT NUMBER		UNO	
⊕ GF	20A, 125V, 2 POLE, 3 WIRE GFCI, GROUNDING DUPLEX RECEPTACLE, NEMA 5-20R	WALL	18" AFF UNO
⊖ GF WP	20A, 125V, 2 POLE, 3 WIRE, WEATHER RESISTANT, GFCI TYPE GROUNDING DUPLEX RECEPTACLE, NEMA 5-20R WITH WEATHERPROOF WHILE-IN-USE COVER PLATE	WALL	18" AFF UNO
⏚	QUADRPLEX RECEPTACLE 20A, 125V, 3 WIRE GROUNDING TYPE, NEMA 5-20R	WALL	18" AFF UNO
⏚ ⊖	SPECIAL POWER OUTLET - NEMA CONFIGURATION AS NOTED ON THE DRAWINGS	WALL	18" AFF UNO
⊖	20 AMP, 125V, 2 POLE, 3 WIRE GROUNDING SIMPLEX RECEPTACLE, NEMA 5-20R	WALL	18" AFF UNO
—	PLUGMOLD/SURFACE RACEWAY	WALL	
□ ⊖	JUNCTION BOX - 'EHD' INDICATES ELECTRIC HAND DRYER	VARIABLES	-----
⊖ a	SINGLE POLE SWITCH - 'a' DENOTES FIXTURE SWITCH CONTROL	WALL	44" AFF
⊖ D	DIMMER SWITCH	WALL	44" AFF
⊖ 3	THREE POLE SWITCH	WALL	44" AFF
⊖ 4	FOUR POLE SWITCH	WALL	44" AFF
⊖ OCD	SINGLE POLE, LINE VOLTAGE, OCCUPANCY SENSOR SWITCH - SENSOR SWITCH #WSX-PDT-EZ-SA-COLOR	WALL	44" AFF
⊖ OCD	SINGLE POLE, LINE VOLTAGE OCCUPANCY SENSOR DIMMER SWITCH - SENSOR SWITCH #WSX-PDT-EZ-D-SA-COLOR	WALL	44" AFF
⊖ M	MOTOR RATED SWITCH WITH THERMAL MOTOR OVERLOAD PROTECTION - PROVIDE THERMAL UNIT SIZED FOR MOTOR LOAD ACTUALLY SERVED, VERIFY WITH EQUIPMENT MANUFACTURER	VARIABLES	-----
□ ⊖ 30/NF	NON-FUSED DISCONNECT SWITCH - SIZED TO MATCH OVER CURRENT PROTECTION DEVICE - '3R' INDICATES PROVIDE NEMA 3R DISCONNECT SWITCH	WALL	
□ 30/30	FUSED DISCONNECT SWITCH - SUBSCRIPT INDICATES AMPS/FUSE SIZE - FUSES SHALL BE TIME DELAY TYPE - '3R' INDICATES PROVIDE NEMA 3R DISCONNECT SWITCH	WALL	
⊖	MOTOR - SUBSCRIPT INDICATES HORSEPOWER	VARIABLES	-----
—	120/208 VOLT PANELBOARD	WALL	
⊖	EQUIPMENT CONNECTION	VARIABLES	-----
—/—	HOMERUN TO PANELBOARD AND CIRCUIT BREAKER NUMBER(S) INDICATED ON THE DRAWINGS	WALL	-----
—/—	DIRECT CURRENT DC WIRING - 2 CONDUCTOR #12 AWG COPPER MINIMUM, UNLESS OTHERWISE NOTED OR REQUIRED	WALL	-----
SPD	SURGE PROTECTION DEVICE	WALL	
MOD	MOTOR OPERATED DAMPER	VARIABLES	
CGB	CENTRAL GROUND BUSBAR	WALL	54" AFF
TV	TELEVISION	WALL	60" AFF
VFD	VARIABLE FREQUENCY DRIVE, INSTALLED BY OTHERS, WIRED BY E.C.	VARIABLES	
⊖	UTILITY METER		
PC	PHOTOELECTRIC CELL	WALL	
TC	TIME CLOCK	WALL	
EPO	EMERGENCY POWER OFF PUSH BUTTON		
BUILDING AUTOMATION SYSTEM CONTROL PANEL - FURNISHED AND INSTALLED BY MECHANICAL CONTRACTOR AND LINE VOLTAGE POWER WIRED BY THE ELECTRICAL CONTRACTOR		WALL	

4	EM NL	1'x4' LIGHT FIXTURE - 'EM' INDICATES EMERGENCY LIGHT FIXTURE, 'NL' INDICATES NIGHT LIGHT, '4' DENOTES CIRCUIT NUMBER	CEILING
	—	WALL MOUNTED LIGHT FIXTURE	WALL
	●—□	ONE POLE MOUNTED LIGHT FIXTURE	CONCRETE BASE
	△	EMERGENCY BATTERY UNIT 'EBU' WITH TWO, LED EMERGENCY LIGHTING HEADS	WALL
	◎◎	DUAL TECHNOLOGY OCCUPANCY SENSOR	CEILING
	◎→	ULTRASONIC OCCUPANCY SENSOR, LONG RANGE FOR CORRIDORS	CEILING
	ICP	LIGHTING CONTROL PANEL WITH UL924 RELAYS FOR OVERRIDE ON	WALL
	↑↓	SINGLE FACED, LED EXIT SIGN - ARROW(S) INDICATE DIRECTION - 'P' INDICATES PENDANT MOUNT WITH BOTTOM AT 8'-0" AFF	CEILING/ WALL
	↑↑	DOUBLE FACED, LED EXIT SIGN - ARROW(S) INDICATE DIRECTION - 'P'	CEILING/ WALL

ON/OFF/RAISE/LOWER BUTTONS ARE TO CONTROL THE 'b' DESIGNATED FIXTURES – TYPICAL	
LCP	LIGHTING NETWORK CONTROLLER – NLIGHT ECLYPSE
SLP	SITE LIGHTING CONTROL RELAY PANEL WITH PROGRAMMABLE, DIGITAL TIME CLOCK AND A TOTAL OF EIGHT SINGLE, 120/277 VOLT RATED RELAYS IN A SURFACE MOUNTED, NEMA ONE ENCLOSURE WITH SCREW ON COVER – NLIGHT #ARP-INTENCO8-NLT-MVOLT-1VB- SC-DTC


ELECTRICAL SYMBOL NOTES	
1.	ALL SYMBOLS ARE NOT NECESSARILY USED.
2.	ALL MOUNTING HEIGHTS SHOWN IN SYMBOL LEGEND SHALL BE AS PER ADA REQUIREMENTS UNLESS OTHERWISE NOTED ON THE DRAWINGS.
3.	REFERENCE ARCHITECTURAL DOCUMENTS FOR DIMENSIONED LOCATION AND

LCF	<p>SITE LIGHTING CONTROL RELAY PANEL WITH PROGRAMMABLE, DIGITAL TIME CLOCK AND A TOTAL OF EIGHT SINGLE, 120/277 VOLT RATED RELAYS IN A SURFACE MOUNTED, NEMA ONE ENCLOSURE WITH SCREW ON COVER – NLIGHT #ARP-INTENCO8-NLT-MVOLT-1VB-SC-DTC</p> <p>SLP</p> <p>SEE THE LIGHTING CONTROL NOTES ON THIS DRAWING.</p>	WALL
-----	--	------

BY ANALYSIS, TESTING OR
COMPLIANCE WITH SUBMITTALS.

ELECTRICAL SYMBOL NOTES

1. ALL SYMBOLS ARE NOT NECESSARILY USED.
2. ALL MOUNTING HEIGHTS SHOWN IN SYMBOL LEGEND SHALL BE AS PER ADA REQUIREMENTS UNLESS OTHERWISE NOTED ON THE DRAWINGS.
3. REFERENCE ARCHITECTURAL DOCUMENTS FOR DIMENSIONED LOCATION AND MOUNTING HEIGHT OF LIGHT FIXTURES AND MISCELLANEOUS ELECTRICAL DEVICES.




BASEMENT FLOOR PLAN - LIGHTING

SCALE: 1/4" = 1'-0"

HORIZONTAL SCALE IN FEET
4 2 0 4 8 12 16

ELECTRICAL GENERAL NOTES:

1. COORDINATE ALL LIGHTING FIXTURE LOCATIONS WITH ARCHITECTURAL REFLECTED CEILINGS PLANS AND ELEVATIONS. CONFIRM SWITCHING SCHEME AND SWITCH LOCATIONS WITH ARCHITECT/OWNER PRIOR TO INSTALL.
2. PROVIDE UNSWITCHED WIRING TO EXIT SIGNS. COORDINATE EXIT SIGN LOCATIONS WITH ARCHITECTURAL EMERGENCY EGRESS PLANS.
3. ALL LIGHT FIXTURE LOCATIONS SHALL BE COORDINATED WITH HVAC DUCTWORK AND OTHER EQUIPMENT IN FIELD TO AVOID INTERFERENCE PRIOR TO INSTALL.
4. ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL ELECTRICAL ITEMS SHOWN ON THIS DRAWING.
5. TYPE "MC" CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER AND LIGHTING CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
6. ALL MOUNTING HEIGHTS FOR LIGHTING FIXTURES ARE TO THE BOTTOM OF THE FIXTURES UNLESS INDICATED OTHERWISE.
7. SEE ARCHITECTURAL EXTERIOR ELEVATIONS FOR MOUNTING HEIGHTS OF EXTERIOR LIGHTING FIXTURES AND REFLECTED CEILING PLAN FOR INTERIOR LIGHTS.
8. PROVIDE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUITING AND SWITCHING SHOWN.
9. USE #10 AWG CONDUCTORS FOR 20 AMPERE, 120 VOLT BRANCH CIRCUITS LONGER THAN 75 FEET, #8 AWG FOR 20 AMP, 120 VOLT BRANCH CIRCUITS LONGER THAN 150 FEET AND #10 AWG FOR 20 AMPERE, 277 VOLT CIRCUITS LONGER THAN 150 FEET, UNLESS SPECIFICALLY NOTED OTHERWISE. THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
10. OCCUPANCY SENSORS SHALL BE LOCATED A MINIMUM OF SIX FEET FROM MECHANICAL EQUIPMENT AIR FLOW VENTS.
11. THE ELECTRICAL CONTRACTOR SHALL AIM ALL EMERGENCY LIGHTING HEADS IN THE FIELD TO ENSURE PROPER ILLUMINATION OF EGRESS PATHS.



PROJECT
Alice Ward Library

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King Inc.

Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 530597

RELEASE

RELEASE DATE

RELEASE + REVISION LOG
MARK DESCRIPTION DATE

PROJECT NORTH



DRAWING NAME

BASEMENT FLOOR PLAN - LIGHTING

DRAWN JKW DATE 09.30.2025
CHECKED SMP SCALE AS NOTED
DRAWING NUMBER


CD SET
FOR BIDDING

09.30.2025

E1.1

ELECTRICAL GENERAL NOTES:

1. COORDINATE ALL LIGHTING FIXTURE LOCATIONS WITH ARCHITECTURAL REFLECTED CEILINGS PLANS AND ELEVATIONS. CONFIRM SWITCHING SCHEME AND SWITCH LOCATIONS WITH ARCHITECT/OWNER PRIOR TO INSTALL.
2. PROVIDE UNSWITCHED WIRING TO EXIT SIGNS. COORDINATE EXIT SIGN LOCATIONS WITH ARCHITECTURAL EMERGENCY EGRESS PLANS.
3. ALL LIGHT FIXTURE LOCATIONS SHALL BE COORDINATED WITH HVAC DUCTWORK AND OTHER EQUIPMENT IN FIELD TO AVOID INTERFERENCE PRIOR TO INSTALL.
4. ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL ELECTRICAL ITEMS SHOWN ON THIS DRAWING.
5. TYPE 'MC' CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER AND LIGHTING CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
6. ALL MOUNTING HEIGHTS FOR LIGHTING FIXTURES ARE TO THE BOTTOM OF THE FIXTURES UNLESS INDICATED OTHERWISE.
7. SEE ARCHITECTURAL EXTERIOR ELEVATIONS FOR MOUNTING HEIGHTS OF EXTERIOR LIGHTING FIXTURES AND REFLECTED CEILING PLAN FOR INTERIOR LIGHTS.
8. PROVIDE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUITING AND SWITCHING SHOWN.
9. USE #10 AWG CONDUCTORS FOR 20 AMPERE, 120 VOLT BRANCH CIRCUITS LONGER THAN 75 FEET, #8 AWG FOR 20 AMP, 120 VOLT BRANCH CIRCUITS LONGER THAN 150 FEET AND #10 AWG FOR 20 AMPERE, 277 VOLT CIRCUITS LONGER THAN 150 FEET, UNLESS SPECIFICALLY NOTED OTHERWISE, THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
10. OCCUPANCY SENSORS SHALL BE LOCATED A MINIMUM OF SIX FEET FROM MECHANICAL EQUIPMENT AIR FLOW VENTS.
11. THE ELECTRICAL CONTRACTOR SHALL AIM ALL EMERGENCY LIGHTING HEADS IN THE FIELD TO ENSURE PROPER ILLUMINATION OF EGRESS PATHS.



FIRST FLOOR PLAN - LIGHTING

SCALE: 1/4" = 1'-0"

HORIZONTAL SCALE IN FEET
4 2 0 4 8 12 16

E1.2

DRAWN JKW DATE 09.30.2025
CHECKED SMP SCALE AS NOTED
DRAWING NUMBER

CD SET
FOR BIDDING

09.30.2025

PROJECT Alice Ward Library

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King Inc.

Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 530597

RELEASE

RELEASE DATE


RELEASE + REVISION LOG
MARK DESCRIPTION DATE

N
DRAWING NAME

FIRST FLOOR PLAN -
LIGHTING

ELECTRICAL GENERAL NOTES:

- COORDINATE ALL LIGHTING FIXTURE LOCATIONS WITH ARCHITECTURAL REFLECTED CEILINGS PLANS AND ELEVATIONS. CONFIRM SWITCHING SCHEME AND SWITCH LOCATIONS WITH ARCHITECT/OWNER PRIOR TO INSTALL.
- PROVIDE UNSWITCHED WIRING TO EXIT SIGNS. COORDINATE EXIT SIGN LOCATIONS WITH ARCHITECTURAL EMERGENCY EGRESS PLANS.
- ALL LIGHT FIXTURE LOCATIONS SHALL BE COORDINATED WITH HVAC DUCTWORK AND OTHER EQUIPMENT IN FIELD TO AVOID INTERFERENCE PRIOR TO INSTALL.
- ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL ELECTRICAL ITEMS SHOWN ON THIS DRAWING.
- TYPE 'MC' CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER AND LIGHTING CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
- ALL MOUNTING HEIGHTS FOR LIGHTING FIXTURES ARE TO THE BOTTOM OF THE FIXTURES UNLESS INDICATED OTHERWISE.
- SEE ARCHITECTURAL EXTERIOR ELEVATIONS FOR MOUNTING HEIGHTS OF EXTERIOR LIGHTING FIXTURES AND REFLECTED CEILING PLAN FOR INTERIOR LIGHTS.
- PROVIDE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUITING AND SWITCHING SHOWN.
- USE #10 AWG CONDUCTORS FOR 20 AMPERE, 120 VOLT BRANCH CIRCUITS LONGER THAN 75 FEET, #8 AWG FOR 20 AMP, 120 VOLT BRANCH CIRCUITS LONGER THAN 150 FEET AND #10 AWG FOR 20 AMPERE, 277 VOLT CIRCUITS LONGER THAN 150 FEET, UNLESS SPECIFICALLY NOTED OTHERWISE, THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
- OCCUPANCY SENSORS SHALL BE LOCATED A MINIMUM OF SIX FEET FROM MECHANICAL EQUIPMENT AIR FLOW VENTS.
- THE ELECTRICAL CONTRACTOR SHALL AIM ALL EMERGENCY LIGHTING HEADS IN THE FIELD TO ENSURE PROPER ILLUMINATION OF EGRESS PATHS.



SECOND FLOOR PLAN - LIGHTING

SCALE: 1/4" = 1'-0"

HORIZONTAL SCALE IN FEET

4 2 0 4 8 12 16

PROJECT
Alice Ward Library

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King Inc.

Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 530597

RELEASE

RELEASE DATE

RELEASE + REVISION LOG

MARK	DESCRIPTION	DATE

PROJECT NORTH



DRAWING NAME

SECOND FLOOR PLAN -
LIGHTING

DRAWN JKW DATE 09.30.2025


CHECKED SMP SCALE AS NOTED

DRAWING NUMBER

CD SET
FOR BIDDING

09.30.2025

E1.3



CT e Ward Library

ark St.
an, VT 05903

JECT NUMBER
0597

LTANTS

DuBois & King^{inc.}

Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 530597

SE

USE DATE

CT NORT

1

LAST NAME

BASEMENT FLOOR PLAN - POWER

JKW	DATE	09.30.2025
SMP	SCALE	AS NOTED
NUMBER		

E1.4

ELECTRICAL GENERAL NOTES:

- THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL MECHANICAL AND ELECTRICAL ITEMS SHOWN ON THIS DRAWING, UNLESS OTHERWISE NOTED.
- TYPE 'MC' CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER AND LIGHTING CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
- VERIFY EQUIPMENT LOCATIONS, CIRCUIT BREAKER, FUSE SIZES, CONDUIT SIZES, WIRE SIZES AND ROUGH-IN REQUIREMENTS FOR ALL EQUIPMENT BEING FURNISHED BY ANOTHER TRADE OR BY THE OWNER PRIOR TO ROUGHING-IN.
- PROVIDE THE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUITING SHOWN ON THE DRAWINGS.
- CIRCUIT NUMBERS AT EQUIPMENT AND AT HOMERUNS CORRESPOND TO PANELBOARD CIRCUIT BREAKERS (SEE PANELBOARD SCHEDULES). BRANCH CIRCUITS SHALL BE SIZED ACCORDING TO THE CIRCUIT BREAKER RATING, UNLESS OTHERWISE NOTED ON THE ELECTRICAL EQUIPMENT SCHEDULES. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ALL LOADS CONNECTED TO EACH PANELBOARD ARE BALANCED EVENLY.
- USE #10 AWG CONDUCTORS FOR 20 AMPERE, 120 VOLT BRANCH CIRCUITS LONGER THAN 75 FEET, #8 AWG FOR 20 AMP, AND 120 VOLT BRANCH CIRCUITS LONGER THAN 150 FEET, AND #10 AWG FOR 20 AMPERE, 277 VOLT CIRCUITS LONGER THAN 150 FEET, UNLESS SPECIFICALLY NOTED OTHERWISE. THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
- UNLESS SPECIFICALLY NOTED OTHERWISE. THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
- RECEPTACLES INSTALLED ON THE EXTERIOR OF THE BUILDING SHALL BE LISTED AS WEATHER RESISTANT AND SHALL BE PROVIDED WITH 'EXTRA-DUTY' LISTED, WEATHERPROOF WHILE-IN-USE COVERPLATES.
- TYPE 'MC' CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
- ALL PANELBOARDS, DISCONNECTS AND DEVICES SHALL BE PROPERLY LABELED. EXACT NAMING SHALL BE COORDINATED WITH OWNER.

⑧ ELECTRICAL KEYED NOTES:

1. IDF WALL RACK LOCATION.
2. EXTEND EXISTING BACKBOARD OR PROVIDE NEW 3/4" AC PLYWOOD FOR THE NEW MDP PANEL.

ENT FLOOR PLAN - POWER


HORIZONTAL SCALE IN FEET

BASEMENT FLOOR PLAN - POWER
SCALE: $1/4" = 1'-0"$

HORIZONTAL SCALE IN FEET



MDP (1)
EXISTING
MP



FIRST FLOOR PLAN - POWER

SCALE: 1/4" = 1'-0"

HORIZONTAL SCALE IN FEET
4 2 0 4 8 12 16

ELECTRICAL GENERAL NOTES:

1. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL MECHANICAL AND ELECTRICAL ITEMS SHOWN ON THIS DRAWING, UNLESS OTHERWISE NOTED.
2. TYPE 'MC' CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER AND LIGHTING CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
3. VERIFY EQUIPMENT LOCATIONS, CIRCUIT BREAKER, FUSE SIZES, CONDUIT SIZES, WIRE SIZES AND ROUGH-IN REQUIREMENTS FOR ALL EQUIPMENT BEING FURNISHED BY ANOTHER TRADE OR BY THE OWNER PRIOR TO ROUGHING-IN.
4. PROVIDE THE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUITING SHOWN ON THE DRAWINGS.
5. CIRCUIT NUMBERS AT EQUIPMENT AND AT HOMERUNS CORRESPOND TO PANELBOARD CIRCUIT BREAKERS (SEE PANELBOARD SCHEDULES). BRANCH CIRCUITS SHALL BE SIZED ACCORDING TO THE CIRCUIT BREAKER RATING, UNLESS OTHERWISE NOTED ON THE ELECTRICAL EQUIPMENT SCHEDULES. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ALL LOADS CONNECTED TO EACH PANELBOARD ARE BALANCED EVENLY.
6. USE #10 AWG CONDUCTORS FOR 20 AMPERE, 120 VOLT BRANCH CIRCUITS LONGER THAN 75 FEET, #8 AWG FOR 20 AMP, AND 120 VOLT BRANCH CIRCUITS LONGER THAN 150 FEET, AND #10 AWG FOR 20 AMPERE, 277 VOLT CIRCUITS LONGER THAN 150 FEET, UNLESS SPECIFICALLY NOTED OTHERWISE. THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
7. UNLESS SPECIFICALLY NOTED OTHERWISE, THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
8. RECEPTACLES INSTALLED ON THE EXTERIOR OF THE BUILDING SHALL BE LISTED AS WEATHER RESISTANT AND SHALL BE PROVIDED WITH 'EXTRA-DUTY' LISTED, WEATHERPROOF WHILE-IN-USE COVERPLATES.
9. RECEPTACLES INSTALLED WITHIN 6'-0" OF A WATER SOURCE SHALL BE 5mA GFCI TYPE.
10. ALL TELECOMMUNICATION CABLES SHALL BE INSTALLED IN CONDUIT.
11. '??' INDICATES PROVIDE FUSES IN THE SIZE RECOMMENDED BY THE EQUIPMENT MANUFACTURER. THIS INFORMATION WAS NOT PROVIDED FOR THE ELECTRICAL DESIGN.
12. TYPE 'MC' CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
13. ALL PANELBOARDS, DISCONNECTS AND DEVICES SHALL BE PROPERLY LABELED. EXACT NAMING SHALL BE COORDINATED WITH OWNER.

ELECTRICAL KEYED NOTES:

1. SMOKE DETECTOR BY BRK WITH RM-4 RELAY.

27 Park St.
Canaan, VT 05903
PROJECT NUMBER
530597


DuBois & King Inc.
Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 530597

RELEASE

RELEASE DATE

RELEASE + REVISION LOG
MARK DESCRIPTION DATE

PROJECT NORTH




FIRST FLOOR PLAN -
POWER

DRAWN JKW DATE 09.30.2025
CHECKED SMP SCALE AS NOTED
DRAWING NUMBER

CD SET
FOR BIDDING

09.30.2025

E1.5



SECOND FLOOR PLAN - POWER

SCALE: 1/4" = 1'-0"

HORIZONTAL SCALE IN FEET



ELECTRICAL GENERAL NOTES:

1. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR WIRING ALL MECHANICAL AND ELECTRICAL ITEMS SHOWN ON THIS DRAWING, UNLESS OTHERWISE NOTED.
2. TYPE 'MC' CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER AND LIGHTING CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
3. VERIFY EQUIPMENT LOCATIONS, CIRCUIT BREAKER, FUSE SIZES, CONDUIT SIZES, WIRE SIZES AND ROUGH-IN REQUIREMENTS FOR ALL EQUIPMENT BEING FURNISHED BY ANOTHER TRADE OR BY THE OWNER PRIOR TO ROUGHING-IN.
4. PROVIDE THE PROPER NUMBER OF CONDUCTORS TO ACHIEVE CIRCUITING SHOWN ON THE DRAWINGS.
5. CIRCUIT NUMBERS AT EQUIPMENT AND AT HOMERUNS CORRESPOND TO PANELBOARD CIRCUIT BREAKERS (SEE PANELBOARD SCHEDULES). BRANCH CIRCUITS SHALL BE SIZED ACCORDING TO THE CIRCUIT BREAKER RATING, UNLESS OTHERWISE NOTED ON THE ELECTRICAL EQUIPMENT SCHEDULES. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ALL LOADS CONNECTED TO EACH PANELBOARD ARE BALANCED EVENLY.
6. USE #10 AWG CONDUCTORS FOR 20 AMPERE, 120 VOLT BRANCH CIRCUITS LONGER THAN 75 FEET, #8 AWG FOR 20 AMP, AND 120 VOLT BRANCH CIRCUITS LONGER THAN 150 FEET, AND #10 AWG FOR 20 AMPERE, 277 VOLT CIRCUITS LONGER THAN 150 FEET, UNLESS SPECIFICALLY NOTED OTHERWISE. THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
7. UNLESS SPECIFICALLY NOTED OTHERWISE, THIS INCREASED WIRE SIZE SHALL BE REQUIRED FOR THE ENTIRE LENGTH OF THE CIRCUIT.
8. RECEPTACLES INSTALLED ON THE EXTERIOR OF THE BUILDING SHALL BE LISTED AS WEATHER RESISTANT AND SHALL BE PROVIDED WITH 'EXTRA-DUTY' LISTED, WEATHERPROOF WHILE-IN-USE COVERPLATES.
9. RECEPTACLES INSTALLED WITHIN 6'-0" OF A WATER SOURCE SHALL BE 5mA GFCI TYPE.
10. ALL TELECOMMUNICATION CABLES SHALL BE INSTALLED IN CONDUIT.
11. '??' INDICATES PROVIDE FUSES IN THE SIZE RECOMMENDED BY THE EQUIPMENT MANUFACTURER. THIS INFORMATION WAS NOT PROVIDED FOR THE ELECTRICAL DESIGN.
12. TYPE 'MC' CABLE WITH INTEGRAL GROUND WIRE MAY BE UTILIZED FOR POWER CIRCUITS ONLY WHERE COMPLETELY CONCEALED.
13. ALL PANELBOARDS, DISCONNECTS AND DEVICES SHALL BE PROPERLY LABELED. EXACT NAMING SHALL BE COORDINATED WITH OWNER.

PROJECT
Alice Ward Library

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King Inc.


Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 530597

RELEASE

RELEASE DATE

MARK	DESCRIPTION	DATE

PROJECT NORTH



DRAWING NAME


SECOND FLOOR PLAN -
POWER

DRAWN	JKW	DATE	09.30.2025
CHECKED	SMP	SCALE	AS NOTED
DRAWING NUMBER			

CD SET
FOR BIDDING

09.30.2025

E1.6



PROJECT
Alice Ward Library

27 Park St.
Canaan, VT 05903

PROJECT NUMBER
530597

CONSULTANTS
DuBois & King Inc.
Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 530597

RELEASE

RELEASE DATE

RELEASE + REVISION LOG
MARK DESCRIPTION DATE

PROJECT NORTH




DRAWING NAME

ELECTRICAL DETAILS


DRAWN JKW DATE 09.30.2025
CHECKED SMP SCALE AS NOTED
DRAWING NUMBER

E5.1



TELECOM RISER KEYED NOTES:

1. PROVIDE CAT6 48-PORT UNIVERSAL RJ45/110 PATCH PANELS AS REQUIRED FOR QUANTITY OF DATA DROPS WITH 20% SPARE CAPACITY. PROVIDE ALL INFRASTRUCTURE INCLUDING NETWORK SUPPORT RACKS, CABLE/LADDER TRAY, GROUNDING/BONDING, POWER RECEPTACLES AND PLYWOOD BACKBOARD AS REQUIRED. UPS UNITS ARE PROVIDED BY OTHERS. PROVIDE 3/4" C FIRE RATED PLYWOOD PAINTED BLACK ALL AROUND DATA ROOMS. CONTRACTOR SHALL COORDINATE WITH OWNER'S I.T. PERSONNEL FOR EXACT REQUIREMENTS PRIOR TO PURCHASING AND CONSTRUCTION.
2. CONTRACTOR SHALL COORDINATE EXACT REQUIREMENTS AND CONFIGURATION OF FLOOR BOX WITH OWNER PRIOR TO ROUGH-IN AND PURCHASING OF DEVICE. PROVIDE (2) DUPLEX RECEPTACLES, (2) DATA/1 VOICE PORTS, (2) HDMI PORTS.
3. PROVIDE PLUENUM RATED, CATEGORY 6 UTP CABLE (COLORED 'BLUE' FOR PHONE/DATA, 'GREEN' FOR SECURITY, 'YELLOW' FOR WIRELESS ACCESS POINTS) FROM OUTLET TO PATCH PANEL. '2D' DENOTES TWO DATA RJ45 JACKS AND TWO CATEGORY 6 UTP CABLES. WIRELESS ACCESS POINTS SHALL HAVE TWO DATA DROPS PER DEVICE LOCATION.
4. ELECTRICAL CONTRACTOR SHALL PROVIDE ALL HOMERUNS FROM DEVICE TO RESPECTIVE FLOOR IDF CLOSET. CONTRACTOR SHALL TERMINATE ALL HOMERUNS AT DEVICE END AND AT PATCH PANELS WITHIN IDF CLOSET. PROVIDE SERVICE LOOPS AT BOTH PATCH PANEL AND DEVICE END. PROVIDE 10'-FT OF EXTRAL LENGTH, LOOPED, IN THE IDF CLOSET TO ALLOW FOR FUTURE ADJUSTMENT OF PATCH PANELS. CERTIFY AND TEST ALL CABLES IN ACCORDANCE WITH TIA/EIA STANDARDS. PROVIDE REPORT TO OWNER. WIRE PUNCH/TERMINATION PROTOCOL SHALL BE VERIFIED WITH OWNER FOR VOICE OVER INTERNET PROTOCOL (VOIP) PRIOR TO INSTALL. COORDINATE WITH OWNER'S I.T. PERSONNEL FOR LABELING CONVENTIONS OF JACKS AND CABLE.
5. NOT USED
6. PROVIDE 12U PASSIVE WALL MOUNTED ENCLOSURE, (1) PER FLOOR, EQUAL TO HUBBELL #HS224. DIMENSIONS-20" DEEP AND 24" HIGH. PROVIDE MOUNTING SUPPORT AND GROUNDING TO TIA STANDARDS.
7. PROVIDE 2U CABLE MANAGEMENT, EQUAL TO HUBBELL # HM24C TYPICAL.
8. PROVIDE 48 PORT CATEGORY 6 PATCH PANELS, EQUAL TO HUBBELL # HP648 TYPICAL.
9. PROVIDE 2U, FIBER ENCLOSURE, EQUAL TO HUBBELL # FCR2U6SP WITH TWO OCSPLCD12M4 MULTI MODE FIBER SPLICE CASSETTES, AND TERMINATE ALL MULTIMODE FIBER STRANDS.



NOTES:

1. ALL MOUNTING HEIGHTS SHALL BE MEASURED FROM THE FINISHED FLOOR TO THE CENTER OF THE DEVICE UNLESS OTHERWISE INDICATED.
2. DEVICES SHALL BE INSTALLED ON A COMMON HORIZONTAL CENTERLINE WHEN GROUPED TOGETHER.
3. ALL DEVICES SHALL BE INSTALLED AT MOUNTING HEIGHTS AS INDICATED ON THIS DETAIL UNLESS OTHERWISE NOTED ON THE PLANS.
4. ALL DEVICES SHOWN ON THIS DETAIL, MAY NOT BE PRESENT ON THIS PROJECT. THIS IS A TYPICAL DEVICE MOUNTING HEIGHT DETAIL. EACH PROJECT MAY HAVE MORE OR LESS VARIETY OF DEVICES AND SYSTEMS.


TYPICAL DEVICE MOUNTING HEIGHT DETAIL

N.T.S.

FEEDER SCHEDULE - 600V MAXIMUM (COPPER)			
TAG	DESCRIPTION	TAG	DESCRIPTION
15.3	3#12, #12G-3/4"	250.3	3-250KCMIL, #4G-2 1/2"
15.4	4#12, #12G-3/4"	250.4	4-250KCMIL, #4G-2 1/2"
20.3	3#12, #12G-3/4"	300.3	3-350KCMIL, #4G-2 1/2"
20.4	4#12, #12G-3/4"	300.4	4-350KCMIL, #4G-3"
30.3	3#10, #10G-3/4"	400.3	3-500KCMIL, #3G-3"
30.4	4#10, #10G-3/4"	400.4	4-500KCMIL, #3G-3"
40.3	3#8, #10G-3/4"	500.3	2 SETS OF 3-250KCMIL, #2G-2 1/2"
40.4	4#8, #10G-3/4"	500.4	2 SETS OF 4-250KCMIL, #2G-2 1/2"
50.3	3#6, #10G-3/4"	600.3	2 SETS OF 3-350KCMIL, #1G-2 1/2"
50.4	4#6, #10G-3/4"	600.4	2 SETS OF 4-350KCMIL, #1G-3"
60.3	3#4, #10G-1"	800.3	2 SETS OF 3-500KCMIL, #1/0G-3"
60.4	4#4, #10G-1 1/4"	800.4	2 SETS OF 4-500KCMIL, #1/0G-3 1/2"
70.3	3#4, #8G-1"	900.3	3 SETS OF 3-350KCMIL, #2/0G-2 1/2"
70.4	4#4, #8G-1 1/4"	900.4	3 SETS OF 4-350KCMIL, #2/0G-3"
80.3	3#3, #8G-1 1/4"	1000.3	3 SETS OF 3-400KCMIL, #2/0G-2 1/2"
80.4	4#3, #8G-1 1/4"	1000.4	3 SETS OF 4-400KCMIL, #2/0G-3"
90.3	3#2, #8G-1 1/4"	1200.3	4 SETS OF 3-350KCMIL, #3/0G-2 1/2"
90.4	4#2, #8G-1 1/4"	1200.4	4 SETS OF 4-350KCMIL, #3/0G-3"
100.3	3#2, #8G-1 1/4"	1600.3	5 SETS OF 3-500KCMIL, #4/0G-3"
100.4	4#2, #8G-1 1/4"	1600.4	5 SETS OF 4-500KCMIL, #4/0G-3 1/2"
125.3	3#1, #6G-1 1/4"	2000.3	6 SETS OF 3-500KCMIL, #1-250KCMILG-3"
125.4	4#1, #6G-1 1/4"	2000.4	6 SETS OF 4-500KCMIL, #1-250KCMILG-3 1/2"
150.3	3#1/0, #6G-1 1/2"	2500.3	7 SETS OF 3-500KCMIL, #1-350KCMILG-3"
150.4	4#1/0, #6G-1 1/2"	2500.4	7 SETS OF 4-500KCMIL, #1-350KCMILG-3 1/2"
175.3	3#2/0, #6G-2"	3000.3	8 SETS OF 3-500KCMIL, #1-400KCMILG-3"
175.4	4#2/0, #6G-2"	3000.4	8 SETS OF 4-500KCMIL, #1-400KCMILG-3 1/2"
200.3	3#3/0, #6G-2"	4000.3	11 SETS OF 3-500KCMIL, #1-500KCMILG-3"
200.4	4#3/0, #6G-2"	4000.4	11 SETS OF 4-500KCMIL, #1-500KCMILG-3 1/2"
225.3	3#4/0, #4G-2"		
225.4	4#4/0, #4G-2 1/2"		


TELECOMMUNICATIONS RISER

N.T.S.








POWER RISER

N.T.S.



CD SET
FOR BIDDING
09.30.2025



PROJECT
Alice Ward Library

27 Park St.
Canaan, VT 05093

PROJECT NUMBER
530597

CONSULTANTS

DuBois & King Inc.


Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 530597

RELEASE

RELEASE DATE

RELEASE + REVISION LOG	MARK	DESCRIPTION	DATE

PROJECT NORTH



DRAWING NAME

ELECTRICAL DETAILS

DRAWN	JKW	DATE	09.30.2025
CHECKED	SMP	SCALE	AS NOTED
DRAWING NUMBER			

CD SET
FOR BIDDING

09.30.2025

E5.2

LIGHT FIXTURE SCHEDULE

TYPE	DESCRIPTION	MANUFACTURER	MODEL	LUMENS	TEMP (K)	WATTAGE	VOLTAGE	NOTES
D	6IN Adjustable Wafer	JUNO LIGHTING	WF6 ALO20 SWW5 90CRI MVOLT 2700K	1014	2700	12.5	120	
EBU	Emergency Battery Unit	LITHONIA	ELM4L	-	-	-	120	
L4	GR20240927-09-03-47-ZP5INCH PRISM-HE55-4FT	LUMENWERX	SHLUSS-D-SMPO-SW-90CRI-750LMF-35K-4FT	3000	3500	26.4	120	
L8	GR20240927-09-03-47-ZP5INCH PRISM-HE55-4FT	LUMENWERX	SHLUSS-D-SMPO-SW-90CRI-750LMF-35K-4FT	3000	3500	52.8	120	
R1	Decorative Ring Light	TBD	TBD	TBD	TBD	TBD	120	
R2	Two Wet Location Remote Aimable Battery Powered LED Emergency Lighting Heads	LITHONIA	ERE-T-WP-SQ	-	-	2	120	
S	Contractor LED Single Strip, 48", 4000 Lumens, 120-347V, 4000K, 80 CRI	LITHONIA	CSS L48 4000LM UVOLT 40K 80 CRI	4819	4000	37.89	120	
S1	Decorative Stair Light	TBD	TBD	TBD	TBD	TBD	120	
ST	Luminaire LED Dim. Vandal Resistant surface mount 1x2"	LUMINAIRE LED	TS19 24IN 25W FAM7 40K OP	16	4000	26.3	120	
SW	Slot 4 Wall Indirect/Direct 8FT 90CRI 35K 800LMF Lambertian I1000LMF Lambertian Flush Lens	MARK ARCHITECTURAL LIGHTING	S4WID 8FT 90CRI 35K 800LMF STD I1000LMF AS FLL	5743	3500	50.09	120	
UC	Under Cabinet Light	KELVIX	EZ-502-I-TBD-35K-TBD	TBD	3500	TBD	120	
V	Vanity Light	BROWNLEE	5165-24-BN-H13-35K	1663	3500	13	120	
W1	Decorative Wall Pack	LUMENWERX	UBIW-DI-HLO-TIO-SW-90-500-750-35-4FT	5002	3500	48.49	120	WITH PHOTOCELL
W2	Exterior Wall Pack	RAB	WPLED10N	1287	4000	10	120	WITH PHOTOCELL
X1	Exit Sign	LITHONIA	ECRG-HO-SQ-M6	-	-	4	120	WITH REMOTE HEADS

PANEL 'NP', 400 AMP, 120/240 VOLT, 1-PHASE, 3-WIRE & GND								
INTERRUPTING CAPACITY: 10,000 AMPS RMS SYM MAIN: 225A M.C.B. MOUNTING: SURFACE								
LOAD DESCRIPTION	CB	CIRC NO.	KVA LOAD	CIRC NO.	CB	LOAD DESCRIPTION		
LOAD DESCRIPTION	CB	CIRC NO.	A	B	CB	LOAD DESCRIPTION		
BASEMENT LTG	1-20	1	0.45	0.72	2	1-20	RCPTS	
BASEMENT EXT LTG	1-20	3	0.04	0.72	4	1-20	RCPTS	
FIRST FLOOR LTG	1-20	5	0.50	0.18	6	1-20	RCPTS	
RCPTS	1-20	7	0.18	0.54	8	1-20	RCPTS	
RCPTS	1-20	9	0.54	0.36	10	1-20	RCPTS	
RCPTS	1-20	11	0.18	0.18	12	1-20	RCPTS	
RCPTS	1-20	13	0.36	0.18	14	1-20	REFRIGERATOR RCPT*	
RCPTS	1-20	15	0.54	0.72	16	1-20	RCPTS	
RCPTS	1-20	17	0.72	0.18	18	1-20	RCPTS	
EH2	2-20	19	1.50	0.76	20	2-20	EH-1	
SPACE	1-20	23	0.00	2.04	24	2-20	HP-2	
HP-1	2-20	25	2.04	2.04	26	2-20	HP-2	
FC-1	2-20	27	2.04	3.00	28	2-20	HP-2	
FC-3	2-20	29	0.28	3.00	30	2-20	FC-2	
FC-3	2-20	31	0.28	0.28	32	2-20	FC-2	
EH4	2-20	33	0.28	0.28	34	2-20	EH-3	
EDH1	2-20	35	0.28	1.50	36	2-20	EDH-2	
WH-1	2-20	37	0.76	1.50	38	2-20	EDH-2	
SECOND FLOOR LTG	1-20	49	0.50	0.08	50	1-20	FIRST FLOOR LTG	
SECOND FLOOR LTG	1-20	51	0.50	0.18	52	1-20	EXTERIOR RCPT	
RCPTS	1-20	53	0.54		54	1-20	PIT RCPT	
RCPTS	1-20	55	0.18		56	1-20	EXTERIOR RCPT	
RANGE	2-20	57	16.67		58	1-20	ELEVATOR LIFT	
RANGE	2-20	59	16.67	0.50	60	1-20	STAIR LTG	
SPARE	1-20	61	2.08		62	1-20	SPARE	
SPARE	1-20	63	2.08		64	1-20	SPARE	
SPARE	1-20	65			66	1-20	SPARE	
SPARE	1-20	67			68	1-20	SPARE	
SPARE	1-20	69			70	1-20	SPARE	
SPARE	1-20	71			72	1-20	SPARE	
SPARE	1-20	73			74	1-20	SPARE	
SPARE	1-20	75			76	1-20	SPARE	
SPARE	1-20	77			78	1-20	SPARE	
SPARE	1-20	79			80	1-20	SPARE	
SPARE	1-20	81			82	1-20	SPARE	
SPARE	1-20	83			84	1-20	SPARE	
PHASE A	42.00	KVA	TOTAL LOAD 63.65 KVA			NOTES: CIRCUITS DENOTED WITH A ** ARE TO BE GFCI TYPE BREAKERS.		
PHASE B	41.66	KVA						

MECHANICAL & PLUMBING EQUIPMENT ELECTRICAL CONNECTION SCHEDULE									
EQUIPMENT TAG	HP	AMPS (MCA)	VOLT	PHASE	DEVICE	PANEL CIRCUIT No.	CIRCUIT BREAKER		REMARKS
							AMP	POLE	
HP-1	17.00	240	1		PROVIDE WP DISCONNECT	NP-25,27	25	2	2#10, 1#10, 3/4"
HP-2	17.00	240	1		PROVIDE WP DISCONNECT	NP-24,26	25	2	2#10, 1#10, 3/4"
HP-3	25.00	240	1		PROVIDE WP DISCONNECT	NP-28,30	30	2	2#10, 1#10, 3/4"
FC-1	2.30	240	1		PROVIDE DISCONNECT	NP-29,31	15	2	2#12, 1#12, 3/4"
FC-2	2.30	240	1		PROVIDE DISCONNECT	NP-32,34	15	2	2#12, 1#12, 3/4"
FC-3	2.30	240	1		PROVIDE DISCONNECT	NP-33,35	15	2	2#12, 1#12, 3/4"
EH-1	6.30	240	1		PROVIDE DISCONNECT	NP-20,22	15	2	2#12, 1#12, 3/4"
EH-2	12.50	240	1		PROVIDE DISCONNECT	NP-19,21	20	2	2#12, 1#12, 3/4"
EH-3	12.50	240	1		PROVIDE DISCONNECT	NP-36,38	20	2	2#12, 1#12, 3/4"
EH-4	6.30	240	1		PROVIDE DISCONNECT	NP-37,39	15	2	2#12, 1#12, 3/4"
EDH-1	4.20	240	1		PROVIDE DISCONNECT	NP-41,43	20	2	2#12, 1#10, 3/4"
EDH-2	12.50	240	1		PROVIDE DISCONNECT	NP-40,42	25	2	2#10, 1#10, 3/4"
EDH-3	12.50	240	1		PROVIDE DISCONNECT	NP-44,46	25	2	2#10, 1#10, 3/4"
EF-1	0.11	120	1		PROVIDE DISCONNECT	NP-48	15	1	2#12, 1#12, 3/4"
WH-1	16.67	240	1		PROVIDE DISCONNECT	NP-45,47	20	2	2#12, 1#12, 3/4"

SEAL
STATE OF VERMONT
NO. 134688
ELECTRICAL
PROFESSIONAL
ENGINEER
PROJECT
Alice Ward Library
27 Park St.
Canaan, VT 05903
PROJECT NUMBER
530597
CONSULTANTS
DuBois & King Inc.
Building Services Division
Bedford, NH
MEP/FP Engineers
603.444.6578
Project # 53